

# FARMAX RC

## Row Crop Tires in USA

 Agriculture  Row Crop  Radial



- 1 **(D-RATED (40 MPH) TIRES)** Improved transportation speed
- 2 **(HIGHER ANGLE AND LUG OVERLAP AT CENTER)** Better roadability and stability
- 3 **(ROUNDED SHOULDER)** Reduced crop damage
- 4 **(HIGHER NUMBER OF LUGS)** Superior traction
- 5 **(STRONG CARCASS AND BEAD)** Higher load carrying capacity

### Sizes

Sizes	RIM
380/105R50	W11, W12, W13

### Table of Specifications

Sizes	RIM	Infl tire dimension		SLR	RC	SRI	LI/SS	Infl. press.	Recommend load, kg (lbs)					
		SW	OD						Speed, km/h (mph)					
		mm	mm						Recommended Load					
		in	in						10	25	40	50	65	70
								bar	6	16	25	31	40	43
								psi	6	16	25	31	40	43
380/105R50	W11, W12, W13	400	2050	952	6144	-	168D/171A8	0.8	3110	2450	2270	2170	2070	1880
								12	6850	5400	5000	4780	4560	4140
								1.6	4650	3670	3390	3260	3100	2820
								23	10240	8080	7470	7180	6830	6210
								2.4	5900	4660	4300	4130	3930	3580
								35	13000	10260	9470	9100	8660	7890
								3.6	7470	5900	5450	5230	4980	4530
								52	16450	13000	12000	11520	10970	9980
								4.0	7950	6280	5800	5570	5300	4820
								58	17510	13830	12780	12270	11670	10620
								4.4	8400	6640	6130	5880	5600	5100
								64	18500	14630	13500	12950	12330	11230