

SWRİL DİFÜZÖR
SWRIL DIFFUSER
РОТАЦИОННЫЙ – ДИФФУЗОР

ESS-U

69

Seçim Tablosu

Table of Selection

Таблица Выбора

Ölçüler (mm) ∅	Debi V (m ³ /h)	Atış Mesafesi L (m)		Basınç Kaybı ΔP(Pa)	Ses Seviyesi dB(A)
Dimensions (mm) ∅	Air Flow V (m ³ /h)	Shoot Length L (m)		Pressure Loss ΔP(Pa)	Sound Level dB(A)
Размер (мм) ∅	Объем Воздуха V (м ³ /ч)	Дистанция Выброса Воздуха L(м)		Потеря Давления ΔP(Pa)	Показатели Шума dB (A)
		V _L = 0.25 m/s	V _L = 0.10 m/s		
		V _L = 0.25 m/s	V _L = 0.10 m/s		
		V _L = 0.25 m/c	V _L = 0.10 m/c		
300	140	1,40	3,10	17	31
	180	1,75	3,90	27	37
	220	2,15	4,90	38	42
	260	2,50	5,60	52	47
	300	3,00	6,60	70	50
400	170	1,15	2,90	7	<20
	240	1,70	4,30	14	24
	310	2,15	5,50	24	33
	380	2,60	6,70	35	38
	450	3,20	8,00	52	44
500	220	1,30	3,30	7	<20
	300	1,80	4,50	11	25
	320	2,20	5,70	17	31
	460	2,70	7,00	25	37
	540	3,20	8,20	38	42
595	2990	1,50	3,75	6	20
	375	2,05	5,05	11	28
	460	2,50	6,25	14	32
	545	3,00	7,50	20	37
	630	3,50	8,70	28	42