

Sound column with 100V line transformer

**BENEFITS**

Optimised for voice reproduction and transmission with maximum clarity.

The configuration of its loudspeakers achieves the concentration of the sound in the area of the audience to which it is directed.

Avoids feedback and therefore increases the amplification capacity of the sound system.

Maintenance-free for long life, enclosure and mesh made of aluminium to prevent rust.

IP-44 protection for outdoor use under cover.

**Applications:**

Installations for speech and background music. Especially in rooms with high reverberation, such as religious centres, conference rooms, theatres.

**Technical data:**

Power 40/20 W RMS @ 100 V

8 x 2.5" speakers

IP-44 protection



**TOWER-40TB**

FEATURES	Sound column with line transformer
POWER SUPPLY	40 W RMS
SPEAKERS	8 x 2.5"
RESPONSE	170-15,000 Hz
IMPEDANCE	40 W RMS@100 V (250 Ohm) 20 W RMS@100 V (500 Ohm)
SENSIBILITY	93 dB at 1 W/1 m
DISPERSION	155° H x 110° V (1 kHz) 180° H x 70° V (4 kHz)
PROTECTION	IP44
MATERIAL	Aluminium enclosure Aluminium mesh
COLOUR	White (RAL 9016)
DIMENSIONS	10.6 x 69 x 7.5 cm depth
WEIGHT	3.5 kg
ACCESSORIES	Fastening brackets