

# ENSTO

Heating cable, self-regulating

EFPO20

Code	EFPO20
GTIN	6418677639180
Name	Heating cable, self-regulating OptiHeat Self-regulating heating cable 20W/m/10°C, 230V, dim 5,8x14,1mm, black, min bending radius 25 mm, min installation temp -5°C, drum 300-1000m, earthed.
Description	Self-regulating heating cable for frost protection of rainwater systems, roofs and small stairs. Power of the cable, on pipe is about 20W/m/10°C and 26W/m/0°C, in water 40W/m/0°C. The outer jacket of the cable is UV-protected so it can be exposed to sun light. The cable is available on drums so it is easy to make a suitable frost protection solution. It is recommended to use always a thermostat, e.g. ECO910. For the fixing and connection of the cable, there is a wide range of accessories.
Vendor	Ensto Building Systems Finland Oy



## Technical specification

### Electrical values

Rated voltage:	230 V
Power at 10°C:	20 W/m

### Ratings

Installation temperature min:	-60 °C
Operating temperature max:	65 °C
Min. bending radius:	25 mm

### Dimensions

Length:	1000 mm
Width:	14.1 mm
Height:	5.8 mm
Weight:	0.108 kg
Weight kg/m:	0.108 kg/m

## Others

ETIM Class:	EC000339
-------------	----------

## ETIM Technical specification

---

### etim

Cable type:	Self-limiting parallel
Max. hold temperature:	65 °C
Heating capacity:	20 W
Screening:	Braiding
Nominal voltage:	230 V
Height:	5.8 mm
Width:	14.1 mm
Length:	1000 m
Colour:	Black
Application:	Gutter/roof

## Packaging

---

### Plastic bag (Default package)

Package size:	1 mtr
Depth:	1000 mm
Width:	14.1 mm
Height:	5.8 mm
Weight:	0.133 kg
Volume:	0.08178 l

### Carton

Package size:	1000 mtr
Depth:	750 mm
Width:	750 mm
Height:	364 mm
Weight:	133.05 kg
Volume:	204.75 l

### Pallet package

Package size:	4000 mtr
Weight:	552.2 kg