



TECHNICAL DATA SHEET No 617

1K SPECIAL PAINT ALLOY 310

GENERAL TECHNICAL DESCRIPTION

One component alkyd paint.

Easy application process.

Provides high gloss and durable finish.

Fast drying.

Ideal for alloy wheel refinish.

SURFACE

Suitably prepared HB BODY primed surfaces

PRETREATMENT/CLEANING OF SUBSTRATE



Clean substrate using a soft cloth and 770 ANTISIL NORMAL / 771 ANTISIL FAST DEGREASER.

Make sure the surface is first wiped dry and then air dried.

PRODUCT APPLICATION



20 - 25% 750 SYNT or 767 NITRO THINNER / REDUCER



Ready to spray: 20 - 25 s DIN 4 / 20°C (68°F)



1.2 – 1.4 mm 1.7 - 2.2 bar (25 - 32 psi) 2x coats = 35 - 40 μm (1.4 - 1.6 mil)



15 - 20 min / 23°C (73°F) Flash off time between coats



12 - 15 h / 23°C (73°F)

SPECIFIC GRAVITY

1 ± 0.02 g/cm³

SOLID CONTENT

44 ± 2% Weight

VOC (2004/42/EC)

This product is a special refinish product based on its ingredients and its properties. The maximum VOC content in this category is 840 g/L. The VOC content in the ready for use form of this product is 840 g/L. 2004/42/IIB(e)(840)840

THEORETICAL COVERAGE

 $8-10~m^2/l$ at 35~micron (1.4 mil) dry film thickness

CLEANING OF EQUIPMENT

Clean after final use with 767 NITRO Thinner / Reducer

REMARKS

- Application only with the recommended thinners / reducers.
- Do not use at temperatures below 15°C (59°F).

STORAGE SHELF LIFE

 Guaranteed shelf life of 24 months in unused original containers stored in a cool place (5 - 25°C) (41 - 77°F).



Always wear protective equipment



Follow the application instructions mentioned in this TDS

For professional use only. The information displayed on this sheet has been carefully selected through a series of laboratory investigations. It is based on our best knowledge at the time of issue. The data is given for information purposes only. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for newer updates or further information if needed for his intended purpose. The intellectual property of this product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

JULY 2024