

DH-PFS3005-5GT-L

5-Port Desktop Gigabit Ethernet Switch



- Compact design: Miniature size and light weight make it easy to deploy
- Plug and play: No configuration required
- Green technology: Adopts high quality environmentally friendly plastics
- 7x24H: Stable performance for long-term operation

System Overview

5 × 10/100/1000 Mbps adaptive ports, highly integrated design, compact, portable, easy to operate, suitable for small and medium office and home networks.

Technical Specification

Performance

Layer Layer 2

Managed No

Hardware

Standard Power Supply Yes

PoE No

Ethernet Port 5

Ethernet Port Rate 1 Gbps

Power Supply 5V/1A DC

Operating Temperature -10°C to 55°C (14°F to 131°F)

Operating Humidity 10%–90%

Storage Temperature -20°C to 70°C (-4°F to 158°F)

Storage Humidity 10%–90%

Power Consumption Idling: 0.67W
Full load: 1.6W

Performance

Switching Capacity 10 Gbps

Packet Forwarding Rate 7.44 Mpps

Packet Buffer Memory 1.5 Mbit

MAC Table Size 2K

Standards Compliance IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE802.3x

Application

The product is applicable to small and medium office and home networks.

General

ESD	Air discharge: 8kV Contact discharge: 4kV
Thunderproof	Common mode: 2kV
Net Weight	0.09 kg (0.20 lb)
Gross Weight	0.2 kg (0.44 lb)
Dimensions	125 mm × 65 mm × 22 mm (4.92" × 2.56" × 0.87")
Packaging Dimensions	128 mm × 77 mm × 78 mm (5.04" × 3.03" × 3.07")

Dimensions (mm[inch])

