



**ALLIANCE
 AGRICULTURE**

TRA: **R-1W**
 Speed Rating: **D**



SPECIAL COMPOUND STUBBLE GUARD

The high speed 'D' rated AGRI STAR II comes with a Stratified Layer technology (SLT) - a unique combination of two layers: The top layer with a single angle profile and bottom layer with a multi-angle profile. After 40% wear of the tire, bottom layer of the lug comes in contact with the ground which leads to increased contact area at the central portion. This leads to better roadability and performance of the tire. The increased amount of rubber volume in AGRI STAR II enhances its stiffness that results in better wear resistance.

85 Series - 420/85R30(16.9R30)

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
		SW mm	OD mm					Speed						
								Tractor Applications						
								Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	65 kmph
420/85R30(16.9R30)	W15LX30 W14LX30	443	1476	675	4383	140D	0.8	3680	2400	1896	1840	1752	1680	1600
							1.2	4738	3090	2441	2369	2256	2163	2060
							1.4	5290	3450	2726	2645	2519	2415	2300
							1.6	5750	3750	2963	2875	2738	2625	2500

For ATC Tires Pvt Limited



Dan Steltmann
 Chief Technology Officer

