


NEK2168GK



ENGINEERING CODE
959FA51



REFRIGERANT
R-404A



POWER SUPPLY
220-240 V 50 Hz



APPLICATION
LBP



MOTOR TYPE
CSIR



STANDARD
EN12900



COOLING CAPACITY
384 W



EFFICIENCY
0.96 W/W

DATA

GENERAL DATA

Model	NEK2168GK
Type	Hermetic Reciprocating
Technology	ON/OFF
Compressor Application	LBP
Expansion Device	Capillary Tube or Expansion Valve
Compressor Cooling	Fan/220
HP	3/4
Starting Torque	HST
Plant	SLOVAKIA

ELECTRICAL DATA

Start Winding Resistance	13.2 Ω at 25°C
Run Winding Resistance	4.0 Ω at 25°C

MECHANICAL DATA

Displacement	14.28 cm³
Oil Charge	350 ml
Oil Type	ESTER
Oil Viscosity	ISO22
Weight	11.6 Kg

ELECTRICAL COMPONENTS

Start Capacitor	88-108 µf/330 V
CSR CSIR BOX	No
Starting Device Type	RELAY
Starting Device Description	9660A-XX-145*
Overload Protection	T0624/G9

EXTERNAL CHARACTERISTICS

Base Plate	SMALL
Tray Holder	NO

Connector	Internal Diameter	Shape	Material
Suction	8.1 mm	SLANTED 42°	COPPER
Discharge	6.1 mm	STRAIGHT	COPPER
Process	6.1 mm	SLANTED 42°	COPPER

PERFORMANCE

TESTED CONDITIONS

Tested Refrigerant	R-404A
Tested Application	LBP
Tested Standard	EN12900
Tested Cooling	Fan
Tested Voltage	220 V
Tested Frequency	50 Hz
Refrigerant Temperature	Dew

RATED POINTS

Condensing Temperature °C	Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
40	-35	384	0.96	399	-	10.39
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.						

PERFORMANCE CURVE

Condensing Temperature 35°C

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-40	319	0.95	337	-	8.10
-35	424	1.10	386	-	10.82
-30	553	1.24	445	-	14.18
-25	705	1.38	511	-	18.18
-20	880	1.52	581	-	22.83
-15	1077	1.65	653	-	28.14
-10	1295	1.79	725	-	34.13
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.					

PERFORMANCE CURVE

Condensing Temperature 45°C


Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-40	256	0.72	353	-	7.39
-35	343	0.85	406	-	9.94
-30	452	0.96	471	-	13.13
-25	581	1.06	546	-	16.98
-20	729	1.16	627	-	21.48
-15	897	1.26	714	-	26.66
-10	1083	1.35	802	-	32.53
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.					

PERFORMANCE CURVE

Condensing Temperature 55°C

Evaporating Temperature °C	Cooling Capacity W	Efficiency W/W	Power Consumption W	Current A	Gas Flow Rate kg/h
-30	351	0.74	473	-	11.98
-25	455	0.82	554	-	15.63
-20	575	0.89	645	-	19.95
-15	712	0.96	742	-	24.95
-10	865	1.02	844	-	30.64
Test Condition: Subcooling 0 K, Return Gas 20 °C. Data are an indication of performance based simulation.					

ENVELOPE



EXTERNAL DIMENSIONS

