



*Specialized in chemicals*

Hefei TNJ Chemical Industry Co.,Ltd.

D1508 Xincheng Business Center,

Qianshan Rd. Hefei 230022 China

Tel : (0086) 551 65418677

Fax: (0086) 551 65418697

Email: info@tnjchem.com

Site: www.tnjchem.com

## Material Safety Data Sheet

### Ethylenediamine MSDS

#### Section 1: Chemical Product and Company Identification

**Product Name:** Ethylenediamine

**Catalog Codes:** SLE2005, SLE1237

**CAS#:** 107-15-3

**RTECS:** KH8575000

**TSCA:** TSCA 8(b) inventory: Ethylenediamine

**CI#:** Not available.

**Synonym:** 1,2-Diaminoethane

**Chemical Formula:** C<sub>2</sub>H<sub>8</sub>N<sub>2</sub>

**Contact Information for Emergency:** (0086) 551 65418677

**Hefei TNJ Chemical Industry Co.,Ltd.**

D1508 Xincheng Business Center

Qianshan Road, Hefei

230004Anhui

China

Tel : (0086) 551 65418677

Fax: (0086) 551 65418697

Email: info@tnjchem.com

Site: www.tnjchem.com

#### Section 2: Composition and Information on Ingredients

##### Composition:

Name	CAS # %	By Weight
Ethylenediamine	107-15-3	100

**Toxicological Data on Ingredients:** Ethylenediamine: ORAL (LD50): Acute: 500 mg/kg [Rat]. 470 mg/kg [Guinea pig]. DERMAL (LD50): Acute: 750 mg/kg [Rabbit]. VAPOR (LC50): Acute: 424.3 ppm 4 hour(s) [Mouse].

### Section 3: Hazards Identification

#### Potential Acute Health Effects:

Extremely hazardous in case of skin contact (corrosive, irritant, permeator), of eye contact (irritant), of ingestion, of inhalation. Very hazardous in case of skin contact (sensitizer). Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Severe over-exposure can result in death. Inflammation of the eye is characterized by redness, watering, and itching. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

#### Potential Chronic Health Effects:

Extremely hazardous in case of skin contact (corrosive, irritant, permeator), of eye contact (irritant), of ingestion, of inhalation. Very hazardous in case of skin contact (sensitizer). CARCINOGENIC EFFECTS: Not available.

MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY:

Not available. The substance is

toxic to kidneys, lungs, liver, mucous membranes. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection. Repeated exposure to an highly toxic material may produce general deterioration of health by an accumulation in one or many human organs. Repeated or prolonged inhalation of vapors may lead to chronic respiratory irritation.

### Section 4: First Aid Measures

#### Eye Contact:

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Do not use an eye ointment. Seek medical attention.

#### Skin Contact:

If the chemical got onto the clothed portion of the body, remove the contaminated clothes as quickly as possible, protecting your own hands and body. Place the victim under a deluge shower. If the chemical got on the victim's exposed skin, such as the hands : Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. Cold water may be used. If irritation persists, seek medical attention. Wash contaminated clothing before reusing.

#### Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

**Inhalation:** Allow the victim to rest in a well ventilated area. Seek immediate medical attention.

#### Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation.

**WARNING:** It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.

#### Ingestion:

Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation.

Seek immediate medical attention.

**Serious Ingestion:** Not available.

## Section 5: Fire and Explosion Data

**Flammability of the Product:** Flammable.

**Auto-Ignition Temperature:** 385°C (725°F)

**Flash Points:** CLOSED CUP: 34°C (93.2°F).

**Flammable Limits:** LOWER: 4.2%

**Products of Combustion:** These products are carbon oxides (CO, CO<sub>2</sub>), nitrogen oxides (NO, NO<sub>2</sub>...).

**Fire Hazards in Presence of Various Substances:** Flammable in presence of open flames and sparks, of heat, of oxidizing materials.

**Explosion Hazards in Presence of Various Substances:**

Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

**Fire Fighting Media and Instructions:**

Flammable liquid, soluble or dispersed in water. SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use alcohol foam, water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.

**Special Remarks on Fire Hazards:** Not available.

**Special Remarks on Explosion Hazards:** Not available.

## Section 6: Accidental Release Measures

**Small Spill:**

Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.

**Large Spill:**

Flammable liquid. Corrosive liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources. Call for assistance on disposal. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

## Section 7: Handling and Storage

**Precautions:**

Keep locked up Keep container dry. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapour/spray. Never add water to this product In case of insufficient ventilation, wear suitable respiratory equipment If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes

**Storage:**

Flammable materials should be stored in a separate safety storage cabinet or room. Keep away from heat. Keep away from sources of ignition. Keep container tightly closed. Keep in a cool, well-ventilated place. Ground all equipment containing material. A refrigerated room would be preferable for materials with a flash point lower than

37.8°C (100°F).

## Section 8: Exposure Controls/Personal Protection

### Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

### Personal Protection:

Face shield. Full suit. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves. Boots.

### Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

### Exposure Limits:

TWA: 10 (ppm) TWA: 25 (mg/m3) Consult local authorities for acceptable exposure limits.

## Section 9: Physical and Chemical Properties

**Physical state and appearance:** Liquid. (Clear viscous liquid.)

**Odor:** Ammoniacal.

**Taste:** Not available.

**Molecular Weight:** 60.1 g/mole

**Color:** Yellow.

**pH (1% soln/water):** Not available.

**Boiling Point:** 117.2°C (243°F)

**Melting Point:** 8.5°C (47.3°F)

p. 4

**Critical Temperature:** Not available.

**Specific Gravity:** 0.8995 (Water = 1)

**Vapor Pressure:** 10.7 mm of Hg (@ 20°C)

**Vapor Density:** 2.07 (Air = 1)

**Volatility:** 100% (v/v).

**Odor Threshold:** 10.2 ppm

**Water/OilDist. Coeff.:** Not available.

**Ionicity (in Water):** Not available.

**Dispersion Properties:** See solubility in water.

**Solubility:** Easily soluble in cold water.

## Section 10: Stability and Reactivity Data

**Stability:** The product is stable.

**Instability Temperature:** Not available.

**Conditions of Instability:** Not available.

**Incompatibility with various substances:** Not available.

**Corrosivity:** Non-corrosive in presence of glass.

**Special Remarks on Reactivity:** Not available.

**Special Remarks on Corrosivity:** Not available.

**Polymerization:** No.

## Section 11: Toxicological Information

**Routes of Entry:** Dermal contact. Eye contact. Inhalation. Ingestion.

**Toxicity to Animals:**

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE.

Acute oral toxicity (LD50): 470 mg/kg [Guinea pig]. Acute dermal toxicity (LD50): 750 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50): 424.3 ppm 4 hour(s) [Mouse].

**Chronic Effects on Humans:** The substance is toxic to kidneys, lungs, liver, mucous membranes.

**Other Toxic Effects on Humans:**

Extremely hazardous in case of skin contact (corrosive, irritant, permeator), of ingestion, of inhalation. Very hazardous in case of skin contact (sensitizer).

**Special Remarks on Toxicity to Animals:** Not available.

**Special Remarks on Chronic Effects on Humans:** Not available.

**Special Remarks on other Toxic Effects on Humans:** Not available.

## Section 12: Ecological Information

**Ecotoxicity:** Not available.

**BOD5 and COD:** Not available.

**Products of Biodegradation:**

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

**Toxicity of the Products of Biodegradation:** The products of degradation are as toxic as the original product.

**Special Remarks on the Products of Biodegradation:** Not available.

## Section 13: Disposal Considerations

**Waste Disposal:**

Waste must be disposed of in accordance with federal, state and local environmental control regulations.

## Section 14: Transport Information

**DOT Classification:** CLASS 8: Corrosive liquid.

**Identification:** : Ethylenediamine : UN1604 PG: II

**Special Provisions for Transport:** Not available.

## Section 15: Other Regulatory Information

### Federal and State Regulations:

Pennsylvania RTK: Ethylenediamine Massachusetts RTK: Ethylenediamine TSCA 8(b) inventory: Ethylenediamine SARA

302/304/311/312 extremely hazardous substances: Ethylenediamine CERCLA: Hazardous substances.: Ethylenediamine

**Other Regulations:** OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

### Other Classifications:

#### WHMIS (Canada):

CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-1B: Material causing immediate and serious toxic effects (TOXIC). CLASS D-2A: Material causing other toxic effects (VERY TOXIC). CLASS E: Corrosive liquid.

#### DSCL (EEC):

R10- Flammable. R21/22- Harmful in contact with skin and if swallowed. R35- Causes severe burns. R43- May cause sensitization by skin contact.

#### HMIS (U.S.A.):

**Health Hazard:** 3

**Fire Hazard:** 3

**Reactivity:** 0

**Personal Protection:**

**National Fire Protection Association (U.S.A.):**

**Health:** 3

**Flammability:** 3

**Reactivity:** 0

**Specific hazard:**

**Protective Equipment:** Gloves. Full suit. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Face shield.

## Section 16: Other Information

**References:** Not available.

**Other Special Considerations:** Not available.

**Created:** 10/10/2005 11:23 AM

**Last Updated:** 05/05/2015 12:00 PM

*The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall ScienceLab.com be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if ScienceLab.com has been advised of the possibility of such damages.*