

Specifications



Photo is representative



Eaton 066166

Eaton Moeller® series EMT6 Thermistor overload relay for machine protection, 1W , 24-240V50/60Hz, 24-240VDC, without reclosing lockout

General specifications

PRODUCT NAME	Eaton Moeller® series EMT6 Thermistor overload relay
CATALOG NUMBER	066166
MODEL CODE	EMT6
EAN	4015080661665
PRODUCT LENGTH/DEPTH	103 mm
PRODUCT HEIGHT	83 mm
PRODUCT WIDTH	23 mm
PRODUCT WEIGHT	0.128 kg
CERTIFICATIONS	CSA Class No.: 3211-03 IEC/EN 60947-8 UL Category Control No.: NKCR CSA CSA-C22.2 No. 14 EN 55011 IEC/EN 60947 IEC/EN 61000-4-2 VDE 0660 CSA File No.: 12528 UL UL 508 UL File No.: E29184 IEC/EN 61000-4-3 CE



Powering Business Worldwide

Features & Functions	
ELECTRIC CONNECTION TYPE	Screw connection
FUNCTIONS	Test function via separate button Notifications of mains and faults via LED display
TEMPERATURE MEASURING RANGE - MIN	0 °C
TEMPERATURE MEASURING RANGE - MAX	0 °C

Climatic environmental conditions	
AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	45 °C
AMBIENT STORAGE TEMPERATURE - MIN	45 °C
AMBIENT STORAGE TEMPERATURE - MAX	85 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

General	
DEGREE OF PROTECTION	IP20
MOUNTING POSITION	As required
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	EMT6 thermistor overload relay for machine protection
PROTECTION	Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC 4000 V AC
SAFE ISOLATION	250 V AC, Between the contacts, According to EN 61140 250 V AC, Between the contacts and power supply, According to EN 61140
SHOCK RESISTANCE	10 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
VOLTAGE TYPE	AC/DC

Electro magnetic compatibility	
AIR DISCHARGE	8 kV
BURST IMPULSE	According to IEC/EN 61000-4-4 1 kV, Signal cable 2 kV, Supply cable
CONTACT DISCHARGE	6 kV
ELECTROMAGNETIC FIELDS	10 V/m at 80 - 1000 MHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3) 1 V/m at 2.0 - 2.7 GHz (according to IEC EN 61000-4-3)
IMMUNITY TO LINE-CONDUCTED INTERFERENCE	10 V (according to IEC/EN 61000-4-6)
RADIO INTERFERENCE CLASS	Class B (EN 55011)
SURGE RATING	According to IEC/EN 61000-4-5, power pulses (Surge), EMC 2 kV, symmetrical, power pulses (Surge), EMC 4 kV, asymmetrical, power pulses (Surge), EMC

Terminal capacities	
TERMINAL CAPACITY	2 x (0.5 - 1.5) mm ² , solid 1 x (0.5 - 2.5) mm ² , solid 1 x (0.5 - 2.5) mm ² , flexible with ferrule 2 x (0.5 - 1.5) mm ² , flexible with ferrule 20 - 14 AWG, solid or stranded
SCREW SIZE	M3.5, Terminal screw
SCREWDRIVER SIZE	1 x 6 mm, Terminal screw, Standard screwdriver 2, Terminal screw, Pozidriv screwdriver
TIGHTENING TORQUE	1.2 Nm, Screw terminals

Electrical rating	
CONVENTIONAL THERMAL CURRENT ITH OF AUXILIARY CONTACTS (1-POLE, OPEN)	6 A
PICK-UP VOLTAGE	0.85 - 1.1 V x U _e
POWER CONSUMPTION	2 W at DC 3.5 VA at AC
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MIN	24 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 50 HZ - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MIN	24 V
RATED CONTROL SUPPLY VOLTAGE (US) AT AC, 60 HZ - MAX	240 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MIN	24 V
RATED CONTROL SUPPLY VOLTAGE (US) AT DC - MAX	240 V
RATED INSULATION VOLTAGE (UI)	400 V
RATED OPERATIONAL CURRENT (IE)	1 A at AC-15, 380 V 400 V 415 V (NC) 3 A at AC-14, 380 V 400 V 415 V (NO) 3 A at AC-15, 220 V 230 V 240 V (NO) 3 A at AC-15, 220 V 230 V 240 V 3 A at AC-14, 300 V (NO) 1 A at AC-15, 380 V 400 V 415 V (NO) 3 A at AC-14, 300 V (NC) 3 A at AC-14, 400 V (NC) 3 A at AC-14, 380 V 400 V 415 V (NC) 1 A at AC-15, 300 V (NO) 3 A at AC-15, 220 V 230 V 240 V (NC) 1 A at AC-15, 300 V (NC)
RATED OPERATIONAL VOLTAGE (UE) - MAX	240 V
RESET RESISTANCE	1600 Ω
SHORT-CIRCUIT PROTECTION RATING	Max. 6 A gG/gL, Fuse, Contacts
TRIP RESISTANCE	3600 Ω
VOLTAGE RATING - MAX	600 V

Contacts

Design verification

NUMBER OF CONTACTS (CHANGE-OVER CONTACTS)	0
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	1
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	1

EQUIPMENT HEAT DISSIPATION, CURRENT- DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT- DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON- CURRENT-DEPENDENT PVS	0.8 W

Resources

BROCHURES	EMR6 - EMT6 - ETR4 brochure
CATALOGUES	eaton-product-overview-for- machinery-catalogue- ca08103003zen-en-us.pdf
CHARACTERISTIC CURVE	eaton-tripping-emt6-thermistor- overload-relay-characteristic- curve.eps 230U002
DECLARATIONS OF CONFORMITY	DA-DC-00003971.pdf DA-DC-00003562.pdf
DRAWINGS	eaton-tripping-thermistor-relay- emt6-dimensions.eps 230X009 2327DIM-22 eaton-tripping-devices-relay- emt6-thermistor-overload- relay-dimensions.eps 2327DRW-34 eaton-tripping-devices-relay- emt6-thermistor-overload- relay-3d-drawing.eps
ECAD MODEL	ETN.EMT6
INSTALLATION INSTRUCTIONS	eaton-emt6-thermistor-motor- protection-relays-instruction- leaflet-il121016zu.pdf
MANUALS AND USER GUIDES	MN03407006Z DE EN
MCAD MODEL	eaton-cadenas-front_view- emt6_front.pra eaton-emt6-3d-model.stp DA-CS-emt6 eaton-emt6-drawing.dwg

[eaton-cadenas-path-emt6_etr4-
emt6.3db](#)

[eaton-cadenas-side_view-
emt6_side.pra](#)

[DA-CD-emt6](#)

WIRING DIAGRAMS

[eaton-tripping-devices-auto-
mode-emt6-thermistor-
overload-relay-wiring-
diagram.eps](#)

[230S008](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights
Reserved.

Eaton is a registered trademark.

All other trademarks are property of
their respective owners.

Follow us on social media to get the latest
product and support information.

