

10 April, 2025

PEAT ANALYSIS CERTIFICATE
02267



Parameter	Test results
Type of peat	High bog
Milled peat	100 %
Fraction, mm	0-7
Decomposition Von Post	H4-H6 Color: Black brown
Organic matter, %	>90
Dry matter by volume, g/l	120-140
Bulk density, g/l	330-340
Ash, %	3-8
Total pore volume,% (V/V)	90-93
Air share, %	8-12
Water absorption, times	>6,0
Moisture content, %	55-60
Limestone, kg/m ³	14,00
Acidy, pH (H ₂ O, v/v 1:1)	>7,0
Electrical conductivity (H ₂ O, v/v 1:1), mS/cm	0,1-0,4
Total Nitrogen(N), mg/l	<50
Phosphorous(P ₂ O ₅), mg/l	<50
Potassium(K ₂ O), mg/l	<50
Trace elements (Mg, Fe, Cu, Mn, B, Mo, Zn)	+

*This product may contain remnants of resistant fibers, twigs from the Ericaceae family, and pine wood sticks.
Outlined in sections 5.2.6.2 and 5.2.6.3 of the standard LST 1957 (DIN 11540).
The volume of the product in the bales is determined during filling in accordance with the standard EN 12580.*

Akcinė bendrovė „Rėkyva“
Įm. kodas / Enterprise code 144929986
PVM kodas/VAT code LT 449299811

Lingailių g. 27A, LT-79241 Šiauliai
Tel. +370 41 519020. Fax +370 41 519024
El. paštas:info@rekyva.eu
www.rekyva.eu

