



LUX-Y Battery Pack

LUX-Y-48280/48300LG01



Product Features



Higher safe performance
and longer cycle life



Multiple Protection:
Built-in smart BMS,
Breaker and Fuse



Flexible Installation:
Wall-Mounted or
Floor-Mounted



Aerosol Fire
Extinguishing
System



Wide Compatibility:
Compatible with
leading inverter brands



High Scalability



Built-in WIFI:
Remote monitor of
the battery pack data



Long Warranty:
10 Years

Specification

Model	LUX-Y-48280LG01	LUX-Y-48300LG01
Battery Type	LiFePO4	
Nominal Energy	14.3kWh	15kWh
Nominal Capacity	280Ah	300Ah
Nominal Voltage	51.2V	
Operating Voltage	44.8~57.6V	
Recommend Charge/Discharge Current	120A	
Max.continuous charge/Discharge current[1]	150A	
Peak Charge/Discharge Current(15s)	200A	
Scalability	Max.15(215kWh)	Max.15(225kWh)
Depth of Discharge(DOD)	≥95%	
Display type	LCD	
Protection Level	IP21	
Working Temperature Range	Charge: 0°C~ +55°C	
	Discharge:-20°C~ +55 °C	
Storge Temperature Range	0°C~ +35°C	
Humidity	5%-95%	
Altitude	≤2000m	
Communication	RS485 / CAN	
Cycle Life[2]	≥ 6000 Cycles	
Installation	Wall-Mounted / Floor-Mounted	
Protection	Built-in smart BMS, Breaker, Fuse	
Warranty Period[3]	10Years	
Product Weight Approximate	135kg	
Package Weight Approximate	160kg	
Product Dimension	480x1100x300mm	
Package Dimension	1150x635x498mm	
[1] Max.continuous charge/Discharge current is affected by temperature and SOC.		
[2] Test conditions: 0.5C Charging/Discharging @25°C, 80% DOD, 60%EOL.		
[3] Conditions apply, refer to FelicityESS Warranty Letter.		