

PORT PRO RX

Port Bias



- 1 **(SPECIALLY FORMULATED COMPOUND)** Resist to cut and snags with optimized wear
- 2 **(DESIGNED FOR REACH STACKER WITH STRONG NYLON CASING)** High load carrying capacity
- 3 **(STRONG BEAD)** Minimizing bead failure
- 4 **(HIGHER UNDER TREAD)** Resistance to Puncture

Sizes

| Sizes | RIM |
|----------|-----|
| 18.00-25 | 13 |

Table of Specifications

| Size | Rim Rec | Inflated Tire Dimension | | SLR | RC | PR | Flange Height | Inflation Pressure | Recommended Load, kg (lbs) | | | | |
|----------|---------|-------------------------|------|--------|------|----|---------------|--------------------|----------------------------|-------|-------|-------|-------|
| | | SW | OD | | | | | | Speed, km/h (mph) | | | | |
| | | mm | mm | | | | | | Constant Load | | | | |
| | | In | In | | | | | | Static | 1 | 5 | 10 | 25 |
| | | bar | psi | Static | 1 | 3 | 6 | 16 | | | | | |
| 18.00-25 | 13 | 498 | 1673 | 764 | 4952 | 40 | 2.5 | 10.0 | 11040 | 29000 | 24650 | 10000 | 27000 |
| | | 20 | 66 | 30 | 195 | | | 145 | 24343 | 63945 | 54353 | 22050 | 59535 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.