

# FLOATMAX FT

Agriculture Trailer Radial



- 1 **(DIRECTIONAL LUG & ROBUST LUG)** Better traction , Self cleaning , Better grip
- 2 **(HIGHER V/R RATIO)** Longer life
- 3 **(ROUNDED SHOULDER)** Reduced soil disturbance
- 4 **(ROBUST CENTRE BLOCKS & FLAT TREAD PROFILE)** Low vibration and smoother ride hard surfaces , Larger footprint increases flotation

## Sizes

Sizes	RIM
560/45R22.5	AG16.00

## Table of Specifications

Size	Rim Rec	Inflated Tire Dimension		SLR	RC	Li/SS	Inflation Pressure	Recommended Load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
		mm	mm					Mixed Application					
		in	in					Static	10	30	40	50	65
		mm	mm	mm	mm	bar	Static	6	19	25	31	40	
		in	in	in	in	psi	Static	6	19	25	31	40	
560/45R22.5	AG16.00	543 21.4	1076 42.4	493 19.4	3278.9 129.1	152D 152D	0.8	2650	2070	1740	1560	1390	1150
							12	5840	4560	3830	3440	3060	2530
							1.6	4140	3240	2720	2450	2180	1800
							23	9120	7140	5990	5400	4800	3960
							2.4	5430	4250	3560	3210	2860	2360
							35	11960	9360	7840	7070	6300	5200
							3.2	6900	5400	4530	4080	3630	3000
							46	15200	11890	9980	8990	8000	6610
							3.6	7480	5850	4910	4420	3930	3250
							52	16480	12890	10810	9740	8660	7160
							4.0	8170	6390	5360	4830	4300	3550
							58	18000	14070	11810	10640	9470	7820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.