

FARMAX R85

Agriculture Tractor Radial



- 1 (HIGHER ANGLE AND LUG OVERLAP AT CENTER) Better roadability
- 2 (ROUNDED SHOULDER) Reduced damage to soil and crop
- 3 (R1-W TREAD DEPTH) Longer tyre life
- 4 (LOWER ANGLE AT SHOULDER) Superior traction
- 5 (REDUCED SOIL COMPACTION) Wider tread , Larger inner volume

Sizes

Sizes	RIM
280/85R24	W10

Table of Specifications

Size	Rim Rec	RIM ALT	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended Load, kg (lbs)						
			SW	OD					Speed, km/h (mph)						
			mm	mm					Tractor Application						
			in	in					mm	mm	mm	mm	mm	mm	mm
280/85R24	W10	W9	285	1086	496	3235	115D/118A8	0.8	Static	10	20	30	40	50	65
								12	Static	6	12	19	25	31	40
								1.2	1840	1200	980	920	880	840	800
								17	4050	2640	2160	2030	1940	1850	1760
								1.4	2350	1530	1250	1170	1120	1070	1020
								20	5180	3370	2750	2580	2470	2360	2250
								1.6	2580	1680	1380	1290	1230	1180	1120
								23	5680	3700	3040	2840	2710	2600	2470
psi	2790	1820	1490	1400	1330	1280	1215								
23	6150	4010	3280	3080	2930	2820	2680								

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.