

FLOATMAX FT

 Agriculture  Trailer  Radial



- 1 **(DIRECTIONAL LUG & ROBUST LUG)** Better traction , Self cleaning , Better grip
- 2 **(HIGHER V/R RATIO)** Longer life
- 3 **(ROUNDED SHOULDER)** Reduced soil disturbance
- 4 **(ROBUST CENTRE BLOCKS & FLAT TREAD PROFILE)** Low vibration and smoother ride hard surfaces , Larger footprint increases flotation

Sizes

Sizes	RIM
800/45R26.5	AG28.00

Table of Specifications

Size	Rim Rec	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended Load, kg (lbs)					
		SW	OD					Speed, km/h (mph)					
		mm	mm					Mixed Application					
		in	in					bar	Static	10	30	40	50
				mm	mm		psi	Static	6	19	25	31	40
800/45R26.5	AG28.00	808	1393	632	4113.7	174D 	0.8	4880	3820	3350	2880	2570	2120
							12	10750	8410	7380	6340	5660	4670
							1.6	7710	6030	5290	4560	4050	3350
							23	16980	13280	11650	10040	8920	7380
							2.4	10350	8100	7110	6120	5450	4500
							35	22800	17840	15660	13480	12000	9910
							3.0	12190	9540	8370	7210	6410	5300
							44	26850	21010	18440	15880	14120	11670
							3.6	14150	11070	9720	8360	7440	6150
							52	31170	24380	21410	18410	16390	13550
							4.0	15410	12060	10590	9110	8110	6700
							58	33940	26560	23330	20070	17860	14760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.