

# FARMAX R85

Agriculture Tractor Radial



- 1 (HIGHER ANGLE AND LUG OVERLAP AT CENTER) Better roadability
- 2 (ROUNDED SHOULDER) Reduced damage to soil and crop
- 3 (R1-W TREAD DEPTH) Longer tyre life
- 4 (LOWER ANGLE AT SHOULDER) Superior traction
- 5 (REDUCED SOIL COMPACTION) Wider tread , Larger inner volume

## Sizes

Sizes	RIM
380/85R28	W12

## Table of Specifications

Size	Rim Rec	RIM ALT	Inflated Tire Dimension		SLR	RC	U/SS	Inflation Pressure	Recommended Load, kg (lbs)						
			SW	OD					Speed, km/h (mph)						
			mm	mm					Tractor Application						
			in	in					mm	mm	mm	mm	mm	mm	mm
								bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
380/85R28	W12	W13,W11	390	1357	620	4035	133D/136A8	0.8	3150	2060	1690	1580	1500	1440	1370
								12	6940	4540	3720	3480	3300	3170	3020
								1.0	3590	2340	1920	1790	1710	1640	1560
								15	7910	5150	4230	3940	3770	3610	3440
								1.3	4190	2730	2240	2090	1990	1910	1820
								19	9230	6010	4930	4600	4380	4210	4010
								1.6	4740	3090	2530	2370	2260	2160	2060
								23	10440	6810	5570	5220	4980	4760	4540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.