CEAT SPECIALTY
AGRICULTURE & OTR TYRES

FARMAX R65

Agriculture | Tractor | Radial

1. **(R1 W TREAD DEPTH)** Longer tyre life
2. **(TILTED LUG TIP)** Lesser vibration and noise
3. **(LOWER ANGLE AT SHOULDER)** Superior traction
4. **(MUD BREAKER)** Better self cleaning
5. **(ROUNDED SHOULDER)** Reduced damage to soil and crop
6. **(HIGHER ANGLE AND LUG OVERLAP AT CENTER)** Better roadability
7. **(REDUCED SOIL COMPACTION)** Wider tread , Larger inner volume

Sizes

Sizes	RIM
540/65R34	W16L

Table of Specifications

Size	Rim Rec	RIM ALT	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended Load, kg (lbs)							
									Speed, km/h (mph)							
			SW	OD					Non-Cyclic Operation					Cyclic Operation		
			mm	mm	mm	mm		bar	Field Operation	25	40	50	65	bar	10	15
			in	in	in	in		psi	Field Operation	16	25	31	40	psi	6	9
540/65R34	W16L	W18L	550 21.7	1566 61.7	717 28.2	4659 183.4	152D	0.8	2220	2290	2110	2030	1930	1.0	3280	2990
								12	4890	5040	4650	4470	4250	15	7220	6590
								1.2	2730	2810	2600	2490	2370	1.5	4030	3670
								17	6010	6190	5730	5480	5220	22	8880	8080
								1.8	3450	3560	3290	3150	3000	2.3	5100	4650
								26	7600	7840	7250	6940	6610	33	11230	10240
								2.4	4080	4210	3890	3730	3550	3.0	6040	5500
								35	8990	9270	8570	8220	7820	44	13300	12110

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.