CEAT SPECIALTY
AGRICULTURE & OTR TYRES

TORQUEMAX

Agriculture | Tractor | Radial

1. **(WIDER TREAD WIDTH)** Lower Compaction
2. **(STEPPED LUG DESIGN)** Better Grip
3. **(TILTED LUG GRIP)** Lower Vibration At High Speeds
4. **(LOWER LUG ANGLE AT THE SHOULDER)** Better Traction
5. **(STRONGER AND WIDER LUGS)** Longer Life
6. **(ROUNDED SHOULDER)** Less Soil/crop Damage

Sizes

Sizes	RIM
VF710/60R38 NRO	DW24B

Table of Specifications

Size	Rim Rec	RIM ALT	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended Load, kg (lbs)					
									Speed, km/h (mph)					
									Tractor Application				Cyclic Operation	
			SW	OD										
			mm	mm	mm	mm		bar	10	20	30	40 - 65	bar	10
			in	in	in	in		psi	6	12	19	25 - 40	psi	6
VF710/60R38 NRO	DW24B	DW27B, DW23B(NRO)	710 28.0	1820 71.7	799 31.5	5375 211.6	171D	0.6	4400	4160	4080	4000	1.4	5600
								9	9690	9160	8990	8810	20	12330
								0.8	4280	4050	3970	3890	1.6	5450
								12	9430	8920	8740	8570	23	12000
								1.0	4900	4630	4540	4450	1.8	6230
								15	10790	10200	10000	9800	26	13720
								1.2	5510	5210	5110	5010	2.0	7010
								17	12140	11480	11260	11040	29	15440
								1.4	6120	5780	5670	5560	2.2	7780
								20	13480	12730	12490	12250	32	17140
								1.6	6770	6400	6270	6150	2.4	8610
								23	14910	14100	13810	13550	35	18960

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.