

# FARMAX HPT

Agriculture Tractor Radial



- 1 **(LUG BASE TIE BAR)** Additional support to lugs and also helps to remove mud from lugs
- 2 **(LUG TIP STEP)** Increase the grip and reducing the tractor slip
- 3 **(50° LUG ANGLE AT CENTRE)** Smoother road driving comfort, less noise and vibration.
- 4 **(EXTRA WIDE TREAD)** Wider footprint provides increased stability
- 5 **(DEEPER TREAD DEPTHS)** Provides improved traction and gripping power longer tyre life
- 6 **(ROUNDER SHOULDER)** Provides less soil damage Better Grip

## Sizes

Sizes	RIM
800/70R38	DW27B

## Table of Specifications

Size	Rim Rec	RIM ALT	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended Load, kg (lbs)						
			SW	OD					Speed, km/h (mph)						
			mm	mm					Tractor Application						
			in	in					Static	10	20	30	40	50	65
800/70R38	DW27B	DW25B	820 32.3	2089 82.2	927 36.5	6110 240.6	178D/181A8	bar	Static	10	20	30	40	50	65
								psi	Static	6	12	19	25	31	40
								0.8	9490	6190	5070	4740	4520	4330	4125
								12	20900	13630	11170	10440	9960	9540	9090
								1.2	12190	7950	6520	6100	5800	5570	5300
								17	26850	17510	14360	13440	12780	12270	11670
								1.6	14950	9750	8000	7480	7120	6830	6500
								23	32930	21480	17620	16480	15680	15040	14320
								2.0	16330	10650	8730	8170	7770	7460	7100
								29	35970	23460	19230	18000	17110	16430	15640
								2.4	17250	11250	9690	8630	8210	7880	7500
								35	38000	24780	21340	19010	18080	17360	16520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.