

FARMAX HPT

Agriculture Tractor Radial



- 1 **(LUG BASE TIE BAR)** Additional support to lugs and also helps to remove mud from lugs
- 2 **(LUG TIP STEP)** Increase the grip and reducing the tractor slip
- 3 **(50° LUG ANGLE AT CENTRE)** Smoother road driving comfort, less noise and vibration.
- 4 **(EXTRA WIDE TREAD)** Wider footprint provides increased stability
- 5 **(DEEPER TREAD DEPTHS)** Provides improved traction and gripping power longer tyre life
- 6 **(ROUNDER SHOULDER)** Provides less soil damage Better Grip

Sizes

Sizes	RIM
710/70R42	DW23B

Table of Specifications

Size	Rim Rec	RIM ALT	Inflated Tire Dimension		SLR	RC	LI/SS	Inflation Pressure	Recommended Load, kg (lbs)						
			SW	OD					Speed, km/h (mph)						
			mm	mm					Tractor Application						
			in	in					Static	10	20	30	40	50	65
		bar	Static	6	12	19	25	31	40						
		psi	Static	6	12	19	25	31	40						
710/70R42	DW23B	DW25B	716 28.2	2075 81.7	942 37.1	6160 242.5	176D/179A8	0.8	8170	5330	4370	4080	3890	3730	3550
								12	18000	11740	9630	8990	8570	8220	7820
								1.2	10350	6750	5540	5180	4930	4730	4500
								17	22800	14870	12200	11410	10860	10420	9910
								1.6	12880	8400	6890	6440	6130	5880	5600
								23	28370	18500	15180	14190	13500	12950	12330
								2.0	14150	9230	7560	7070	6730	6460	6150
								29	31170	20330	16650	15570	14820	14230	13550
								2.4	14950	9750	8400	7480	7120	6830	6500
								35	32930	21480	18500	16480	15680	15040	14320
2.8	16330	10650	8730	8170	7770	7460	7100								
41	35970	23460	19230	18000	17110	16430	15640								

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.