

AW-5890U Thermal Receipt Printer



Specifications

Print Method	Direct Line Thermal
Interfaces	USB / USB+Bluetooth (optional)
Print Comand	ESC / POS command
Print Speed	70mm/s
Resolution	203DPI (8dot/mm)
TPH Reliability	50km
Logo	support downloading and printing logo
Printing Density	384 dots/line
Extension Character Sheet	PC437 (Standard Europe) 、Katakana、PC850 (Multilingual) 、PC860 (Portuguese) 、PC863 (Canadian) 、PC865 (Nordic) 、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2) 、PC852 (Latin2) 、PC858、IranII、Latvian、Arabic、Thai、PT151 (1251)
Character Size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese, Traditional Chinese:3.0×3.0mm (24×24 dots)
Supported Code:	1D: UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 2D: QR CODE, PDF417
Driver	Windows / Linux / Mac OS / OPOS / Android
Power Adapter	Input: AC 100-240V, 50 ~ 60Hz ; Output: DC 8.5V/2A
Cash Drawer	DC 12V

Paper

Paper Types	Thermal Roll Paper
Paper Width	57.5±0.5mm / ϕ 50 mm
Print Width	48mm
Paper Thickness	0.06-0.08 mm

Package

Printer Dimension	15.9*11.5*9.5 CM
Printer N.W.	0.32 kg
Package	1pc with accessories/Box, 24 boxes/CTN
Accessories	Manual, USB Cable, Power Adapter, Paper Roll
Box Dimension	16.8*11.7*12.5 CM
Box G.W.	0.52 Kgs
CTN Dimension	49.5*35*39 CM
CTN G.W.	13.5 Kgs

Environmental Requirements

Work Environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage Environment	Temperature(- 10 ~ 60°C) humidity(10 ~ 90%)