

AW-5810 Portable Bluetooth Receipt Printer



Specifications

Print Method	Direct Line Thermal
Interfaces	Type-c +Bluetooth
Print Comand	ESC / POS command
Print Speed	70mm/s
Resolution	203DPI (8dot/mm)
TPH Reliability	50km
Logo	support downloading and printing logo
Printing Density	384 dots/line
Extension Character Sheet	PC437(Standard Europe), Katakana, PC850(Multilingual), PC860(Portuguese), PC863(Canadian), PC865(Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866(Cyrillic#2), PC852(Latin2), PC858, IranII, Latvian, Arabic, Thai, PT151(1251)
Character Size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese, Traditional Chinese:3.0×3.0mm (24×24 dots)
Supported Code:	1D: UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 2D: QR CODE, PDF417
Driver	Windows / Linux / Mac OS / OPOS / Android
Power Adapter	Input: AC 100-240V, 50 ~ 60Hz ; Output: DC 5V/1A (Optional)
Battery Power	7.4V/1500mA

Paper

Paper Types	Thermal Roll Paper
Paper Width	57.5±0.5mm / φ 43 mm
Print Width	48mm
Paper Thickness	0.06-0.08 mm

Package

Package	1pc with accessories/Box, 40 boxes/CTN	1pc with accessories/Box, 60 boxes/CTN
Accessories	Manual, USB Cable, Power Adapter, Paper Roll	Manual, USB Cable, Paper Roll
Box Dimension	14.7*11.9*7 CM	12*6.2*11 CM
Box G.W.	0.42 Kgs	0.3 Kgs
CTN Dimension	50*31.4*37.2 CM	37.5*33.5*46 CM
CTN G.W.	17.6 Kgs	18.8 Kgs

Environmental Requirements

Work Environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage Environment	Temperature(-10 ~ 60°C) humidity(10 ~ 90%)