

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.865 g/cm3
Viscosity @ 100°C (cSt)	13.7 cSt
Viscosity @ 40°C	92
Viscosity Index	151
Viscosity CCS @ -25°C	6000 cP
T.B.N (mg KOH/g)	10 mg KOH/g
Sulphated Ash Mass (%)	1.3 %
Zinc (%)	0.12 %
Colour	Brown
Phosphorus (%)	0.11 %
Flash Point (°C)	230 °C
Pour Point (°C)	-39 °C
Calcium (%)	0.3 %

EUROLITE 10W-40

Semi Synthetic

Official Approvals:

VW 501 01, VW 505 00

Recommended by Comma for applications requiring any of the following:

ACEA A3/B4, API SN/CF, RN0700, RN0710, PSA B71 2300, MB 229.3

Product Features:

- Semi synthetic, high performance 10W-40 oil, suitable for petrol and diesel vehicles including those with fuel injected and multivalved engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025