

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.848 g/cm3
Viscosity @ 100°C (cSt)	12.1 cSt
Viscosity @ 40°C	71
Viscosity Index	169
Viscosity CCS @ -30°C (cP)	6000 cP
T.B.N (mg KOH/g)	8.2 mg KOH/g
Sulphated Ash Mass (%)	0.7 %
Zinc (%)	0.09 %
Colour	Brown
Phosphorus (%)	0.07 %
Flash Point (°C)	230 °C
Pour Point (°C)	-36 °C
Calcium (%)	0.07 %

PRO-TECH 5W-30

Fully Synthetic

Recommended by Comma for applications requiring any of the following:

ACEA C2, PSA B71 2290

Product Features:

- Fully synthetic, high performance 5W-30 mid SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust after-treatment units that require an ACEA C2 grade.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025