

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.845 g/cm3
Viscosity @ 100°C (cSt)	11.7 cSt
Viscosity @ 40°C	65
Viscosity Index	177
Viscosity CCS @ -30°C (cP)	5700 cP
T.B.N (mg KOH/g)	8.6 mg KOH/g
Sulphated Ash Mass (%)	0.8 %
Zinc (%)	0.1 %
Colour	Brown
Phosphorus (%)	0.08 %
Flash Point (°C)	230 °C
Pour Point (°C)	-39 °C
Calcium (%)	0.17 %

PROLIFE 5W-30

Fully Synthetic

Official Approvals:

VW 504 00, VW 507 00

Recommended by Comma for applications requiring any of the following:

ACEA C3, API SN, MB 229.51, BMW LL-04, PORSCHE C30

Product Features:

- Fully synthetic, high performance 5W-30 mid SAPS oil, for modern VW-Audi group petrol and diesel vehicles including those operating under long life service regimes. Also protects exhaust after-treatment units.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025