

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.85 g/cm ³
Viscosity @ 100°C (cSt)	14.2 cSt
Viscosity @ 40°C	87
Viscosity Index	169
Viscosity CCS @ -30°C (cP)	6000 cP
T.B.N (mg KOH/g)	8 mg KOH/g
Sulphated Ash Mass (%)	0.8 %
Zinc (%)	0.1 %
Colour	Brown
Phosphorus (%)	0.08 %
Flash Point (°C)	230 °C
Pour Point (°C)	-39 °C
Calcium (%)	0.18 %

PD PLUS 5W-40

Fully Synthetic

Official Approvals:

VW 505 00, VW 505 01

Recommended by Comma for applications requiring any of the following:

ACEA C3, API SN/CF, Porsche A40, FORD WSS M2C917-A, MB 229.31, MB 226.5, dexos 2

Product Features:

- For VW PD/unit injector engines operating on fixed service intervals.
- Fully synthetic, high performance, 5W-40 oil, for vehicles fitted with the VW 'Pumpe Düse' PD or unit injector engine. Also protects exhaust after-treatment units.
- Do not mix this oil with other types of oil as the exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 17.06.2025