

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.852 g/cm ³
Viscosity @ 100°C (cSt)	12.4 cSt
Viscosity @ 40°C	76
Viscosity Index	162
Viscosity CCS @ -30°C (cP)	6000 cP
T.B.N (mg KOH/g)	10.5 mg KOH/g
Sulphated Ash Mass (%)	1.4 %
Zinc (%)	0.13 %
Colour	Brown
Phosphorus (%)	0.12 %
Flash Point (°C)	230 °C
Pour Point (°C)	-39 °C
Calcium (%)	0.33 %

LONG LIFE 5W-30

Fully Synthetic

Recommended by Comma for applications requiring any of the following:

ACEA A3/B4, API SL/CF, GM-LL-B-025, MB 229.3, VW 502 00, VW 505 00

Product Features:

- Fully synthetic, high performance 5W-30 oil, for GM/Vauxhall/Opel petrol and diesel vehicles including those operating under long life service regimes.
- Do not mix this oil with other types of oil, as the requirement for the long life service intervals will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025