

Technical Data Sheet



Typical Inspection Data:

Density @ 20°C	0.844 g/cm ³
Viscosity @ 100°C (cSt)	8.5 cSt
Viscosity @ 40°C	44
Viscosity Index	174
Viscosity CCS @ -35°C (cP)	6000 cP
T.B.N (mg KOH/g)	7.4 mg KOH/g
Sulphated Ash Mass (%)	0.7 %
Zinc (%)	0.08 %
Colour	Brown
Phosphorus (%)	0.07 %
Flash Point (°C)	230 °C
Pour Point (°C)	-39 °C
Calcium (%)	0.13 %

PRO-NRG 0W 20

Fully Synthetic

Recommended by Comma for applications requiring any of the following:

API SP, GM dexos1 Gen3, GM dexos1 Gen2 (backward compatible), GM 6094M & GM 4718M, ILSAC GF-6A, Chrysler MS 6395

Product Features:

- Fully synthetic, high performance 0W-20 oil for modern petrol vehicles
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

Shelf life:

- 5 years from date of manufacture
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

UPDATED: 06.05.2025