

FOX ECS BATTERY STORAGE SYSTEM



HIGH VOLTAGE BATTERY FROM FOX

The ECS is a high-performance, scalable battery storage system. The modular design allows for maximum flexibility, making it suitable for a broad range of storage applications.

Additional batteries can be installed in series, allowing for a maximum storage capacity of 29.03kWh. Installation is easy, with a plug and play solution that can save valuable time for installers.



- 4.14kWh capacity
- Scalable to 29.03 kWh
- 90% Depth of Discharge
- Large temperature tolerance
- Easy installation
- CAN/RS485 communication
- High voltage



High Voltage



Simple Installation



Height Efficiency



Expandable System



90% DoD

| Model | ECS4300H -H2 | ECS4300H -H3 | ECS4300H -H4 | ECS4300H -H5 | ECS4300H -H6 | ECS4300H -H7 |
|------------------------------------|---------------------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
| ELECTRICAL CHARACTERISTICS | | | | | | |
| Battery Type | LiFePO4 Prismatic Cell | | | | | |
| Battery Module | 1*CM4300H 1*CS4300H | 1*CM4300H 2*CS4300H | 1*CM4300H 3*CS4300H | 1*CM4300H 4*CS4300H | 1*CM4300H 5*CS4300H | 1*CM4300H 6*CS4300H |
| Nominal Capacity [Wh] | 8290 | 12440 | 16590 | 20740 | 24880 | 29030 |
| Nominal Voltage [V] | 115.2 | 172.8 | 230.4 | 288 | 345.6 | 403.2 |
| Operating Voltage [V] | 97.2 ~ 131.4 | 145.8 ~ 197.1 | 194.4 ~ 262.8 | 243 ~ 328.5 | 291.6 ~ 394.2 | 340.2 ~ 459.9 |
| Recommend Discharge Current [A] | 35 | | | | | |
| Max.Charge/Discharge Current [A] | 50 | | | | | |
| Peak Discharge Current [A] | 65 @30sec | | | | | |
| Battery Pack Round-Trip Efficiency | >95% | | | | | |
| Depth of discharge | 90% | | | | | |
| Cycle Life *1 | ≥6000 | | | | | |
| Communication | CAN | | | | | |
| Display | CS: LED*1, CM: LED*6 | | | | | |
| Scalability | Max. 7 Modules in Series | | | | | |
| OPERATING CONDITIONS | | | | | | |
| Installation Location | Outdoor/ Indoor (Stand) | | | | | |
| Operating Temperature [°C]*2 | Charge: 0 ~ 55 Discharge: -10 ~ 55 | | | | | |
| Storage Temperature [°C] | -20 ~ 55 | | | | | |
| Cooling method | Natural Convection | | | | | |
| Humidity | 5% ~ 95% (No Condensing) | | | | | |
| Altitude [m] | Max. 2,000 | | | | | |
| Mechanical Characteristics | | | | | | |
| Dimensions (W*H*D) (mm) | 570*350*380 | 570*470*380 | 570*590*380 | 570*710*380 | 570*830*380 | 570*950*380 |
| Weight (kg) | 75.6±1 | 112.5±1.5 | 148.3±2 | 184.7±2.5 | 221±3 | 257.4±3.5 |
| Certificates | | | | | | |
| Safety | IEC 62619 | | | | | |
| EMC | IEC 61000-6-1/2/3/4 | | | | | |
| Transportation | UN38.3 | | | | | |
| Ingress Protection | IP65 | | | | | |

*1, 25°C, @90% DOD, 0.5C charging/discharging.

*2, Charge derating will occur between 0°C and +15°C.

