

High Precision Flange Output Right Angle Planetary Gearbox

EVT



- 1. Quiet operation
Helical gears are used to achieve smooth and quiet operation.
- 2. High precision
The backlash is less than 3 arcmin and the positioning is accurate.
- 3. High rigidity & torque
The use of integral ball bearings greatly improves the rigidity and torque.
- 4. Methods of flange and connector
It can be installed on any motor in the world.
- 5. No grease leakage
The use of grease with high viscosity which is not easy to separate effectively prevents the grease leakage.
- 6. Convenient maintenance
No need to replace the grease in the product life period, and the installation is more convenient.

Model Selection of Speed Reducers

EVT Type

EVT090 - 10 - S1 - P1 / Motor

Reducer Model

EVT047, EVT064, EVT090
EVT110, EVT140, EVT200
EVT255

Output Shaft Keyway

S2: Standard (Keyway)

Motor Model

Servo
Nema



Ratio

1-stage: 3, 4, 5, 6, 7, 8, 9, 10
2-stage: 12, 15, 16, 20, 25, 28, 30, 35,
40, 50, 70, 80, 100

Backlash Grade

P0: High precision backlash
P1: Precision backlash
P2: Standard backlash

The gearbox matching motor needs to be confirmed with following dimensions :



EVT Reducer Specifications

| Specs | Unit | Stage | Ratio | EVT047 | EVT064 | EVT090 | EVT110 | EVT140 | EVT200 | EVT255 |
|---|-----------|-------|--------|---------------------------------|--------|--------|--------|--------|--------|--------|
| Rated Output Torque / T2N | Nm | 1 | 4 | 19 | 50 | 133 | 278 | 555 | 1050 | 1700 |
| | | | 5 | 22 | 60 | 160 | 330 | 650 | 1200 | 2000 |
| | | | 7 | 19 | 50 | 140 | 300 | 550 | 1100 | 1800 |
| | | | 10 | 14 | 40 | 100 | 230 | 450 | 900 | 1500 |
| | | 2 | 20 | 19 | 50 | 133 | 278 | 555 | 1050 | 1700 |
| | | | 25 | 22 | 60 | 160 | 330 | 650 | 1200 | 2000 |
| | | | 35 | 19 | 50 | 140 | 300 | 550 | 1100 | 1800 |
| | | | 40 | 19 | 45 | 120 | 260 | 500 | 1000 | 1600 |
| | | | 50 | 22 | 60 | 160 | 330 | 650 | 1200 | 2000 |
| | | | 70 | 19 | 50 | 140 | 300 | 550 | 1100 | 1800 |
| | | 100 | 14 | 40 | 100 | 230 | 450 | 900 | 1500 | |
| Max. Output Torque / T _{2NOT} ¹ | Nm | 1,2 | 4~100 | 3Times of Nominal Output Torque | | | | | | |
| Rated Input Speed / P1N | rpm | 1,2 | 4~100 | 5000 | 5000 | 4000 | 4000 | 3000 | 3000 | 2000 |
| Max. Input Speed / P1B | rpm | 1,2 | 4~100 | 10000 | 10000 | 8000 | 8000 | 6000 | 6000 | 4000 |
| Micro Backlash P0 | arcmin | 1 | 4~10 | ≤2 | ≤2 | ≤2 | ≤2 | ≤2 | ≤2 | ≤2 |
| | | 2 | 12~100 | ≤4 | ≤4 | ≤4 | ≤4 | ≤4 | ≤4 | ≤4 |
| Precision Backlash P1 | arcmin | 1 | 4~10 | ≤4 | ≤4 | ≤4 | ≤4 | ≤4 | ≤4 | ≤4 |
| | | 2 | 20~100 | ≤6 | ≤6 | ≤6 | ≤6 | ≤6 | ≤6 | ≤6 |
| Standard Backlash P2 | arcmin | 1 | 4~10 | ≤6 | ≤6 | ≤6 | ≤6 | ≤6 | ≤6 | ≤6 |
| | | 2 | 20~100 | ≤8 | ≤8 | ≤8 | ≤8 | ≤8 | ≤8 | ≤8 |
| Torsional Rigidity | Nm/arcmin | 1,2 | 4~100 | 8 | 13 | 30 | 80 | 150 | 450 | 1010 |
| Max. Radial Force / F _{2R} ² | N | 1,2 | 4~100 | 43 | 125 | 235 | 430 | 1300 | 3064 | 5900 |
| Max. Axial Force / F _{2A1B} ² | N | 1,2 | 4~100 | 990 | 1050 | 2850 | 2990 | 10590 | 16660 | 29430 |
| Service Life | hr | 1,2 | 4~100 | 22000h | | | | | | |
| | | 1 | 4~10 | ≥97% | | | | | | |
| Efficiency / η | % | 2 | 20~100 | ≥94% | | | | | | |
| | | 1 | 4~10 | 0.7 | 1.3 | 3.2 | 5.8 | 12.3 | 33 | 57.9 |
| Weight | kg | 2 | 20~100 | 1 | 1.5 | 4.1 | 7.6 | 16.8 | 38 | 72.6 |
| | | 1,2 | 4~100 | (-15℃ ~ +90℃) | | | | | | |
| Operating Temperature | ℃ | 1,2 | 4~100 | (Synthetic Grease) | | | | | | |
| Lubrication | | 1,2 | 4~100 | IP65 | | | | | | |
| Protection Class | | 1,2 | 4~100 | (Any Direction) | | | | | | |
| Mounting Position | | 1,2 | 4~100 | | | | | | | |
| Noise Level (n1=3000rpm, No load) | dB(A) | 1,2 | 4~100 | ≤58 | ≤59 | ≤62 | ≤65 | ≤68 | ≤69 | ≤70 |

Reducer Rotary Inertia

| Specs | Unit | Stage | Ratio | EVT047 | EVT064 | EVT090 | EVT110 | EVT140 | EVT200 | EVT255 |
|-------------------|--------------------|-------|--------|--------|--------|--------|--------|--------|--------|--------|
| Moment of Inertia | kg.cm ² | 1 | 4 | 0.03 | 0.14 | 0.48 | 2.74 | 7.54 | 23.67 | 54.37 |
| | | | 5 | 0.03 | 0.13 | 0.47 | 2.71 | 7.42 | 23.29 | 53.27 |
| | | | 7 | 0.03 | 0.13 | 0.45 | 2.62 | 7.14 | 22.48 | 50.97 |
| | | | 10 | 0.03 | 0.13 | 0.44 | 2.57 | 7.03 | 22.51 | 50.56 |
| | | 2 | 20~40 | 0.03 | 0.03 | 0.13 | 0.47 | 2.71 | 7.42 | 23.29 |
| | | | 50~100 | 0.03 | 0.03 | 0.13 | 0.44 | 2.57 | 7.03 | 22.51 |

1. Ratio (i=Nin/Nout) . 2. The Max. acceleration torque T2B=60% of T2NOT.

3. When output speed is 100rpm, acting on the output shaft center position *Continuous operation, service life is 15000hrs.


MODEL: EVT

1-Stage

Ratio: 3, 4, 5, 6, 7, 8, 9, 10



Dimensions:



Unit:mm

| Size | EVT047-L1 | EVT064-L1 | EVT090-L1 | EVT110-L1 | EVT140-L1 | EVT200-L1 | EVT255-L1 |
|------|-----------|-------------|--------------|----------------|------------------|----------------|----------------|
| D1 | ≤11/≤12 | 11(11 ~ 14) | 19(19 ~ 24) | 24(22 ~ 32) | 32(24 ~ 35) | ≤48 | ≤55 |
| D2 | 30 | 50 | 70(70 ~ 110) | 110(110 ~ 130) | 110(110 ~ 114.3) | 85 | 116 |
| D3 | 46 | 70 | 90(90 ~ 145) | 145(145 ~ 165) | 145(145 ~ 200) | 215 | 235 |
| D4 | M4 | M4 | M8 | M8 ~ M10 | M8 ~ M12 | M12 | M12 |
| D5 | 12 | 20 | 31.5 | 40 | 50 | 80 | 100 |
| D6 | 28 | 40 | 63 | 80 | 100 | 160 | 180 |
| D7 | 47 | 64 | 90 | 110 | 140 | 200 | 255 |
| D8 | 72 | 86 | 118 | 145 | 179 | 247 | 300 |
| D9 | 20 | 31.5 | 50 | 63 | 80 | 125 | 140 |
| D10 | 4-M3 | 7-M5x深度(D)8 | 8-M6x深度(D)12 | 11-M6x深度(D)12 | 11-M8x深度(D)17 | 11-M10x深度(D)20 | 12-M16x深度(D)25 |
| D11 | 67 | 79 | 109 | 135 | 168 | 233 | 280 |
| D12 | 8-Ø3.4 | 8-Ø4.5 | 8-Ø5.5 | 8-Ø5.5 | 12-Ø6.6 | 12-Ø9 | 16-Ø13.5 |
| D13 | Ø3 | Ø5x深度(D)8 | Ø6x深度(D)7 | Ø6x深度(D)7 | Ø8x深度(D)7 | Ø10x深度(D)10 | Ø12x深度(D)10 |
| L1 | 3.5 | 5 | 12 | 10 | 8 | 6 | 6 |
| L2 | 8 | 10 | 13 | 19 | 17 | 20 | 24 |
| L3 | 30 | 32 | 42 ~ 47 | 57 ~ 60 | 67 ~ 77 | 85 | 116 |
| L4 | 74 | 80.5 | 107 ~ 112 | 134 ~ 147.5 | 166.5 ~ 167 | 213.5 | 268.5 |
| L5 | 104 | 115.5 | 152 ~ 157 | 195 ~ 208.5 | 217.5 ~ 241.5 | 316 | 398.5 |
| L6 | 6.5 | 8 | 12 | 13 | 12 | 22.5 | 30.5 |
| L7 | 3 | 3 | 6 | 6 | 6 | 8 | 12 |
| L8 | 7 | 7 | 10 | 11 | 15 | 15 | 20 |
| L9 | 4 | 4 | 7 | 8 | 10 | 12 | 18 |
| L10 | 19.5 | 19.5 | 25 | 29 | 38 | 50 | 66 |
| L11 | 60 | 71 | 102 | 130 | 142.5 | 189 | 216 |
| L12 | 107.5 | 125.5 | 172 | 220 | 255.5 | 334.5 | 392 |
| C1 | 48 | 60 | 90(90 ~ 130) | 130 ~ 160 | 130(130 ~ 220) | 190 | 220 |


MODEL: EVT

2-Stage

Ratio: 12, 15, 16, 20, 25, 28, 30, 35
40, 50, 70, 80, 100



Dimensions:



Unit:mm

| Size | EVT47-L2 | EVT064-L2 | EVT090-L2 | EVT110-L2 | EVT140-L2 | EVT200-L2 | EVT255-L2 |
|------|----------|-------------|--------------|----------------|------------------|----------------|----------------|
| D1 | ≤11/≤12 | 11(11 ~ 14) | 19(19 ~ 24) | 24(22 ~ 32) | 32(24 ~ 35) | ≤48 | ≤55 |
| D2 | 30 | 50 | 70(70 ~ 110) | 110(110 ~ 130) | 110(110 ~ 114.3) | 85 | 116 |
| D3 | 46 | 70 | 90(90 ~ 145) | 145(145 ~ 165) | 145(145 ~ 200) | 215 | 235 |
| D4 | M4 | M4 | M8 | M8 ~ M10 | M8 ~ M12 | M12 | M12 |
| D5 | 12 | 20 | 31.5 | 40 | 50 | 80 | 100 |
| D6 | 28 | 40 | 63 | 80 | 100 | 160 | 180 |
| D7 | 47 | 64 | 90 | 110 | 140 | 200 | 255 |
| D8 | 72 | 86 | 118 | 145 | 179 | 247 | 300 |
| D9 | 20 | 31.5 | 50 | 63 | 80 | 125 | 140 |
| D10 | 4-M3 | 7-M5x深度(D)8 | 8-M6x深度(D)12 | 11-M6x深度(D)12 | 11-M8x深度(D)17 | 11-M10x深度(D)20 | 12-M16x深度(D)25 |
| D11 | 67 | 79 | 109 | 135 | 168 | 233 | 280 |
| D12 | 8-Ø3.4 | 8-Ø4.5 | 8-Ø5.5 | 8-Ø5.5 | 12-Ø6.6 | 12-Ø9 | 16-Ø13.5 |
| D13 | Ø3 | Ø5x深度(D)8 | Ø6x深度(D)7 | Ø6x深度(D)7 | Ø8x深度(D)7 | Ø10x深度(D)10 | Ø12x深度(D)10 |
| L1 | 3.5 | 5 | 12 | 10 | 8 | 6 | 6 |
| L2 | 8 | 10 | 13 | 19 | 17 | 20 | 24 |
| L3 | 30 | 32 | 42 ~ 47 | 57 ~ 60 | 67 ~ 77 | 85 | 116 |
| L4 | 74 | 80.5 | 107 ~ 112 | 134 ~ 147.5 | 166.5 ~ 167 | 213.5 | 268.5 |
| L5 | 103 | 115.5 | 152 ~ 157 | 195 ~ 208.5 | 217.5 ~ 241.5 | 269.5 | 340 |
| L6 | 4 | 8 | 12 | 13 | 12 | 22.5 | 30.5 |
| L7 | 3 | 3 | 6 | 6 | 6 | 8 | 12 |
| L8 | 7 | 7 | 10 | 11 | 15 | 15 | 20 |
| L9 | 4 | 4 | 7 | 8 | 10 | 12 | 18 |
| L10 | 19.5 | 19.5 | 25 | 29 | 38 | 50 | 66 |
| L11 | 79 | 94.5 | 117 | 163.5 | 187 | 243 | 270 |
| L12 | 122 | 149 | 187 | 253.5 | 300 | 382 | 403 |
| C1 | 48 | 60 | 90(90 ~ 130) | 130 ~ 160 | 130(130 ~ 220) | 190 | 220 |