

Art.no. **90122**

Pit gravity waste oil drainer, suitable for the draining of motor oil, gear oil or differential oil from trucks and passenger cars. Available with collection capacity of 70 l, with anti splash grid and metal rollers. Suitable for the use in service pits between the pit rails. It is possible to adapt the width according to the pit dimensions. The unit can be discharged by gravity through the laterally mounted 3/4" drain valve or by using an evacuation pump with suction hose and female quick coupling to be connected to the male coupling installed on the drainer.



Art. no.	Collection capacity	Width adjustment range (mm)	Connections	Weight	Dimensions (LxWxH) (mm)
90122	70 l	Min 900 - Max 1300	1/2" BSP (F)	27 Kg	850x630x220

Art.no. **90124**
Art.no. **90127**

Mobile low level gravity drainer, suitable for the draining of antifreeze from trucks and passenger cars by using the included pump kit for the eventual refilling of the liquid into the motor or circuit after finishing the service. Available with collection capacity of 70 l and 110 l, with anti splash grid.

The pumping kit consists of a pneumatic piston pump with 2,7: 1 compression ratio, air tap, air pressure regulator, suction pipe and delivery hose with rigid stem.



Art. no.	Compressed air supply	Outlet pressure	Flow rate	Collection capacity	Connections	Weight	Dimensions (LxWxH) (mm)
90124	2-8 bar	24 bar	15 l/min	70 l	1/2" BSP (F)	34 Kg	800x560x180
90127				110 l		46 Kg	1400x560x180