

Art.no. **90120**  
Art.no. **90120-110**

Mobile low level gravity waste oil drainer, suitable for the draining of motor oil, gear oil or differential oil from trucks and passenger cars. Available with collection capacity of 70 l and 110 l, with anti splash grid and removable, lateral antispash guard (optional). The unit can be discharged by gravity through the laterally mounted 3/4" drain valve.



Art. no.	Collection capacity	Connections	Weight	Dimensions (LxWxH) (mm)
<b>90120</b>	70 l	3/4" BSP (F)	26 Kg	800x560x180
<b>90120-110</b>	110 l	3/4" BSP (F)	38 Kg	1400x560x180

Waste oil

Art.no. **90110**  
Art.no. **90110-110**

Mobile low level gravity drainer, suitable for the draining of waste oils and antifreeze from trucks and passenger cars by using the included pump kit for the eventual refilling of the liquid into the motor or circuit after finishing the service. Available with collection capacity of 70 l and 110 l, with anti splash grid.

The pump kit art.no. 90100 consists of a pneumatic rotary pump (art.no. 31221-OT), pressure regulator with manometer, suction hose and dispensing hose with control gun and rigid outlet pipe.



Art. no.	Compressed air supply	Outlet pressure	Flow rate	Collection capacity	Connections	Weight	Dimensions (LxWxH) (mm)
<b>90110</b>	2-4 bar	4 bar	10.5 l/min	70 l	1/2" BSP (F)	34 Kg	800x560x180
<b>90110-110</b>	2-4 bar	4 bar	10.5 l/min	110 l	1/2" BSP (F)	46 Kg	800x560x285

Art.no. **90100**

Waste oil and antifreeze pumping kit composed of: air-operated rotary pump mod. 31221OT, pressure regulator with tap, flexible hoses and delivery gun. To be fitted on pans.



Art. no.	Compressed air supply	Outlet pressure	Flow rate	Connections	Weight	Dimensions (LxWxH) (mm)
<b>90100</b>	2-4 bar	4 bar	10.5 l/min	3/8" BSP (F)	30 Kg	200x160x150