



GEAR MOTOR GR2 UNIDIRECT FIXED DISPL

121.20.719.00 [🔗](#)

Model Code:

S-N-U-2-N-N-/-6,0-R-N-02-DB-P1-F4-F4-NN-N-N-/-NNN-N-N

Where to buy [🔗](#)

Product specifications

Characteristic	Value	Description
D_SIZE GROUP2	2	Group 2:from 3 to 28 cc
Displacement	6,0	Displacement 6,0 cc
Drive gear	DB	Spline DIN 5482 B17 x 14 L=14 SC02
E_VALVE GROUP2	N	Without Valve
F_DRAIN GROUP2	N	Standard
Inlet size	F4	1/2 GAS
Mark position	N	Position Marking standard (on the top in relation to drive gear)
Mark type	N	Standard Marking
Mounting flange	02	Flange with pilot Ø80 mm and 4 holes for bolts
O-Ring, Inside Diameter	/	Slash
Outlet size	F4	1/2 GAS
Ports position	NN	Standard from catalogue
Project version	N	Standard Version of Project
ROTATION	R	Product with clockwise rotation
Rear cover	P1	Standard cover for pump
Screws	N	Screws standard
Seals	N	Standard seal
Slash separator	/	Slash
Valve setting	NNN	without setting



General specifications

Characteristic	Value
Proposition 65	Cancer and Reproductive Harm

For the most current information and other product assets, please use this link to visit the product page on Danfoss PowerSource [🔗](#)