



GEAR MOTOR GR2 FAN DRIVE FIXED DISPL

121.20.769.00 [🔗](#)

Model Code:

SNM2YN-/-014-R-4-02-AA-Y6-E5-E5-NN-N-A-/-XAS-N-N

Where to buy [🔗](#)

Product specifications

Characteristic	Value	Description
D_SIZE GROUP2		2
Displacement	014	Displacement 14 cc
Drive gear	AA	Taper 1:5 - M12 x 1,25 - Key = 3 CO02
E_VALVE GROUP2	Y	Proportional Valve with internal drain and anti-cavitation check valve on the bearings
F_DRAIN GROUP2	N	Standard
Inlet size	E5	7/8-14UNF
Mark position	N	Position Marking standard (on the top in relation to drive gear)
Mark type	N	Standard Marking
Mounting flange	02	Flange with pilot Ø80 mm and 4 holes for bolts
O-Ring, Inside Diameter	/	Slash
Outlet size	E5	7/8-14UNF
Ports position	NN	Standard from catalogue
Project version	4	Standard with precharge seal on cover
ROTATION	R	Product with clockwise rotation
Rear cover	Y6	Cover for motor per proportional valve and axial drain 9/16-18UNF-2B
Screws	A	Product with galvanized assembly screws (+nuts, washers or cap nuts if listed on the Bill of Material)
Seals	N	Standard seal



Characteristic	Value	Description
Single Stage Family	SNM2YN	Gr2 Bidir.Motor+PRV Valve
Slash separator	/	Slash
Valve setting	XAS	Setting proportional valve, type of connector 12 DT Volt and pressure 170 bar with oil ISO VG68 a 40°-50°C

General specifications

Characteristic	Value
Proposition 65	Cancer and Reproductive Harm

For the most current information and other product assets, please use this link to visit the product page on Danfoss PowerSource [🔗](#)