



TANDEM=GEAR PUMP GR3+GEAR PUMP GR1

181.25.773.00 [🔗](#)Model Code: PRT---033-/-2,2-R-1-07-SL-P1-E9-E8-NN-E4-E3-NN
-N-N-/-NNN-N-N**Where to buy** [🔗](#)

Product specifications

Characteristic	Value	Description
A: Tandem Gr.3+1 family	PRT	SNW3NN + SNP1NN
B: 1st stage displacement	033	Displacement 33cc
C: 2nd stage displacement	2,2	Displacement 2,2cc
D: Rotation	R	Product with clockwise rotation
E: Project version	1	With intermediate flange
F: Mounting flange	07	Flange SAE b with pilot D.101,6 and 2 holes for bolts
G: Drive gear	SL	Splined SAE J498-13T-16/32-Dp Class 1FIT -for flange SAE 'B' ; rear spline DIN 5482 22 x 19 L=16,5 SC47
H: Rear cover	P1	Standard Cover for pump
I: 1st stage inlet size	E9	27x1-5/8-12UN
J: 1st stage outlet size	E8	23,5x1-5/16-12UN
K: 1st stage ports position	NN	Standard from catalogue
L: 2nd stage inlet size	E4	3/4-16UNF
M: 2nd stage outlet size	E3	9/16-18UNF
N: 2nd stage ports position	NN	Standard from catalogue
O-Ring, Inside Diameter	/	Slash
O: Seals	N	Standard seal
OC DELIMITER (-)	-	-
P: Screws	N	Standard screws
Q: Valve setting	NNN	without valve



Characteristic	Value	Description
R: Mark type	N	Std Sauer Danfoss Marking
S: Mark position	N	Position Marking standard
Slash separator	/	Slash

General specifications

Characteristic	Value
Proposition 65	Cancer and Reproductive Harm

For the most current information and other product assets, please use this link to visit the product page on Danfoss PowerSource [🔗](#)