

Complete mobile pneumatic grease supply kits, suitable for 50 kg – drums in any kind of inside or outside use.
Max pressure achievable: 400 bar.

Art.no. **81920**

Mobile pneumatic grease supply kit for 50 kg - drums, consisting of:

- Pneumatic grease pump, art. no. 81860;
- Pressure regulator, art. no. 40400;
- 3 m – high pressure hose SAE 100 R2 AT, 1/4", art. no. 81003;
- High pressure grease control gun, 300 mm – steel braid outlet hose \varnothing ext. 10 mm and 4 - jaws - hydraulic coupler, art. no. 88410;
- High pressure Z – swivel, art. no. 88442;
- Follower plate, \varnothing 390 - 325 mm, art. no. 80634-VU;
- Metal drum cover, \varnothing 400 – 360 mm, art. no. 80560;
- Trolley with 2 wheels, art. no. 80723.



Art. no.	Max outlet pressure	Flow rate	Connection compressed air	Compressed air supply	Weight	Dimensions (LxWxH) (mm)
81920	400 bar	2400 g/min	1/4" BSP (F)	2-8 bar	16 kg	510x690x690

Art.no. **81960**

Mobile pneumatic grease supply kit for 50 kg - drums, consisting of:

- Pneumatic grease pump, art. no. 81860;
- Pressure regulator, art. no. 40400;
- 3 m – high pressure hose SAE 100 R2 AT, 1/4", art. no. 81003;
- High pressure grease control gun, 300 mm – steel braid outlet hose \varnothing ext. 10 mm and 4 jaws - hydraulic coupler, art. no. 88410 ;
- High pressure Z – swivel, art. no. 88442;
- Follower plate, \varnothing 390 - 325 mm, art. no. 80634-VU;
- Metal drum cover, \varnothing 400 – 360 mm, art. no. 80560;
- Trolley with 4 wheels, art. no. 80722.



Art. no.	Max outlet pressure	Flow rate	Connection compressed air	Compressed air supply	Weight	Dimensions (LxWxH) (mm)
81960	400 bar	2400 g/min	1/4" BSP (F)	2 - 8 bar	18 kg	600x600x1050