

250 bar




Art.no. **5100**

Portable, manual grease supply kit, consisting of metal 16 kg – pail, lever action grease pump, follower plate, \varnothing 230 mm, art. no. 07 5131, 1.5 m - rubber hose R1AT, \varnothing 1/4", ball valve and rigid outlet pipe with 4 – jaws – hydraulic coupler.



MADE IN ITALY

Art. no.	Max outlet pressure	Delivery per stroke	Connections	Weight	Dimensions (LxWxH) (mm)
5100	250 bar	8 g	1/4" BSP (M)	5.5 kg	240x490x630




250 bar



Art.no. **5105**

Portable, manual grease supply kit, consisting of metal 16 kg – pail with 2 wheels, lever action grease pump, follower plate, \varnothing 230 mm, art. no. 07 5131, 1.5 m - rubber hose R1AT \varnothing 1/4", ball valve and rigid outlet pipe with 4 – jaws – hydraulic coupler.

Art. no.	Max outlet pressure	Delivery per stroke	Connections	Weight	Dimensions (LxWxH) (mm)
5105	250 bar	8 g	1/4" BSP (M)	7.5 kg	250x540x630



250 bar



Art.no. **5115**

Manual grease supply kit, consisting of metal 16 kg – pail, mounted on trolley, art.no. 4350, with fixation bracket, 2 wheels and frontal support leg, with lever action grease pump, follower plate, \varnothing 230 mm, art. no. 07 5131, 1.5 m - rubber hose R1AT, \varnothing 1/4", ball valve and rigid outlet pipe with 4 – jaws – hydraulic coupler.

Art. no.	Max outlet pressure	Delivery per stroke	Connections	Weight	Dimensions (LxWxH) (mm)
5115	250 bar	8 g	1/4" BSP (M)	8 kg	510x580x880

