

LITHIUM IRON PHOSPHATE (LiFePO4) BATTERY LP1500 Series

0.64~5.12KWH

The Must LP1500 SERIES LiFePO4 battery is fit for E-mobility, Energy Storage System, Defense & Security, telecom outdoor applications, renewable energy systems, and other harsh environment applications.



- 6000 cycles @ 80% DOD, 25 °C for effectively lower total of ownership cost.
- Safe, reliable and long life
- Support series or parallel connection
- Battery Management System (BMS) is incorporated against abuse.
- Superior charge/discharge efficiency
- Low maintenance batteries with stable chemistry.
- Extreme heat tolerance
- Lithium batteries provide more Wh/Kg while also being up to 1/3 the weight of its SLA equivalent.
- Support Bluetooth and APP to view battery information (optional)

Application



Technical Data		LP15-1250	LP15-12100	LP15-12150	LP15-12200	LP15-24100	LP15-24150	LP15-24200	
Nominal Voltage		12.8V				25.6V			
Nominal Capacity		50Ah	100Ah	150Ah	200Ah	100Ah	150Ah	200Ah	
Nominal energy		640Wh	1280Wh	1920Wh	2560Wh	2560Wh	1920Wh	5120Wh	
Max. output power		0.6KW	1.2KW	1.2KW	1.2KW	2.5KW	2.5KW	2.5KW	
Life Cycles		6000 cycles @ 80% DOD, 25°C							
Recommended Charge Voltage		14.6V				29.2V			
Recommended Charge Current		20A		40A		20A		40A	
End Of Discharge Voltage		10V				20V			
Standard Method	Charge	10A	20A	30A	40A	20A	30A	40A	
	Discharge	25A	50A	75A	100A	50A	75A	100A	
Maximum Continuous Current	Charge	25A	50A	75A	100A	60A	75A	100A	
	Discharge	50A	100A	100A	100A	100A	100A	100A	
BMS Cut-Off Voltage	Charge	15.4 V (3.85V/Cell)				30.8 V (3.85V/Cell)			
	Discharge	9.2 V (2s) (2.3V/Cell)				18.4 V (2s) (2.3V/Cell)			
Temperature	Charge	0~50°C							
	Discharge	-20~60°C							
Storage Temperature		-5~35°C							
Shipment voltage		≥12.8V				≥25.6V			
Case Material		ABS+PC							
Machine Dimension (W*H*D) (mm)		260*167*210	339*185*218	339*185*218	502*186*243	502*186*243	522*240*218	522*240*218	
Package Dimension (W*H*D) (mm)		carton box	315*225*260	385*230*260	385*230*260	520*225*280	520*225*280	545*285*288	545*285*288
N.W (kg)		7.5	12	15	21	20	29	37	
G.W (kg)		carton box	/	13	16	22	21	31	38

* Variations in dimensions and weights may occur due to production batches.

Charge Retention And Capacity Recovery Capability	Standard charge the battery, and then put aside at room temperature for 28d or 55°C for 7d, Charge retention rate≥90%, Recovery rate of charge≥90%
Warranty	5 years
Certification & Standards	CE-EMC (EN 61000-6-3+A1+AC EN IEC 61000-6-1); UN38.3/ MSDS

*The technical specifications of this document are subject to change without any notice