

MOTIP Super Fast Wax

Technical Information



Protect and restore the gloss of lacquered surfaces on your car easily with the maintenance, product MOTIP Superfast Wax. Super Fast Wax protects against the weather, gives a glossy result, reduces the adhesion of dirt and contains silicones.

Ord.-no: 000744

Quality & properties

- User-friendly
- Protects against weather influences
- Gives a glossy result
- Reduces the adhesion of dirt
- Contains silicones

Physical & chemical data

- Base: Abrasives and PE wax
- Colourname: no colour
- Smell: Characteristic
- Surfaces: Lacquered surfaces, both metallic and non-metallic
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- pH value: 8,5
- Flash point: >100
- Storage stability: 5 years
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- Store frost-free.
- Do not use in the blazing sun.
- Shake well before use.
- The surface should be clean and dry.
- Apply Superfast Wax with a moist cloth in a thin, equal layer and allow to dry.
- Polish to high gloss with a dry, soft cloth.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.