



PowerX series

Low voltage wall mounted battery



Thin and delicate appearance

Products are thin, compact pack group process.

The appearance is beautiful, the surface is made of special materials.



Reliable waterproof

IP65 standard for outdoor use

15 years design life, reliable guarantee



Economical and efficient

High energy density, saving installation site

Plug and play, easy and efficient wiring

SYSTEM PARAMETER

Item	PowerX W5	PowerX W10
		
Cell type	LiFePO4	LiFePO4
Nominal energy	5.12kWh	10.24kWh
Nominal capacity	100Ah	200Ah
Rated voltage	51.2Vdc	51.2Vdc
Operating voltage range	43.2Vdc~57.6Vdc	43.2Vdc~57.6Vdc
Maximum charge/discharge current	50A/100A	100A/150A
DOD	95%	95%
Communication	RS485 , CAN , WIFI(optional)	RS485 , CAN , WIFI(optional)
Expansion	Up to 8 units in parallel	Up to 8 units in parallel
Dimensions (W*D*H)	420*140*650mm	630*184*750 mm
Weight	≈ 45kg	≈ 85kg
Temperature	Charge: -10~50°C; Discharge: -20~50°C	Charge: -10~50°C; Discharge: -20~50°C
Humidity	5~95%RH, No condensation	5~95%RH, No condensation
Altitude	< 2000m	< 2000m
Protection level	IP65	IP65
Installation	Wall-mounted, door-to-battery	Wall-mounted, door-to-battery
Cycle life	> 6000@25°C@0.5C	> 6000@25°C@0.5C
Certification	IEC62619/CE/UN38.3/RoHs	IEC62619/CE/UN38.3/RoHs

Address
No.8, Keji Avenue, Gaocheng
Town, Yixing City, Jiangsu
Province, P.R. CHINA

Website
www.en.feibattery.com

Base
ESS:
Yixing, China
Cylindrical Cell:
Yichun, China

**Far East Greater Bay Area
Headquarters**
located on 34F, Block C, Hongrongyuan
Huanzhi Center, Longhua District, Shenzhen

Customer Service Center
located at Wheelock International Plaza,
No. 1717 Nanjing West Road, Jing'an District,
Shanghai

Sales Office
EUR :Rotterdam, Netherland
Frankfurt, Germany
Milano, Italy

ASIA : Shenzhen&Shanghai, China

**Service Center
& Warehouse**
EUR :Rotterdam, Netherland
Frankfurt, Germany
Fermo, Italy