



WINCH BST S 26000 LBS



Technical specifications

Pull capacity (single line)	26000 lbs / 11793 Kg
Motor	4,5 KM / 6,1 kW
Controls	wired / wireless remote control
Gear	3 - stage planetary
Gear ratio	450:1
Brake	internal ratchet brake in the gearbox
Rope	26,5 m x ø 13,8 mm
Net weight	106 Kg
Dimensions L x W x H	638 mm x 298 mm x 300 mm
Fairlead	4-ways rolles
Mounting bolt pattern	254 mm x 114,3 mm 254 mm x 190,5 mm

Included :

- hook
- steel rope
- roller fairlead
- mounting screws
- wired remote control
- wireless remote control
- control set
- rope tensioner
- battery isolation switch

Line speed and motor (first layer)

Line pull	Lbs	0	5000	10000	15000	20000	26000
	Kg	0	2268	4536	6804	9072	11793
Line speed	M/min 24 V	9,3	3,4	2,5	2	1,6	1,1
Motor current	Amper 24 V	23	90	140	180	230	280

Line pull and cable capacity

Layer of cable		1	2	3	4
Rated line pull	Lbs	26000	21553	18406	16060
per layer	Kg	11793	9776	8348	7275
Cable capacity	M	5,4	12	19,7	26,5
per layer					