

S6-EH3P(29.9-50)K-H

Solis Three Phase High Voltage Energy Storage Inverters

Features:

- 2 seconds of 160% overload capability
- Supports a maximum input current of 20A, making it ideal for all high-power PV modules of any brand
- Real-time battery monitoring, remote upgrade, and battery healing function to prolong battery life
- Supports peak shaving features in "self-use" and "generator" modes
- Supports Unbalanced and Half-Wave Loads on both the Grid and Backup Port
- A wide battery voltage range accommodates the prevalent high-voltage lithium batteries found in the market
- Battery charging/discharging current 140A/70A+70A, suitable for 280Ah cell standard 0.5C application condition
- Supports 200% DC/AC ratio and makes full use of PV charging, providing a long backup

Models:

S6-EH3P29.9K-H

S6-EH3P30K-H

S6-EH3P40K-H

S6-EH3P50K-H



DATASHEET

S6-EH3P(29.9-50)K-H

Models	29.9K	30K	40K	50K
Input DC (PV side)				
Recommended max. PV array size	59.8 kW	60 kW	80 kW	100 kW
Max. usable PV input power	59.8 kW	60 kW	80 kW	96 kW
Max. input voltage			1000 V	
Rated voltage			600 V	
Start-up voltage			180 V	
MPPT voltage range			150 - 850 V	
Max. input current	40 A / 40 A / 40 A			4 × 40 A
Max. short circuit current	60 A / 60 A / 60 A			4 × 60 A
MPPT number / Max. input strings number	3 / 6			4 / 8
Battery				
Battery type			Li-ion	
Battery voltage range			150 - 800 V	
Max. charge / discharge power	32.1 kW	33 kW	44 kW	55 kW
Max. charge / discharge current			70 A × 2 ⁽¹⁾	
No. of battery inputs			2	
Max. charge / discharge power of each input	32.1 kW	33 kW	35 kW	35 kW
Communication			CAN / RS485	
Output AC (Grid side)				
Rated output power	29.9 kW	30 kW	40 kW	50 kW
Max. apparent output power	29.9 kVA	30 kVA	40 kVA	50 kVA
Rated grid voltage			3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V	
Rated grid frequency			50 Hz / 60 Hz	
Rated grid output current	45.4 A / 43.2 A	45.6 A / 43.3 A	60.8 A / 57.7 A	76 A / 72.2 A
Max. output current	45.4 A / 43.2 A	45.6 A / 43.3 A	60.8 A / 57.7 A	76 A / 72.2 A
Power factor			> 0.99 (0.8 leading - 0.8 lagging)	
THDi			< 3%	
Input AC (Grid side)				
Max. AC passthrough current	90.8 A / 86.4 A	91.2 A / 86.6 A	121.6 A / 115.4 A	152 A / 144.4 A
Rated input voltage			3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V	
Rated input frequency			50 Hz / 60 Hz	
Input Generator				
Max. input power	29.9 kW	30 kW	40 kW	50 kW
Rated input current	45.4 A / 43.2 A	45.6 A / 43.3 A	60.8 A / 57.7 A	76 A / 72.2 A
Rated input voltage			3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V	
Rated input frequency			50 Hz / 60 Hz	
Output AC (Back-up)				
Rated output power	29.9 kW	30 kW	40 kW	50 kW
Max. apparent output power			1.6 times of rated power, 2 s	
Back-up switch time			< 10 ms	
Rated output voltage			3/N/PE, 220 V / 380 V; 3/N/PE, 230 V / 400 V	
Rated frequency			50 Hz / 60 Hz	
Rated output current	45.4 A / 43.2 A	45.6 A / 43.3 A	60.8 A / 57.7 A	76 A / 72.2 A
THDv (@linear load)			< 2%	
Efficiency				
Max. efficiency			97.8%	
EU efficiency			97.4%	
BAT charged by PV max. efficiency			98.5%	
BAT charged / discharged to AC max. efficiency			97.5%	
Protection				
Anti-islanding protection			Yes	
Output over current protection			Yes	
Short circuit protection			Yes	
Integrated DC switch			Yes	
DC reverse-polarity protection			Yes	
Surge protection			DC Type II / AC Type II	
Integrated AFCI 2.0			Optional	
General Data				
Dimensions (W × H × D)			530 × 880 × 290 mm	
Weight			73 kg	
Topology			Transformerless	
Self-consumption (night)			< 35 W	
Operating ambient temperature range			-25 ~ +60°C	
Relative humidity			0 - 95%	
Ingress protection			IP66	
Cooling concept			Intelligent fan-cooling	
Max. operation altitude			4000 m	
Grid connection standard	G99, VDE-AR-N 4105/VDE V 0124, EN 50549-1/EN 50549-10, VDE 0126/UTE C 15/VFR:2019, NTS 631/RD 1699/RD 244/UNE 206006/UNE 206007-1, CEI 0-21, C10/11, NRS 097-2-1, TOR, EIFS 2018.2, IEC 62116, IEC 61727, IEC 60068, IEC 61683, EN 50530, MEA, PEA, PORTARIA Nº 140, DE 21 DE MARÇO DE 2022			
Safety / EMC standard	IEC/EN 62109-1/-2, IEC/EN 61000-6-2/-4, EN 55011			
Features				
PV connection	MC4 Quick connection plug			
Battery connection	Terminal connector			
AC connection	Terminal Block			
Display	7.0" LCD display & Bluetooth + APP			
Communication	CAN, RS485, Ethernet, Optional: Wi-Fi, Cellular, LAN			

(1) Supporting parallel 140A input.