

booster EX2



To the product

Technical data

Article	146.738	
Voltage	230 V	
Frequency	50/60 Hz	
Power	3000 W	
Welding rod	ø 3-4 mm / 0.12-0.16 in	
Material output ø 3 mm	1.5 kg/h	3.3 lb/h
Material output ø 4 mm	2.2 kg/h	4.85 lb/h
Welding materials	HDPE; LDPE; LLDPE; PP	
Weldable sheet/membrane thickness	10-15 mm	0.39-0.59 in
Air guide	Internal	
Screw heating	Air heated	
Air temperature control	Open loop	
LQS	No	
Display	No	
Brushless blower motor	No	
Brushless drive motor	No	
LED Working light	No	
Length	500 mm	19.68 in
Width	140 mm	5.51 in
Height	380 mm	14.96 in
Weight	6.4 kg	14.1 lb

booster EX2

Technical data

Power cable length	3 m	9.84 ft
Plug	EU, 2 poles, 16A	
Noise emission level	74 dB (A)	
Approvals	CE	
Protection class	II	
Country of origin	P.R. China	

Scope of delivery

Welding shoe K8/K10 IA; Heating element, 230V/2200W; Carbon brushes; Allen wrench 3 mm; Wire brush, brass; Tool case

Product items

146.738 booster EX2, 230V/3000W, EU plug