



### TECHNICAL DATA

Maximum Coil Temperature at 68°F (20°C) Ambient	218°F (105°C)
Arc Suppression (TVS)	Included
Power Consumption (cold) - at rated voltage	22 watts
Maximum Ambient Temperature	122 °F
Voltage/Frequency	24 VDC
Operating Voltage Range	+/- 10% nominal
Duty Cycle Rating	100 %
Connector	Deutsch DT04-2P
Connector Environment Rating	IP69K
Solenoid Tube Diameter	.75 in.
Coil Nut Torque	4.5 lbf in.
Model Weight	0.53 lb.

### PROPORTIONAL PERFORMANCE DATA

Maximum Current	590 mA
Nominal Coil Resistance at 122°F (50°C) Stabilized	37.2 ±5% ohms
Nominal Coil Resistance at 68°F (20°C) Cold	26.2 ±5% ohms

### USED WITH

DMDA	DMDAS	DNCA	DNDA	DNDAS	DNDC	DNDY	DNDYS	FMDA	FMDB
FPCC	FPCH	FPFK	FPHK	HDDA	PRDM	PRDN	PSDL	PSDP	RBAN
RBAP	991723001	991723002							

## TECHNICAL FEATURES

- Coil windings utilize Class N, (392° F [200 °C] rated) magnet wire.
- A TVS surge suppression diode is built into DC coils. Nominal breakdown voltage: 68V. Model code 1.5 KE68CA Steady state power dissipation @ 75°C is 6.5 W and peak pulse dissipation is 1500 W for 1 ms, nonrepetitive.
- Power cable with mating connector is required and is not included with product.
- The Deutsch DT04-2P connector satisfies the requirements of thermal shock tests. In this test, the coil is energized to achieve its stabilized temperature and then immediately immersed into ice cold water. This process is repeated 5 times, after which, the insulation resistance of the coils should not fall below 10 megohms.
- The coil is magnetically symmetrical and can be mounted in either direction on the solenoid tube without affecting performance.
- For optimum proportional performance, an amplifier with current sensing and adjustable dither should be used. Dither should be adjustable between 100 - 250 Hz.
- IP rating is dependent on the coil connector and the mating connector used.
- RoHS compliant. Restricted materials less than 0.1% total by weight.
- The external steel shell is plated with clear zinc trivalent.