



80L GS

GMS
hydraulic

Specifications

Spool: 1.. 12 Spools / Double - Single - Closed Center - Motor - Floating - Regenerative Spool

Liter: 80L Nominal -100L Max

Ports: 1/2 Standard

Front Cap: Handle - Mechanical Joystick - Hydraulic Joystick - Remote Cable Control - Lock Handle

End Cap: Spring - Detent - Floating - Pneumatic - Proportional Coil - Hydraulic Control
Electro Hydraulic - Remote Cable Control

Open Center / Carry over / Parallel Circuit

Features

Simple, compact and heavy duty designed sectional valve from 1 to 12 sections for open and closed center hydraulic systems.

- ▶ Fitted with a main pressure relief valve and a load check valve on every working section
- ▶ Available with parallel, tandem or series circuit.
- ▶ Optional carryover port.
- ▶ A wide variety of auxiliary valves.
- ▶ Intermediate sections for several types of circuit.
- ▶ Available manual, pneumatic, hydraulic, electro-hydraulic, and remote with flexible cables spool control kits.
- ▶ Diameter 18 mm (0.71 in) interchangeable spools.

Additional information

This catalogue shows the product in the most standard configurations. Please contact Sales Dpt. for more information that is detailed or special request.

WARNING!

All specifications of this catalogue refer to the standard product at this date.

GMS, oriented to a continuous improvement, reserves the right to discontinue, modify or revise the specifications, without notice.

GMS IS NOT RESPONSIBLE FOR ANY DAMAGE CAUSED BY AN INCORRECT USE OF THE PRODUCT.

1st edition April 2018:

- Valve general informations

Working conditions.	page 4
Standard threads.	page 4
Dimensional data.	page 5
Performance data.	page 6
Hydraulic circuit.	page 7
Complete sections ordering codes	page 8

- Inlet section

Parts ordering codes.	page 10
Dimensional data and hydraulic circuit	page 11
Inlet relief options.	page 13

- Inlet section for special application

Configuration with rotary commutator.	page 16
---	---------

- Working section

Parts ordering codes (mechanical control).	page 17
Spools.	page 19
“A” side spool positioners.	page 20
“B” side options	page 33
Complete controls.	page 38
Port valves.	page 42

- Intermediate section

CS1 mid return manifold section.	page 45
DFG pressure compensated flow divider section.	page 46
EI service relief valve section.	page 47

- Outlet section

Parts ordering codes.	page 48
Dimensional data and hydraulic circuit	page 49

Valve general informations

Working conditions

This catalogue shows technical specifications and diagrams measured with mineral oil of 46 mm²/s – 46cSt viscosity at 40°C temperature.

Nominal flow rating		80 l/min.	
Max. flow		100 l	
Operating pressure (max.)	Series-parallel (tandem) circuit	315 bar	4600 psi
Back pressure (max.)	on outlet port T	25 bar	360 psi
Internal leakage A(B)→T	Δp=100 bar – 1450 psi fluid and valve at 40°C	3cm ³ /min.	0.18 in ³ /min.
Hydraulic fluid		Mineral base oil	
Fluid temperature	with NBR seals	from - 20° to 80°C	
	with FPM (VITON) seals	from - 20° to 100°C	
Viscosity	operating range	from 15 to 75 mm ² /s	from 15 to 75 cSt
	Min.	12 mm ² /s	12 cSt
	Max.	400 mm ² /s	400 cSt
Max. level of contamination		19/16 – ISO 4406	
Tie rods tightening torque (wrench 13)		30 Nm	22 lbft


Standard threads

REFERENCE STANDARD

PORTS	BSP (ISO 228/1)	UN-UNF (ISO 11926-1)	METRIC (ISO 6149-1)
Inlet P	G 1/2	7/8 – 14 (SAE 10)	M22x1,5
A and B ports	G 1/2	3/4 – 16 (SAE 8)	M22x1,5
Outlet T and carry-over C	G 3/4	7/8 – 14 (SAE 10)	M27x2
PILOT PORTS			
Hydraulic ports	G 1/4	-	-
Pneumatic ports	G 1/8	-	-

Valve general informations

Dimensional data



TYPE	A		B		Weight	
	mm	in	mm	in	kg	lb
80L GS 10/1	132	5.20	82	3.23	7.5	16.53
80L GS 10/2	173	6.81	123	4.84	10.8	23.81
80L GS 10/3	214	8.43	164	6.46	14	30.86
80L GS 10/4	255	10.04	205	8.07	17.5	38.58
80L GS 10/5	296	11.65	246	9.69	20.7	45.64
80L GS 10/6	337	13.27	287	11.30	24	52.91



TYPE	A		B		Weight	
	mm	in	mm	in	kg	lb
80L GS 10/7	378	14.88	328	12.91	27.3	60.19
80L GS 10/8	419	16.50	369	14.53	30.6	67.46
80L GS 10/9	460	18.11	410	16.14	34	74.96
80L GS 10/10	501	19.72	451	17.76	37.2	82.00
80L GS 10/11	542	21.34	492	19.37	40.4	89.07
80L GS 10/12	583	22.95	533	20.98	43.6	96.12

Valve general informations

Performance data (pressure drop vs. flow)



Open centre

From side inlet to side outlet.





Inlet to work port

From side inlet to A port (spool in position 1) or B port (spool in position 2).



Work port to outlet

From A port (spool in position 2) or B port (spool in position 1) to side outlet.




Valve general informations

Hydraulic circuit

Parallel circuit


Standard configuration with open centre and side inlet and outlet.



Description example
80L GS10/2/AC(X-100)/18L/18L/RC

Series-parallel (tandem) circuit


A special working section kit is required. Tandem section is fed by the free flow pressure line; it is excluded when an upstream section is operated.



Description example
80L GS10/2/AC(X-100)/18L/SP-18L/RC



Series circuit

It is obtained by mounting a 1S series spool on a standard parallel section.
NOTE – The flows P→A and P→B, on the series spool, are reversed.



Description example
80L GS10/2/AC(X-100)/1S8L/SP-18L/RC

Directional valve with right inlet



Description example
80L GS10/2/BC(X-100)/18L/18L/RC

Complete sections ordering codes

Standard configuration with side inlet and outlet

80L GS10 / 2 / AC(X-100) / (P) - 18L.P3T / EI1 / (P) - 18L.P3T / RC

Nr. of working
section


1.

2.

3.

4.

It's not necessary to indicate the "P" letter in the complete valve description with parallel circuit (standard); in case of other circuits, they must be specified by the related letter (SP).



1. Inlet section * page 10

TYPE	CODE	DESCRIPTION
AC(X-100)	30 08 5749	Side inlet with direct pressure relief valve
AD(X-100)	30 08 5663	Upper inlet with direct pressure relief valve
AC(V)	30 08 5659	Without pressure relief valve

2. Working section * page 17

TYPE	CODE	DESCRIPTION
P-18L	80W010000	Parallel circuit, prearranged for port valves, double acting spool with spring return, lever control
P-1S8L	80W010001	As previous one, with series circuit spool ("P" omitted in description)
SP-18L	80W010003	As previous one, with series-parallel (tandem) circuit

3. Intermediate sections * page 46

TYPE	CODE	DESCRIPTION
DFG	30 08 5774	Pressure compensated flow divider section
EI1(X-100)	30 08 5732	With direct overpressure relief valve
EI2(X-100)	30 08 5733	With direct overpressure relief valve and auxiliary inlet

4. Outlet section * page 48

TYPE	CODE	DESCRIPTION
RC	30 08 5660	Side outlet
RD	30 08 5711	Upper outlet
RE	30 08 5712	Upper outlet with side carry-over sleeve
RK	30 08 5713	Upper outlet with closed centre
RV	30 08 5714	With backpressure valve the combination with electro-hydraulic control is required
VRC	30 08 5715	Backpressure valve for VRC configuration


NOTE (*) - Items are referred to **BSP** thread.

Valve general informations

Complete sections ordering codes

Configuration with 2 side inlets and mid return manifold

80L GS10 / 2 / AC(X-100) / 18L.P3T / CS1 / ED - 18L.P3T / BC(X-100)



5. Return manifold *

page 45

TYPE	CODE	DESCRIPTION
CS1	30 08 5779	Mid return manifold with G3/4 outlet port

6. Right inlet working section *

TYPE	CODE	DESCRIPTION
P-ED-18L	80W010007	As previous one prearranged for port valves ("P" omitted in description)
P-ED-1S8L	80W010008	As previous one with series circuit spool ("P" omitted in description)
SP-ED-18L	80W010006	As previous one with series-parallel (tandem) circuit

7. Right inlet section *

TYPE	CODE	DESCRIPTION
BC(X-100)	30 08 5753	Side inlet with direct pressure relief valve
BD(X-100)	30 08 5757	Upper inlet with pilot operated pressure relief valve
BC(V)	30 08 5769	Side inlet with valve blanking plug

8. Assemb. kit without intermediate section

CODE	DIRECTIONAL VALVE
30 05 6076	Tie rod kit for 1 section valve
30 05 6078	Tie rod kit for 2 sections valve
30 05 6079	Tie rod kit for 3 sections valve
30 05 6080	Tie rod kit for 4 sections valve
30 05 6081	Tie rod kit for 5 sections valve
30 05 6082	Tie rod kit for 6 sections valve
30 05 6083	Tie rod kit for 7 sections valve
30 05 6084	Tie rod kit for 8 sections valve
30 05 6085	Tie rod kit for 9 sections valve
30 05 6112	Tie rod kit for 10 sections valve
30 05 6113	Tie rod kit for 11 sections valve
30 05 6077	Tie rod kit for 12 sections valve


9. Assemb. kit with intermediate section

CODE	DIRECTIONAL VALVE
30 05 6079	Tie rod kit for 2 sections valve (with CS1)
30 05 6080	Tie rod kit for 3 sections valve (with CS1)
30 05 6081	Tie rod kit for 4 sections valve (with CS1)
30 05 6082	Tie rod kit for 5 sections valve (with CS1)
30 05 6083	Tie rod kit for 6 sections valve (with CS1)
30 05 6084	Tie rod kit for 7 sections valve (with CS1)
30 05 6085	Tie rod kit for 8 sections valve (with CS1)
30 05 6112	Tie rod kit for 9 sections valve (with CS1)
30 05 6113	Tie rod kit for 10 sections valve (with CS1)

NOTE (*) - Items are referred to **BSP** thread.


Parts ordering codes

80L GS10 / AC (X - 100) ELN - MAN14 - 12VDC



Available configurations

- AC: with side inlet, for left inlet (standard) directional valve
- AD: with upper inlet, for left inlet (standard) directional valve
- BC: with side inlet, for right inlet directional valve
- BD: with upper inlet, for right inlet directional valve



1. Inlet cover body * page 11

CODE	DESCRIPTION
-	Standard body

2. Parts *

TYPE	CODE	DESCRIPTION
MAN18	30 05 6100	G1/8 Pressure gauge arrangement
MAN14	30 05 6099	G1/4 Pressure gauge arrangement

3. Inlet relief valve options page 13

TYPE	CODE	DESCRIPTION
KE10K01 : direct pressure relief valve type X (X-100)	30 05 4912	Range 20 to 315 bar / 290 to 4600 psi standard setting 100 bar / 1450 psi

KE10K02 : pilot operated pressure relief valve type Z
(Z-100) 30 05 4915 Range 25 to 315 bar / 360 to 4600 psi
standard setting 100 bar / 1450 psi

Standard setting is referred to 6 l/min flow.

V	30 05 4914	Relief valve blanking plug
---	------------	----------------------------

NOTE (*) - Items are referred to **BSP** thread.

4. Inlet valve options page 15

TYPE	CODE	DESCRIPTION
-	30 05 4914	Relief valve blanking plug (omit in description)
F	-	Inlet anti-cavitation valve
L	-	Hydraulic pilot unloader valve
Solenoid operated unloader valve		
ELN	30 05 6108	Without emergency
ELP	30 05 6109	Push-button emergency
ELT	30 05 6110	Push and twist type with detent emergency

5. Coils

TYPE	CODE	DESCRIPTION
12VDC	20 03 2268	Coil type BER , ISO4400 integrated type 12VDC
24VDC	20 03 2269	Coil type BER , ISO4400 integrated type 24VDC

Inlet section

Dimensional data and hydraulic circuit




For left inlet directional valve (standard)

With side inlet, type AC


Allen wrench 8
24 Nm / 17.7 lbft

D - D



G 1/2

Description example
AC(X-100)

With upper inlet, type AD



Allen wrench 8
24 Nm / 17.7 lbft

D - D


Description example
AD(X-100)

For right inlet directional valve



With side inlet, type BC

Description example
BC(X-100)


D - D



With upper inlet, type BD

Description example
BD(X-100)

D - D




Inlet section

Dimensional data and hydraulic circuit

For left inlet directional valve (standard)


With side inlet, type PC

Bushing to divide pump and carryover line assemble to pump section.



For right inlet directional valve

With side inlet, type PD



Inlet section


Inlet relief options

Direct pressure relief valve

KE10K01 (X - 100)


Standard setting in bar

Adjustment type (X, XH)




Adjustment type



X: with screw



XH: valve set and locked



Performance data



Inlet section


Inlet relief options

Pilot pressure relief valve

KE10K02 (Z - 100)

Standard setting in bar



Adjustment type (Z, ZH)





Adjustment type

Z: with screw


ZH: valve set and locked



Performance data



V: relief valve blanking plug



Inlet section

Inlet valve options

Unloader valves





Description example: AC (X - 100) **ELN** - **12VDC**

Hydraulic operated valve: **L**
Solenoid operated valve: **ELN**
ELP
ELT



Feeding voltage: for
solenoid operated

Solenoid operated

Emergency with push button and spring return; for detent position turn the button after press it.
WARNING: the manual override option is intended for emergency use, not for continuous duty operation.





Hydraulic operated



Anti-cavitation valve

Description example: AC (X - 100) **F**





Inlet section for special applications

Configuration with rotary commutator

Dimensional data and hydraulic circuit



Drawing and circuit are referred to left inlet directional valve.



Working section

Parts ordering codes (mechanical control)

Description example:



1. Working section kit *			2. Spools page 19		
TYPE	CODE	DESCRIPTION	TYPE	CODE	DESCRIPTION
P	-	With paralle circuit	2	30 01 3557	Double acting, 3 positions, with A and B open to tank in neutral position
SP	-	With serie-parallel (tandem) circuit	3	30 01 3563	Single acting on A, 3 positions, B plugged; requires G1/2 plug (see part a)
Include body, seals, rings and load check valve.			4	30 01 3564	Single acting on B, 3 positions, A plugged; requires G1/2 plug (see part a)
2. Spools page 19			2H	30 01 3558	Double acting, 3 positions, with A and B partially open to tank in neutral position
TYPE	CODE	DESCRIPTION	1AH	30 01 3561	Double acting, 3 positions, with A partially open to tank in neutral position
1	30 01 3556	Double acting, 3 positions, with A and B closed in neutral position	1BH	30 01 3562	Double acting, 3 positions, with B partially open to tank in neutral position
1A	30 01 3559	Double acting, 3 positions, with A open to tank in neutral position	1S	30 01 3565	As type 1, for series circuit
1B	30 01 3560	Double acting, 3 positions, with B open to tank in neutral position	2S	30 01 3566	As type 2, for series circuit

Working section


Parts ordering codes (mechanical control)

2. Spool options page 19			3. "A" side spool positioners page 20		
TYPE	CODE	DESCRIPTION	TYPE	CODE	DESCRIPTION
Special spools for particular positioner kits			Particular positioner kits for special spools		
. page 32					
5BY	30 01 3654	Double acting, 4 positions, float in position 3 with spool out, 13QN type positioner kit is required	13QN	30 07 5564	4 positions with spring return in neutral position and detent in pos.3: for 5BY spool
8F	30 01 3567	Double acting, 3 positions, regenerative in position 1, 8CR type positioner kit is required	8CR	30 07 5565	3 positions with spring return in neutral and reduced spool stroke: for 8F spool
3. "A" side spool positioners page 20			4. "B" side options page 33		
TYPE	CODE	DESCRIPTION	TYPE	CODE	DESCRIPTION
8	30 07 5349	With spring return in neutral position	L	30 07 5363	Standard lever box
8D	30 07 5352	As type 8, M8 female threaded pin extension for dual control	LF1	30 07 5365	Lever box with spool stroke limiter in position 1
8D1	30 07 5551	As type 8, pin with Ø 8 mm (0.31 in) radial hole	SL	-	Without lever box
8D2	30 07 5353	As type 8, M8 male threaded pin extension for dual control	SLP	30 07 5366	Without lever box, with dust-proof plate
8TL	30 07 5552	As type 8 with pin control with flexible cable	SLCZ	-	Without lever box, with endcap.
8F2	30 07 5350	As type 8 with adjustable stroke limiter	LB	30 07 5367	Steel lever
19	30 07 5553	2 positions, with spring return in neutral position from position 1	LEB	30 07 5369	Safety lever box, vertical configuration
20	30 07 5554	2 positions, with spring return in neutral position from position 2	TQ	30 07 5354	Flexible cable connection; for CG cables
11	30 07 5351	With detent in position 1, neutral and 2	LCB	30 07 5370	Joystick lever for 2 sections operation
12	30 07 5555	Detent in positions 1 and 2			
15	30 07 5556	2 positions, detent in pos. 1 and neutral			
16	30 07 5557	2 positions, detent in pos. 2 and neutral			
17	30 07 5558	With spring return position 1			
18	30 07 5559	With spring return position 2			
17D	30 07 5560	With spring return position 1 and pin with M8 female thread for dual control			
18D	30 07 5561	With spring return position 2 and pin with M8 female thread for dual control			
9B	30 07 5386	With detent in position 1 and spring return in neutral position			
10B	30 07 5387	With detent in position 2 and spring return in neutral position			
11B	30 07 5388	With detent in position 1, 2 and spring return in neutral position			
8MG3(NO)	30 07 5562	As type 8 and operation with microswitch in positions 1 and 2, contact normally open			
8MG3(NC)	30 07 5563	As previous, with contact normally closed			
8P	30 07 5399	ON-OFF pneumatic kit			
8PF	30 07 5596	Proportional pneumatic kit			
8EP3	30 07 5443	ON-OFF 12VDC electro-pneumatic kit			
8EP4	30 07 5400	ON-OFF 24VDC electro-pneumatic kit			
	30 07 5345	ON-OFF 12VDC electro-pneumatic kit with manifold			
8E13	30 07 5346	ON-OFF 24VDC electro-pneumatic kit with manifold			
	30 07 5401	ON-OFF 12VDC electro-hydraulic kit			
8E13F2	30 07 5361	ON-OFF 24VDC electro-hydraulic kit			
	-	12 VDC ON/OFF electrohydraulic kit with adjustable stroke limiter			
-	-	24 VDC ON/OFF electrohydraulic kit with adjustable stroke limiter			
5. Port valves page 42			6. Complete controls page 38		
TYPE	CODE	DESCRIPTION	TYPE	CODE	DESCRIPTION
Assembled on section			8IM	30 07 5372	-
P3T	30 05 4940	A and B ports valve blanking plugs	R	30 07 5373	-
C	-	Anti-cavitation			
<u>Anti-shock valve</u>			Proportional hydraulic control type 8IM and ON/OFF solenoid controls type 8ES and rotative control type R .		
P	30 05 6195	From 0 to 315 bar / 0 to 4600 psi standard setting 100 bar / 1450 psi			
<u>Anti-shock and anti-cavitation valve</u>					
U	30 05 4908	From 0 to 315 bar / 0 to 4600 psi standard setting 100 bar / 1450 psi			
<i>Standard setting is referred to 6 l/min flow.</i>					
a. "A" and "B" ports plugs			b. Optional handlevers		
TYPE	CODE	DESCRIPTION	TYPE	CODE	DESCRIPTION
G1/2	30 05 4919	For single acting spools type 3 and 4	AL01/M10x200	30 05 4989	Lenght L = 200mm / 7.87in


Working section

Spools options


Type 1 (30 01 3556)




Type 1A (30 01 3559)




Type 3 (30 01 3563)




Type 2H (30 01 3558)




Type 1BH (30 01 3562)




Type 2S (30 01 3566)




Type 5BY (30 01 3654)




Type 2 (30 01 3557)




Type 1B (30 01 3560)




Type 4 (03 01 3564)




Type 1AH (30 01 3561)



Type 1S (30 01 3565)



Type 8F (30 01 3567)





"A" side spool positioners

With spring return in neutral position


8 kit (30 07 5349)

It's supplied with standard spring type D (see force-stroke diagram).
It's available with lighter spring type C (8MC) or heavier type E (8ME).




8D kit (30 07 5352)


With M8 female threaded pin extension for dual control.




Spool end joint dimensions (optional)



8D1 kit (30 07 5551)



8D2 kit (30 07 5353)





Working section

"A" side spool positioners



With spring return in neutral position

8F2 kit (30 07 5350)



With spool stroke adjustment in position 2 (P → B)




8TL kit (30 07 5552)



19 kit (30 07 5553)




20 kit (30 07 5554)



"A" side spool positioners


With detent

11 kit (30 07 5351)




Operating features
Locking and release force : 260 N / 58 lbf ±10%

12 kit (30 07 5555)




Operating features
Locking and release force : 260 N / 58 lbf ±10%

15 kit (30 07 5556)



Operating features
Locking and release force : 260 N / 58 lbf ±10%

16 kit (30 07 5557)




Operating features
Locking and release force : 260 N / 58 lbf ±10%

Working section


"A" side spool positioners

With spring return


17 kit (30 07 5558)




18 kit (30 07 5559)



17D kit (30 07 5560)





18D kit (30 07 5561)





"A" side spool positioners

With detent and spring return to neutral position from either directions



9B kit (30 07 5386)



10B kit (30 07 5387)



11B kit (30 07 5388)




Working section


"A" side spool positioners

With microswitch type 8MG3(NO) (30 07 5562)

With spring return in neutral position and microswitch operated in both directions.
Also available **8MG1(NO)** configuration (microswitch operated in position 1) and **8MG2(NO)** configuration (microswitch operated in position 2); dimensions are the same of **8MG3(NO)** configuration.
Same configurations are available with normally closed (NC) contact.
For more information contact Sales Department.





Other configurations



Operating features
MICROSWITCH
Mechanical life : 5x10⁵ operations
Electrical life (resistive load) : 5x10⁴ operations 10A / 12VDC
: 5x10⁴ operations 3A / 24VDC

Type 8MG1\MG2(NC-NC) (30 07 5360)

With double microswitch in position 1 and 2.





Positions	A	B
1		
0		
2		

Operating features
MICROSWITCH
Mechanical life : 5x10⁵ operations
Electrical life (resistive load) : 5x10⁴ operations 10A / 12VDC
: 5x10⁴ operations 3A / 24VDC

"A" side spool positioners

ON/OFF pneumatic kit type 8P (30 07 5399)



With spring return to neutral position.



Operating features
Pilot pressure.....: min. 5.5 bar / 80 psi
: max.10 bar / 145 psi

8PF pneumatic proportional kit (30 07 5596)

With spring return to neutral position.




Operating features
Pilot pressure.....: min. 5.5 bar / 80 psi
: max.10 bar / 145 psi

Working section


"A" side spool positioners

ON/OFF electropneumatic kit type 8EP3 - 30 07 5443 (12V) - 30 07 5400 (24V)


With spring return to neutral position.



Scheme



Scheme ISO 1219



Operating features


CONTROL

Pilot pressure : 6 bar / 87 psi
: max. 15 bar / 218 psi


COIL

Nominal voltage tolerance : ±10%
Power rating : 8 W
Nominal current : 12 VDC
: 24 VDC
Coil insulation : Class H
Weather protection : IP65


ON/OFF electropneumatic kit type 8EP4 - 30 07 5345 (12V) - 30 07 5346 (24V)



Scheme




Scheme ISO 1219




"A" side spool positioners

ON/OFF electrohydraulic kit type 8EI3 - 30 07 5401 (12V) - 30 07 5361 (24V)


ON/OFF electro-hydraulic control with external pilot and drain.



Scheme



Scheme ISO 1219



Operating features

CONTROL

Pilot pressure : min. 10 bar / 145 psi
: max. 50 bar / 725 psi
Max. backpressure on drain L : 25 bar / 360 psi

COIL


Nominal voltage tolerance : ±10%
Power rating : 21 W
Nominal current : 1.75 A - 12 VDC / 0.87 A - 24 VDC
Coil insulation : Class F
Weather protection : IP65

Working section


"A" side spool positioners

ON/OFF electrohydraulic kit type 8EI3F2


Collector kit with pilot and drain lines with stroke limiter



Scheme



Scheme ISO 1219



Operating features


CONTROL	
Pilot pressure	: min. 10 bar / 145 psi
	: max. 50 bar / 725 psi
Max. backpressure on drain L	: 25 bar / 360 psi

COIL	
Nominal voltage tolerance	: ±10%
Power rating	: 21 W
Nominal current	: 1.75 A - 12 VDC / 0.87 A - 24 VDC
Coil insulation	: Class F
Weather protection	: IP65

"A" side spool positioners

ON/OFF electrohydraulic kit type 8EI3

Collector kit for external pilot and drain



COLLECTOR KIT CODES

Type	Code	Description
KE1S0	30 07 5537	Kit one section
KE2S0	30 07 5522	Kit for 2 sections
KE3S0	30 07 5523	Kit for 3 sections
KE4S0	30 07 5524	Kit for 4 sections
KE5S0	30 07 5525	Kit for 5 sections
KE6S0	30 07 5526	Kit for 6 sections
KE7S0	--	Kit for 7 sections


Working section

"A" side spool positioners

ON/OFF electrohydraulic kit type 8EI3

Collector kit with pilot and drain lines


The kit include collector, VRP pressure reducing valve and pipes.



Operating features

VRP VALVE

Output pressure : 25 bar / 363 psi
Max. flow : 8 l/min
Filtering : 80 μ



Description example :
80L GS10/2/AC(X-100)/18EI3L/18EI3L/RV-KE2R3-24VDC

Description type for outlet
cover with VRE valve.



Outlet cover with VRE backpressure
valve (not included in the collector
kit) and carry-over

COLLECTOR KIT CODES

Type	Code	Description
KE1R3	30 07 5488	Kit one section
KE2R3	30 07 5489	Kit for 2 sections
KE3R3	30 07 5490	Kit for 3 sections
KE4R3	30 07 5491	Kit for 4 sections
KE5R3	30 07 5492	Kit for 5 sections
KE6R3	30 07 5493	Kit for 6 sections

VRE - VRC backpressure valve

Valve is assembled on flow through passage of outlet cover; it's necessary to provides pilot pressure to the actuator.
RV complete (with backpressure valve and tapered plug)




"A" side spool positioners

Particular positioner kits for special spools


8CR kit (30 07 5565)

3 positions with spring return in neutral and reduced spool stroke: **for 8F spool.**



13QN kit (30 07 5564)

4 positions with spring return in neutral and detent in position 3: **for 5BY spool.**




Working section

"B" side options


Lever control

Type L (30 07 5363)

Alluminium lever pivot box with protective rubber bellow; it can be roated 180° (configuration L180).




configuration L180




Type LF1 (30 07 5365)

With spool stroke adjustment in position 1 (P → A).



Type SLP (30 07 5366)

Mechanical control with dust-proof plate kit.



"B" side options


Lever control

Type LB (30 07 5367)


Steel manufacture.
Pivot can be assembled below (LB1 configuration) or above (LB3 configuration).

1	0	2
---	---	---

Configuration LB1



Configuration LB3





Working section

"B" side options

Safety lever control

Safety levers with lock in neutral complete with handlever; lift handlever knob to operate.
With insulated handlever type **LEBP**



Type **LEB** (30 07 5369)





"B" side options

Controls prearrangement

Type SL





Type SLCZ



Protection cap usable with pneumatic, electropneumatic, and electrohydraulic spool positioners.

TQ cable remote control kit (30 07 5354)

Waterproof cap prearranged for remote control with flexible cable.



Working section

"B" side options

LCB mechanical joystick for two sections control (30 07 5370)

Execution LCB4

2nd section spool

1st section spool

Allen wrench 3
6.6 Nm / 4.9 lbft

Wrench 12 - 24 Nm / 17.7 lbft

Wrench 13 - 24 Nm / 17.7 lbft

Wrench 10 - 9.8 Nm / 7.2 lbft

Pivot

Wrench 13
24 Nm / 17.7 lbft

Wrench 10

Allen wrench 5
9.8 Nm / 7.2 lbft

1	0	2
1	0	2

LCB HCB KCB

200 254 310

Description example
80L GS10/2/AC(X-100)/18LCB4/18LCB4/RC

Dimensions and movement scheme

Execution LCB1
pivot placed down on the left

1st section axis

41 [1.61]

2nd section axis

34.5 [1.36]

24.5 [0.96]

M10

31.25 [1.23]

9.75 [0.38]

Execution LCB2
pivot placed down on the right

spool axis

10 [0.39]

92.5 [3.64]

34.5 [1.36]

Execution LCB3
pivot placed above on the left

44.5 [1.75]

Execution LCB4
pivot placed above on the right


Complete controls

8ES solenoid control

Solenoid direct control with spring return to neutral position ; it needs special spools and standard working section body (body kit without seals on spool).

Description example:

80L GS10 / P - 1 8ES3 . U1(100) - 12VDC



1. Complete working section

TYPE	CODE	DESCRIPTION
P-18ES3-12VDC	80W010004	Parallel circuit, double acting spool, double acting ON/OFF solenoid control
P-18ES3-24VDC	80W010005	Parallel circuit, double acting spool, double acting ON/OFF solenoid control

2. Working section kit

TYPE	CODE	DESCRIPTION
P/IM-ES	-	As previous with port valves prearrangement

3. Spool options

TYPE	CODE	DESCRIPTION
1(ES)	30 01 3655	Double acting, 3 positions, with A and B closed in neutral position
2(ES)	30 01 3656	Double acting, 3 positions, with A and B open to tank in neutral position

4. Control kit

TYPE	CODE	DESCRIPTION
8ES1	30 07 5566	Single acting P → A, with spring return to neutral position
8ES2	30 07 5566	Single acting P → B, with spring return to neutral position
8ES3	30 07 5567	Double acting, with spring return to neutral position

5. Port valves

For codes please refer to page 18.

6. Coils


TYPE	CODE	DESCRIPTION
With ISO4400 connector		
12VDC	20 03 2300	Nominal voltage 12VDC
24VDC	20 03 2301	Nominal voltage 24VDC

a. "A" and "B" ports plugs

TYPE	CODE	DESCRIPTION
G1/2	30 05 4919	For single acting controls type 8ES1 and 8ES2

8ES solenoid control

Electric wiring example



Operating features

- CONTROL
- Internal leakage A(B)→T
- ($\Delta p = 100 \text{ bar} - 1450 \text{ psi} / T = 40^\circ\text{C}$) : max. $15 \text{ cm}^3/\text{min} - 0.91 \text{ in}^3/\text{min}$
- COIL
- Nominal voltage tolerance : $\pm 10\%$
- Power rating : 36 W
- Coil insulation : class H
- Duty cycle : 100%


8ES3 kit
double acting





8ES1 kit
single acting on A



8ES2 kit
single acting on B



Operating condition diagram





Working section

Complete controls

Proportional hydraulic control type 8IM (30 07 5372)


It can be used with standard spools and body



Operating features

Pilot pressure : max. 50 bar / 725 psi
Internal leakage A(B) → T ($\Delta p = 100$ bar - 1450 psi / $T = 40^\circ\text{C}$)
.....: max. 6cm³/min - 0.37 in³/min



Connection example



Working section

Special configurations

Directional valve with rotary control kit (30 07 5373)






Description example
80L GS10/1/AC(X-100)/1 R SLP /RC

Port valves


Anti - shock valves

P 1 (100)

- Standard setting in bar
- 1 mounted on port A.
- 2 mounted on port B.
- 3 mounted on ports A and B.



Valve type



Performance data


Working section

Port valves


Antishock and anticavitation valves

U 1 (100)



- Standard setting in bar
- 1 mounted on port A.
- 2 mounted on port B.
- 3 mounted on ports A and B.



Valve type



Performance data (Antishock and anticavitation valves)







Port valves

Anticavitation valves

C 1




- 1 mounted on port A.
- 2 mounted on port B.
- 3 mounted on ports A and B.



Valve blanking plug with tank connection

DST 1





- 1 mounted on port A.
- 2 mounted on port B.



Valve blanking plug

P 1 T


- 1 mounted on port A.
- 2 mounted on port B.
- 3 mounted on ports A and B.




Intermediate section

CS1 mid return manifold

Mid return manifolds for directional valve with left and right inlet both; they allow 2 independent circuits with common outlet.



Hydraulic circuit




Description example:

80L GS10/2/AC(X-100)/18L/CS1/ED-18L/BC(X-100)


Intermediate section

DFG pressure compensated flow divider section

The flow on the downstream sections can be adjusted from 0 to 80 l/min. by means of graduated handwheel; exceeding setting flow goes to tank.



Hydraulic circuit



Description example:


80L GS10/2/AC(X-100)/18L/DFG/18L/RC

Intermediate section


Service relief valve section

El configuration

The operation of up stream section exclude the EI downstream section.
The pressure of the downstream sections should be adjusted at least 20 bar below the relief valve setting.
Execution EI2, without plug, is prearranged for a second inlet.



Description example:
80L GS10/2/AC(X-100)/18L/EI1(X-100)/18L/RC



Description example:
80L GS10/2/AC(X-100)/18L/EI2(X-100)/18L/RC

Parts ordering codes


Ordering example:

80L GS10 / RC



Available configurations

- RC: side outlet
- RD: upper outlet
- RE: upper outlet with side carry-over
- RK: upper outlet and closed centre
- RV: With backpressure valve: **to be used together with the electro-hydraulic control**



1. Complete outlet cover *		
TYPE	CODE	DESCRIPTION
RC	30 08 5660	Side outlet
RD	30 08 5711	Upper outlet
RE	30 08 5712	Upper outlet with side carry-over sleeve
RK	30 08 5713	Upper outlet with closed center
RV	30 08 5714	With backpressure valve
VRC	30 08 5715	With backpressure valve


2. Circuit options *			
TYPE	CODE	QTY	DESCRIPTION
-	30 05 4918	1	G 3/8 plug for carry-over (RE), carry-over with backpressure valve (RV) and closed centre (RK) options
VRE	30 05 4990	1	VRE backpressure valve for RV configuration
VRC	30 05 4910	1	Backpressure valve for VRC configuration
-	30 05 4920	1	Plug G 3/4

NOTE (*) - Items are referred to **BSP** thread.


Outlet section

Dimensional data and hydraulic circuit


Type RC




Type RD



Type RE




Type RK




Sectional drawing

When hand lever pushed (spool out position) P to A port. B to T port.



When hand lever pulled (spool in position) P to B port. A to T port.





100L GS

GMS
hydraulic

Specifications

Spool: 1.. 12 Spools /Double - Single - Closed Center - Motor - Floating - Regenerative Spool

Liter: 100L Nominal - 120L Max

Ports: 3/4 Standard -1/2 Optional

Front Cap: Handle - Mechanical Joystick - Hydraulic Joystick - Remote Cable Control - Lock Handle

End Cap: Spring - Detent - Floating - Pneumatic - Proportional Coil - Hydraulic Control - Electro Hydraulic - Remote Cable Control

Open Center / Carry over / Parallel Circuit

Features

Simple, compact and heavy duty designed sectional valve from 1 to 12 sections for open and closed center hydraulic systems.

- ▶ Fitted with a main pressure relief valve and a load check valve on every working section
- ▶ Available with parallel, tandem or series circuit.
- ▶ Optional carryover port.
- ▶ A wide variety of auxiliary valves.
- ▶ Intermediate sections for several types of circuit.
- ▶ Available manual, pneumatic, hydraulic, electro--hydraulic, and remote with flexible cables spool control kits.
- ▶ Diameter 20 mm (0.79 in) interchangeable spools.

Additional information

This catalogue shows the product in the most standard configurations. Please contact Sales Dpt. for more information that is detailed or special request.

WARNING!

All specifications of this catalogue refer to the standard product at this date.
GMS, oriented to a continuous improvement, reserves the right to discontinue, modify or revise the specifications, without notice.

GMS IS NOT RESPONSIBLE FOR ANY DAMAGE CAUSED BY AN INCORRECT USE OF THE PRODUCT.

1st edition April 2018:

- Valve general informations

Working conditions.	page 4
Standard threads.	page 4
Dimensional data.	page 5
Performance data.	page 6
Hydraulic circuit.	page 7
Complete sections ordering codes	page 8

- Inlet section

Parts ordering codes.	page 10
Dimensional data and hydraulic circuit	page 11
Inlet relief options.	page 12

- Inlet section for special application

Configuration with rotary commutator.	page 15
---	---------

- Working section

Parts ordering codes (mechanical control).	page 16
Spools.	page 18
“A” side spool positioners.	page 19
“B” side options	page 32
Complete controls.	page 37
Port valves.	page 39

- Intermediate section

CS1 mid return manifold section.	page 42
DFG pressure compensated flow divider section. .	page 43
EI service relief valve section.	page 44

- Outlet section

Parts ordering codes.	page 45
Dimensional data and hydraulic circuit	page 46

Valve general informations

Working conditions

This catalogue shows technical specifications and diagrams measured with mineral oil of 46 mm²/s – 46cSt viscosity at 40°C temperature.

Nominal flow rating	100 l/min.		
Max. flow	120 l		
Operating pressure (max.)	Series-parallel (tandem) circuit	315 bar	4600 psi
Back pressure (max.)	on outlet port T	25 bar	360 psi
Internal leakage A(B)→T	Δp=100 bar – 1450 psi fluid and valve at 40°C	3cm ³ /min.	0.18 in ³ /min.
Hydraulic fluid	Mineral base oil		
Fluid temperature	with NBR seals	from - 20° to 80°C	
	with FPM (VITON) seals	from - 20° to 100°C	
Viscosity	operating range	from 15 to 75 mm ² /s	from 15 to 75 cSt
	Min.	12 mm ² /s	12 cSt
	Max.	400 mm ² /s	400 cSt
Max. level of contamination	19/16 – ISO 4406		
Tie rods tightening torque (wrench 17)	50 Nm	37 lbft	



Standard threads

REFERENCE STANDARD

PORTS	BSP (ISO 228/1)	OPTIONAL	UN-UNF (ISO 11926-1)	METRIC (ISO 6149-1)
Inlet P	G 3/4	-	1 1/16-12 UN- (SAE 12)	M27x2
A and B ports	G 3/4	G 1/2	1 1/16-12 UN- (SAE 12)	M22x1,5
Outlet T and carry-over C	G 3/4	-	1 1/16-12 UN- (SAE 12)	M27x2
PILOT PORTS				
Hydraulic ports	G 1/4		-	-
Pneumatic ports	G 1/8		-	-

Valve general informations

Dimensional data



TYPE	A		B		Weight	
	mm	in	mm	in	kg	lb
100L GS 16/1	147	5.79	71	2.80	9.5	20.94
100L GS 16/2	192	7.56	116	4.57	13.7	30.20
100L GS 16/3	237	9.33	161	6.34	17.9	39.46
100L GS 16/4	282	11.10	206	8.11	22.1	48.72
100L GS 16/5	327	12.87	251	9.88	26.3	57.98
100L GS 16/6	372	14.65	296	11.65	30.5	67.24



TYPE	A		B		Weight	
	mm	in	mm	in	kg	lb
100L GS 16/7	417	16.42	341	13.43	34.7	76.50
100L GS 16/8	462	18.19	386	15.20	38.9	85.76
100L GS 16/9	507	19.96	431	16.97	43.1	95.02
100L GS 16/10	552	21.73	476	18.74	47.3	104.28
100L GS 16/11	597	23.50	521	20.51	51.5	113.54
100L GS 16/12	642	25.28	566	22.28	55.7	122.80

Valve general informations

Performance data (pressure drop vs. flow)



Open centre

From side inlet to side outlet.





Inlet to work port

From side inlet to A port (spool in position 1) or B port (spool in position 2).



Work port to outlet

From A port (spool in position 2) or B port (spool in position 1) to side outlet.




Valve general informations

Hydraulic circuit

Parallel circuit


Standard configuration with open centre and side inlet and outlet.



Description example
100L GS16/2/AC(X-100)/18L/18L/RC

Series-parallel (tandem) circuit


It needs a special working section kit
Tandem section is fed from thr free flow pressure line; it's excluded when an up stream section is operated.



Description example
100L GS16/2/AC(X-100)/18L/ SP-18L/RC



Series circuit

It needs a special working section kit
The return oil from service ports feed the remaining down stream sections.



Description example
100L GS16/2/AC(X-100)/ S-18L/P-18L/RC

Directional valve with right inlet



Description example
100L GS16/2/BC(X-100)/18L/18L/RC

Valve general informations

Complete sections ordering codes

Standard configuration with side inlet and outlet

100L GS16 / 2 / AC(X-100) / (P)- 18L.P3T / EI1 / (P)- 18L.P3T / RC

Nr. of working
section

1.

2.

3.


4.

4.

8.

9.

It's not necessary to indicate the "P" letter in the complete valve description with parallel circuit (standard); in case of other circuits, they must be specified by the related letter (S,SP).



1. Inlet section * page 10

TYPE	CODE	DESCRIPTION
AC(X-100)	30 08 5750	Side inlet with direct pressure relief valve
AD(X-100)	30 08 5665	Upper inlet with direct pressure relief valve
AC(V)	30 08 5653	Without pressure relief valve

2. Working section * page 16

TYPE	CODE	DESCRIPTION
P-18L	10W010000	Parallel circuit, prearranged for port valves, double acting spool with spring return, lever control
S-18L	10W010002	Series circuit, lever control
SP-18L	10W010003	As previous with series-parallel (tandem) circuit

3. Intermediate sections * page 43

TYPE	CODE	DESCRIPTION
DFG	30 08 5775	Pressure compensated flow divider section
EI1(X-100)	30 08 5734	With direct overpressure relief valve
EI2(X-100)	30 08 5735	With direct overpressure relief valve and auxiliary inlet

4. Outlet section * page 45

TYPE	CODE	DESCRIPTION
RC	30 08 5654	Side outlet
RD	30 08 5716	Upper outlet
RE	30 08 5718	Upper outlet with side carry-over sleeve
RK	30 08 5717	Upper outlet with closed centre
RV	30 08 5719	With backpressure valve the combination with electro-hydraulic control is required
VRC	30 08 5720	Backpressure valve for VRC configuration

NOTE (*) - Items are referred to **BSP** thread.

K-7


GMS **GURMAKSAN**
HID.DEVRE.ELM.SAN.TIC.LTD.STI

Valve general informations

Complete sections ordering codes

Configuration with 2 side inlets and mid return manifold

100L GS16 / 2 / AC(X-100) / 18L.P3T / CS1 / ED - 18L.P3T / BC(X-100)



5. Return manifold * page 42

TYPE	CODE	DESCRIPTION
CS1	30 08 5780	Mid return manifold with G3/4 outlet port

6. Right inlet working section *

TYPE	CODE	DESCRIPTION
P-ED-18L	10W010006	Parallel circuit, prearranged for port valves, double acting spool with spring return, lever control
S-ED-18L	10W010004	As previous with series circuit
SP-ED-18L	10W010005	As previous with series-parallel (tandem) circuit

7. Right inlet section *

TYPE	CODE	DESCRIPTION
BC(X-100)	30 08 5754	Side inlet with direct pressure relief valve
BD(X-100)	30 08 5758	Upper inlet with pilot operated pressure relief valve
BC(V)	30 08 5770	Side inlet with valve blanking plug

8. Assemb. kit without intermediate section

CODE	DIRECTIONAL VALVE
30 05 6033	Tie rod kit for 1 section valve
30 05 6037	Tie rod kit for 2 sections valve
30 05 6038	Tie rod kit for 3 sections valve
30 05 6039	Tie rod kit for 4 sections valve
30 05 6040	Tie rod kit for 5 sections valve
30 05 6041	Tie rod kit for 6 sections valve
30 05 6042	Tie rod kit for 7 sections valve
30 05 6043	Tie rod kit for 8 sections valve
30 05 6044	Tie rod kit for 9 sections valve
30 05 6034	Tie rod kit for 10 sections valve
30 05 6035	Tie rod kit for 11 sections valve
30 05 6036	Tie rod kit for 12 sections valve


9. Assemb. kit with intermediate section

CODE	DIRECTIONAL VALVE
30 05 6038	Tie rod kit for 2 sections valve (with CS1)
30 05 6039	Tie rod kit for 3 sections valve (with CS1)
30 05 6040	Tie rod kit for 4 sections valve (with CS1)
30 05 6041	Tie rod kit for 5 sections valve (with CS1)
30 05 6042	Tie rod kit for 6 sections valve (with CS1)
30 05 6043	Tie rod kit for 7 sections valve (with CS1)
30 05 6044	Tie rod kit for 8 sections valve (with CS1)
30 05 6034	Tie rod kit for 9 sections valve (with CS1)
30 05 6035	Tie rod kit for 10 sections valve (with CS1)

NOTE (*) - Items are referred to **BSP** thread.

Parts ordering codes

100L GS16 / AC (X - 100) ELN - MAN14 - 12VDC




Available configurations

AC: with side inlet, for left inlet (standard) directional valve

AD: with upper inlet, for left inlet (standard) directional valve

BC: with side inlet, for right inlet directional valve

BD: with upper inlet, for right inlet directional valve



1. Inlet cover body * page 11

CODE	DESCRIPTION
-	Standard body

2. Parts *

TYPE	CODE	DESCRIPTION
MAN18	30 05 6102	G1/8 Pressure gauge arrangement
MAN14	30 05 6101	G1/4 Pressure gauge arrangement

3. Inlet relief valve options page 12

TYPE	CODE	DESCRIPTION
KE10K01 : direct pressure relief valve type X (X-100)	30 05 4912	Range 20 to 315 bar / 290 to 4600 psi standard setting 100 bar / 1450 psi

KE10K02 : pilot operated pressure relief valve type **Z**
(Z-100) 30 05 4915 Range 25 to 315 bar / 360 to 4600 psi
standard setting 100 bar / 1450 psi

Standard setting is referred to 6 l/min flow.

V 30 05 4914 Relief valve blanking plug

NOTE (*) - Items are referred to **BSP** thread.

4. Inlet valve options page 14

TYPE	CODE	DESCRIPTION
-	30 05 4914	Relief valve blanking plug (omit in description)
F	-	Inlet anti-cavitation valve
L	-	Hydraulic pilot unloader valve
Solenoid operated unloader valve		
ELN	30 05 6108	Without emergency
ELP	30 05 6109	Push-button emergency
ELT	30 05 6110	Push and twist type with detent emergency

5. Coils

TYPE	CODE	DESCRIPTION
12VDC	20 03 2268	Coil type BER , ISO4400 integrated type 12VDC
24VDC	20 03 2269	Coil type BER , ISO4400 integrated type 24VDC

Inlet section

Dimensional data and hydraulic circuit

For left inlet directional valve (standard)

With side inlet, type AC

Allen wrench 10
24 Nm / 17.7 lbft

D - D

G 3/4

P

43.5



[1.71]

27

[1.06]

51

[2.01]



With upper inlet, type AD

D - D



G 3/4

P

Allen wrench 10
24 Nm / 17.7 lbft




56.5

[2.22]






For right inlet directional valve

With side inlet, type BC



With upper inlet, type BD



Inlet section


Inlet relief options

Direct pressure relief valve

KE10K01 (X - 100)


Standard setting in bar

Adjustment type (X, XH)




Adjustment type


X: with screw




XH: valve set and locked



Performance data



Time response



Inlet section


Inlet relief options

Pilot pressure relief valve

KE10K02 (Z - 100)


Standard setting in bar

Adjustment type (Z, ZH)




Adjustment type



Z: with screw




ZH: valve set and locked



Performance data



V: relief valve blanking plug



Inlet section

Inlet valve options

Unloader valves

Description example: AC (X - 100) **ELN** - **12VDC**





Hydraulic operated valve: **L**
Solenoid operated valve: **ELN**
ELP
ELT

Feeding voltage: for
solenoid operated



Solenoid operated

Emergency with push button and spring return; for detent position turn the button after press it.

WARNING: the manual override option is intended for emergency use, not for continuous duty operation.





Hydraulic operated



Anti-cavitation valve

Description example: AC (X - 100) **F**




Inlet section for special applications


Configuration with rotary commutator

Dimensional data and hydraulic circuit

Drawing and circuit are referred to left inlet directional valve.



Hydraulic circuit and ordering codes



Parts ordering codes (mechanical control)

Description example:

100L GS16 / P - 1 8 L . U 1 (100) *

1.

2.

3.

4.


5.

Port valves setting in bar

1 mounted on A port.

2 mounted on B port.

3 mounted on A and B port.



1. Working section kit *

TYPE	CODE	DESCRIPTION
P	-	With parallel circuit
S	-	With series circuit
SP	-	With series-parallel (tandem) circuit

Include body, seals, rings and load check valve.

2. Spools page 18

TYPE	CODE	DESCRIPTION
1	30 01 3581	Double acting, 3 positions, with A and B closed in neutral position
1A	30 01 3585	Double acting, 3 positions, with A open to tank in neutral position
1B	30 01 3586	Double acting, 3 positions, with B open to tank in neutral position

2. Spools page 18

TYPE	CODE	DESCRIPTION
2	30 01 3582	Double acting, 3 positions, with A and B open to tank in neutral position
3	30 01 3587	Single acting on A, 3 positions, B plugged; requires G3/4 plug (see part a)
4	30 01 3588	Single acting on B, 3 positions, A plugged; requires G3/4 plug (see part a)

Special spools for particular positioner kits page 18
5DY 30 01 3584 Double acting, 4 positions, float in position 3 with spool in, 13NZ type positioner kit is required

Working section

Parts ordering codes (mechanical control)

3. "A" side spool positioners page 19			4. "B" side options page 32		
TYPE	CODE	DESCRIPTION	TYPE	CODE	DESCRIPTION
8	30 07 5375	With spring return in neutral position	L	30 07 5403	Standard lever box
8D	30 07 5383	As type 8, M8 female threaded pin extension for dual control	LF1	30 07 5405	Lever box with spool stroke limiter in position 1
8D1	30 07 5402	As type 8, pin with Ø 8 mm (0.31 in) radial hole	SL	-	Without lever box
8D2	30 07 5384	As type 8, M8 male threaded pin extension for dual control	SLP	30 07 5406	Without lever box, with dust-proof plate
8TL	30 07 5397	As type 8 with pin control with flexible cable	SLCZ	-	Without lever box, with endcap.
8F2	30 07 5377	As type 8 with adjustable stroke limiter	LB	30 07 5407	Steel lever
19	30 07 5436	2 positions, with spring return in neutral position from position 1	LEB	30 07 5409	Safety lever box, vertical configuration
20	30 07 5437	2 positions, with spring return in neutral position from position 2	TQ	30 07 5398	Flexible cable connection; for CG cables
11	30 07 5378	With detent in position 1, neutral and 2	LCB	30 07 5433	Joystick lever for 2 sections operation
12	30 07 5438	Detent in positions 1 and 2			
15	30 07 5439	2 positions, detent in pos. 1 and neutral			
16	30 07 5440	2 positions, detent in pos. 2 and neutral			
17	30 07 5441	With spring return position 1			
18	30 07 5381	With spring return position 2			
17D	30 07 5442	With spring return position 1 and pin with M8 female thread for dual control			
18D	30 07 5382	With spring return position 2 and pin with M8 female thread for dual control			
9B	30 07 5386	With detent in position 1 and spring return in neutral position			
10B	30 07 5387	With detent in position 2 and spring return in neutral position			
11B	30 07 5388	With detent in position 1, 2 and spring return in neutral position			
8MG3(NO)	30 07 5435	As type 8 and operation with microswitch in positions 1 and 2, contact normally open			
8MG3(NC)	30 07 5434	As previous, with contact normally closed			
8P	30 07 5399	ON-OFF pneumatic kit			
8PF	-	Proportional pneumatic kit			
8EP3	30 07 5443	ON-OFF 12VDC electro-pneumatic kit			
	30 07 5400	ON-OFF 24VDC electro-pneumatic kit			
8EP4	30 07 5345	ON-OFF 12VDC electro-pneumatic kit with manifold			
	30 07 5346	ON-OFF 24VDC electro-pneumatic kit with manifold			
8EI3	30 07 5401	ON-OFF 12VDC electro-hydraulic kit			
	30 07 5361	ON-OFF 24VDC electro-hydraulic kit			
8EI3F2	-	12 VDC ON/OFF electrohydraulic kit with adjustable stroke limiter			
	-	24 VDC ON/OFF electrohydraulic kit with adjustable stroke limiter			
Particular positioner kits for special spools page 31					
13NZ	30 07 5415	4 positions with spring return in neutral position and detent in pos.3: for 5DY spool			

5. Port valves page 39

TYPE	CODE	DESCRIPTION
Assembled on section		
P3T	30 05 4940	A and B ports valve blanking plugs
C	-	Anti-cavitation
Anti-shock valve		
P	30 05 6195	From 0 to 315 bar / 0 to 4600 psi standard setting 100 bar / 1450 psi
Anti-shock and anti-cavitation valve		
U	30 05 4908	From 0 to 315 bar / 0 to 4600 psi standard setting 100 bar / 1450 psi

Standard setting is referred to 6 l/min flow.

6. Complete controls page 37

TYPE	CODE	DESCRIPTION
8IM	30 07 5414	-
R	30 07 5379	-

Proportional hydraulic control type 8IM and rotative control type R.

a. "A" and "B" ports plugs


TYPE	CODE	DESCRIPTION
G3/4	30 05 4920	For single acting spools type 3 and 4

b. Optional handlevers


TYPE	CODE	DESCRIPTION
AL01/M10x200	30 05 4989	Length L = 200mm / 7.87in

Spools options


Type 1 (30 01 3581)




Type 2 (30 01 3582)




Type 1A (30 01 3585)




Type 1B (30 01 3586)




Type 3 (30 01 3587)



Type 4 (30 01 3588)



Type 5DY (30 01 3584)





Working section

"A" side spool positioners

With spring return in neutral position


8 kit (30 07 5375)

It's supplied with standard spring type D (see force-stroke diagram).
It's available with lighter spring type C (8MC) or heavier type E (8ME).




8D kit (30 07 5383)


With M8 female threaded pin extension for dual control.




Spool end joint dimensions (optional)



8D1 kit (30 07 5402)



8D2 kit (30 07 5384)




"A" side spool positioners



With spring return in neutral position

8F2 kit (30 07 5377)



With spool stroke adjustment in position 2 (P → B)




8TL kit (30 07 5397)



19 kit (30 07 5436)



20 kit (30 07 5437)




Working section

"A" side spool positioners


With detent

11 kit (30 07 5378)




Operating features
Locking and release force : 260 N / 58 lbf ±10%

12 kit (30 07 5438)




Operating features
Locking and release force : 260 N / 58 lbf ±10%

15 kit (30 07 5439)



Operating features
Locking and release force : 260 N / 58 lbf ±10%

16 kit (30 07 5440)




Operating features
Locking and release force : 260 N / 58 lbf ±10%


"A" side spool positioners

With spring return


17 kit (30 07 5441)




18 kit (30 07 5381)



17D kit (30 07 5442)



18D kit (30 07 5382)





Working section



"A" side spool positioners

With detent and spring return to neutral position from either directions



9B kit (30 07 5386)



10B kit (30 07 5387)



11B kit (30 07 5388)



"A" side spool positioners



With microswitch type 8MG3(NO) (30 07 5435)

With spring return in neutral position and microswitch operated in both directions.



Also available **8MG1(NO)** configuration (microswitch operated in position 1) and **8MG2(NO)** configuration (microswitch operated in position 2); dimensions are the same of **8MG3(NO)** configuration.

Same configurations are available with normally closed (NC) contact.

For more information contact Sales Department.



Other configurations



Operating features

MICROSWITCH

Mechanical life

: 5x10⁵ operations



Electrical life (resistive load)

: 5x10⁴ operations 10A / 12VDC

: 5x10⁴ operations 3A / 24VDC

Type 8MG1\MG2(NC-NC) (30 07 5396)

With double microswitch in position 1 and 2.



Positions	A	B
1		
0		
2		

Operating features

MICROSWITCH

Mechanical life

: 5x10⁵ operations

Electrical life (resistive load)

: 5x10⁴ operations 10A / 12VDC



: 5x10⁴ operations 3A / 24VDC

Working section

"A" side spool positioners

ON/OFF pneumatic kit type 8P (30 07 5399)



With spring return to neutral position.



Operating features
Pilot pressure.....: min. 5.5 bar / 80 psi
: max.10 bar / 145 psi

8PF pneumatic proportional kit (30 07 5596)

With spring return to neutral position.




Operating features
Pilot pressure.....: min. 5.5 bar / 80 psi
: max.10 bar / 145 psi


"A" side spool positioners

ON/OFF electropneumatic kit type 8EP3 - 30 07 5443 (12V) - 30 07 5400 (24V)


With spring return to neutral position.



Scheme



Scheme ISO 1219



Operating features


CONTROL

Pilot pressure : 6 bar / 87 psi
: max. 15 bar / 218 psi


COIL

Nominal voltage tolerance : $\pm 10\%$
Power rating : 8 W
Nominal current : 12 VDC
: 24 VDC
Coil insulation : Class H
Weather protection : IP65


ON/OFF electropneumatic kit type 8EP4 - 30 07 5345 (12V) - 30 07 5346 (24V)



Scheme



Scheme ISO 1219




Working section


"A" side spool positioners

ON/OFF electrohydraulic kit type 8EI3 - 30 07 5401 (12V) - 30 07 5361 (24V)


ON/OFF electro-hydraulic control with external pilot and drain.



Scheme



Scheme ISO 1219



Operating features

CONTROL

Pilot pressure : min. 10 bar / 145 psi
: max. 50 bar / 725 psi
Max. backpressure on drain L : 25 bar / 360 psi


COIL

Nominal voltage tolerance : ±10%
Power rating : 21 W
Nominal current : 1.75 A - 12 VDC / 0.87 A - 24 VDC
Coil insulation : Class F
Weather protection : IP65


"A" side spool positioners

ON/OFF electrohydraulic kit type 8EI3F2


Collector kit with pilot and drain lines with stroke limiter



Scheme



Scheme ISO 1219



Operating features

CONTROL

Pilot pressure	: min. 10 bar / 145 psi
	: max. 50 bar / 725 psi
Max. backpressure on drain L	: 25 bar / 360 psi

COIL



Nominal voltage tolerance	: $\pm 10\%$
Power rating	: 21 W
Nominal current	: 1.75 A - 12 VDC / 0.87 A - 24 VDC
Coil insulation	: Class F
Weather protection	: IP65

Working section

"A" side spool positioners

ON/OFF electrohydraulic kit type 8EI3

Collector kit for external pilot and drain



Description example :
100L GS16/2/AC(X-100)/18EI3L/18EI3L/RC-KE2S0-24VDC

COLLECTOR KIT CODES


Type	Code	Description
KE1S0	30 07 5537	Kit one section
KE2S0	30 07 5527	Kit for 2 sections
KE3S0	30 07 5528	Kit for 3 sections
KE4S0	30 07 5529	Kit for 4 sections
KE5S0	30 07 5530	Kit for 5 sections
KE6S0	30 07 5531	Kit for 6 sections
KE7S0	--	Kit for 7 sections

"A" side spool positioners

ON/OFF electrohydraulic kit type 8EI3

Collector kit with pilot and drain lines

The kit include collector, VRP pressure reducing valve and pipes.



Operating features

VRP VALVE

Output pressure : 25 bar / 363 psi

Max. flow : 8 l/min



Filtering : 80 µ

COLLECTOR KIT CODES

Type	Code	Description
KE1R3	30 07 5500	Kit one section
KE2R3	30 07 5501	Kit for 2 sections
KE3R3	30 07 5502	Kit for 3 sections
KE4R3	30 07 5503	Kit for 4 sections
KE5R3	30 07 5504	Kit for 5 sections
KE6R3	30 07 5505	Kit for 6 sections

VRE - VRC backpressure valve

Valve is assembled on flow through passage of outlet cover; it's necessary to provides pilot pressure to the actuator.
RV complete (with backpressure valve and tapered plug)




Working section

"A" side spool positioners

Particular positioner kits for special spools

13NZ kit (30 07 5415)

4 positions with spring return in neutral and detent in position 3: **for 5DY spool**.





"B" side options


Lever control

Type L (30 07 5403)

Alluminium lever pivot box with protective rubber bellow; it can be roated 180° (configuration **L180**).





configuration L180





Type LF1 (30 07 5405)

With spool stroke adjustment in position 1 (P → A).



Type SLP (30 07 5406)

Mechanical control with dust-proof plate kit.



Working section


"B" side options

Lever control

Type LB (30 07 5407)

Steel manufacture.
Pivot can be assembled below (LB1 configuration) or above (LB3 configuration).

1	0	2
---	---	---




"B" side options

Safety lever control

Safety levers with lock in neutral complete with handlever; lift handlever knob to operate.
With insulated handlever type **LEBP**

Type LEB (30 07 5409)




Working section


"B" side options

Controls prearrangement

Type SL



Type SLCZ (30 07 5347)




Allen wrench 4
6 Nm / 4.4 lbft

Protection cap usable with pneumatic, electropneumatic, and electrohydraulic spool positioners.

TQ cable remote control kit (30 07 5398)


Waterproof cap prearranged for remote control with flexible cable.




NOTE : For further information about remote cable control, require related documentation.

"B" side options

LCB mechanical joystick for two sections control (30 07 5433)



Dimensions and movement scheme





Working section

Complete controls


Proportional hydraulic control type 8IM (30 07 5414)

It can be used with standard spools and body






Operating features
Pilot pressure : max. 50 bar / 725 psi
Internal leakage A(B) → T ($\Delta p = 100 \text{ bar} - 1450 \text{ psi}$ / $T = 40^\circ\text{C}$)
.....: max. $6 \text{ cm}^3/\text{min} - 0.37 \text{ in}^3/\text{min}$

Connection example



Special configurations

Directional valve with rotary control kit (30 07 5379)



Description example

100L GS16/1/AC(X-100)/1 R SLP /RC




Working section

Port valves


Anti - shock valves

P 1 (100)

- Standard setting in bar
- 1 mounted on port A.
- 2 mounted on port B.
- 3 mounted on ports A and B.



Valve type



Performance data


Port valves

Antishock and anticavitation valves


U 1 (100)

Standard setting in bar



- 1 mounted on port A.
- 2 mounted on port B.
- 3 mounted on ports A and B.



Valve type



Performance data (Antishock and anticavitation valves)







Working section

Port valves

Anticavitation valves

C 1




- 1 mounted on port A.
- 2 mounted on port B.
- 3 mounted on ports A and B.



Valve blanking plug with tank connection

DST 1





- 1 mounted on port A.
- 2 mounted on port B.



Valve blanking plug

P 1 T


- 1 mounted on port A.
- 2 mounted on port B.
- 3 mounted on ports A and B.




Intermediate section

CS1 mid return manifold

Mid return manifolds for directional valve with left and right inlet both; they allow 2 independent circuits with common outlet.



Hydraulic circuit




Description example:

100L GS16/2/AC(X-100)/18L/ **CS1**/ED-18L/BC(X-100)


Intermediate section

DFG pressure compensated flow divider section

The flow on the downstream sections can be adjusted from 0 to 100 l/min. by means of graduated handwheel; exceeding setting flow goes to tank.



Hydraulic circuit



Description example:
100L GS16/2/AC(X-100)/18L/DFG/18L/RC

Intermediate section


Service relief valve section

EI configuration

The operation of up stream section exclude the EI downstream section.


The pressure of the downstream sections should be adjusted at least 20 bar below the relief valve setting.

Execution EI2, without plug, is prearranged for a second inlet.



Description example:

100L GS16/2/AC(X-100)/18L/ EI1(X-100)/18L/RC



Description example:

100L GS16/2/AC(X-100)/18L/ EI2(X-100)/18L/RC

Outlet section

Parts ordering codes


Ordering example:

100L GS16 / RC



Available configurations

- RC: side outlet
- RD: upper outlet
- RE: upper outlet with side carry-over
- RK: upper outlet and closed centre
- RV: With backpressure valve: **to be used together with the electro-hydraulic control**




1. Complete outlet cover *			2. Circuit options *			
TYPE	CODE	DESCRIPTION	TYPE	CODE	QTY	DESCRIPTION
RC	30 08 5654	Side outlet	-	30 05 4918	1	G 3/8 plug for carry-over (RE), carry-over with backpressure valve (RV) and closed centre (RK) options
RD	30 08 5716	Upper outlet	VRE	30 05 4905	1	VRE backpressure valve for RV configuration
RE	30 08 5718	Upper outlet with side carry-over sleeve	VRC	30 05 4904	1	Backpressure valve for VRC configuration
RK	30 08 5717	Upper outlet with closed center	-	30 05 4920	1	Plug G 3/4
RV	30 08 5719	With backpressure valve				
VRC	30 08 5720	With backpressure valve				

NOTE (*) - Items are referred to **BSP** thread.


Outlet section

Dimensional data and hydraulic circuit


Type RC




Type RD




Type RE




Type RK



When hand lever pushed (spool out position) P to A port. B to T port.



When hand lever pulled (spool in position) P to B port. A to T port.



100L GS

GS Series

K-47



GURMAKSAN
HID.DEVRE.ELM.SAN.TIC.LTD.STI

ТОВ "Промислова Гідравліка": <https://promhydraulic.com.ua/ua/>

Телефонуйте: +380 (95) 670-15-32, +380 (98) 533-91-67, +380 (96) 244-48-42



150L GS

GMS
hydraulic

Specifications

Spool: 1..12 Spools/Double - Single - Closed Center - Motor - Floating - Regenerative Spool

Liter: 150L Nominal -170L Max

Ports: 3/4 Standard

Front Cap: Handle - Mechanical Joystick - Hydraulic Joystick - Remote Cable Control - Lock Handle

End Cap: Spring - Detent - Floating - Pneumatic - Proportional Coil - Hydraulic Control - Electro Hydraulic - Remote Cable Control

Open Center / Carry over / Parallel Circuit

Features

Simple, compact and heavy duty designed sectional valve from 1 to 12 sections for open and closed center hydraulic systems.

- ▶ Fitted with a main pressure relief valve and a load check valve on every working section
- ▶ Available with parallel, tandem or series circuit.
- ▶ Optional carryover port.
- ▶ A wide variety of auxiliary valves.
- ▶ Intermediate sections for several types of circuit.
- ▶ Available manual, pneumatic, hydraulic, electro--hydraulic, and remote with flexible cables spool control kits.
- ▶ Diameter 20 mm (0.79 in) interchangeable spools.

Additional information

This catalogue shows the product in the most standard configurations. Please contact Sales Dpt. for more information that is detailed or special request.

WARNING!

All specifications of this catalogue refer to the standard product at this date.

GMS, oriented to a continuous improvement, reserves the right to discontinue, modify or revise the specifications, without notice.

GMS IS NOT RESPONSIBLE FOR ANY DAMAGE CAUSED BY AN INCORRECT USE OF THE PRODUCT.

1st edition April 2018:

- Valve general informations

Working conditions.	page 4
Standard threads.	page 4
Dimensional data.	page 5
Performance data.	page 6
Hydraulic circuit.	page 7
Complete sections ordering codes	page 8

- Inlet section

Parts ordering codes.	page 10
Dimensional data and hydraulic circuit	page 11
Inlet relief options.	page 12

- Inlet section for special application

Configuration with rotary commutator.	page 15
---	---------

- Working section

Parts ordering codes (mechanical control).	page 16
Spools.	page 18
“A” side spool positioners.	page 19
“B” side options	page 32
Complete controls.	page 37
Port valves.	page 40

- Intermediate section

CS1 mid return manifold section.	page 43
DFG pressure compensated flow divider section. .	page 44
EI service relief valve section.	page 45

- Outlet section

Parts ordering codes.	page 46
Dimensional data and hydraulic circuit	page 47

Valve general informations

Working conditions

This catalogue shows technical specifications and diagrams measured with mineral oil of 46 mm²/s – 46cSt viscosity at 40°C temperature.

Nominal flow rating		150 l/min.	
Max. flow		170 l	
Operating pressure (max.)	Series-parallel (tandem) circuit	315 bar	4600 psi
Back pressure (max.)	on outlet port T	25 bar	360 psi
Internal leakage A(B)→T	Δp=100 bar – 1450 psi fluid and valve at 40°C	3cm ³ /min.	0.18 in ³ /min.
Hydraulic fluid		Mineral base oil	
Fluid temperature	with NBR seals	from - 20° to 80°C	
	with FPM (VITON) seals	from - 20° to 100°C	
Viscosity	operating range	from 15 to 75 mm ² /s	from 15 to 75 cSt
	Min.	12 mm ² /s	12 cSt
	Max.	400 mm ² /s	400 cSt
Max. level of contamination		19/16 – ISO 4406	
Tie rods tightening torque (wrench 17)		50 Nm	36 lbft


Standard threads

REFERENCE STANDARD

PORTS	BSP (ISO 228/1)	UN-UNF (ISO 11926-1)
Inlet P	G 3/4	1 5/16 - 12 UN - 2B (SAE 16)
A and B ports	G 3/4	1 1/16 - 12 UN - 2B (SAE 12)
Outlet T and carry-over C	G 1	1 5/16 - 12 UN - 2B (SAE 16)
PILOT PORTS		
Hydraulic ports	G 1/4	-
Pneumatic ports	G 1/8	-

Valve general informations

Dimensional data



TYPE	A		B		Weight	
	mm	in	mm	in	kg	lb
150L GS 16/1	176	6.93	124	4.88	13	28.7
150L GS 16/2	224	8.82	172	6.77	18.5	40.8
150L GS 16/3	272	10.71	220	8.66	24	52.9
150L GS 16/4	320	12.60	268	10.55	29.5	65
150L GS 16/5	368	14.49	316	12.44	35	77.2
150L GS 16/6	416	16.38	364	14.33	40.5	89.3



TYPE	A		B		Weight	
	mm	in	mm	in	kg	lb
150L GS 16/7	464	18.27	412	16.22	46	101.4
150L GS 16/8	512	20.16	460	18.11	51.5	113.5
150L GS 16/9	560	22.05	508	20.00	57	125.7
150L GS 16/10	608	23.94	556	21.89	62.5	137.8
150L GS 16/11	656	25.83	604	23.78	68	149.9
150L GS 16/12	704	27.72	652	25.67	73.5	162

Valve general informations

Performance data (pressure drop vs. flow)



Open centre

From side inlet to side outlet.





Inlet to work port

From side inlet to A port (spool in position 1) or B port (spool in position 2).



Work port to outlet

From A port (spool in position 2) or B port (spool in position 1) to side outlet.




Valve general informations

Hydraulic circuit

Parallel circuit


Standard configuration with open centre and side inlet and outlet.



Description example
150L GS16/2/AC(X-100)/18L/18L/RC

Series-parallel (tandem) circuit


It needs a special working section kit
Tandem section is fed from thr free flow pressure line; it's excluded when an up stream section is operated.



Description example
150L GS16/2/AC(X-100)/18L/ SP-18L/RC



Series circuit

It needs a special working section kit
The return oil from service ports feed the remaining down stream sections.



Description example
150L GS16/2/AC(X-100)/ S-18L/P-18L/RC

Directional valve with right inlet




Description example
150L GS16/2/BC(X-100)/18L/18L/RC

Complete sections ordering codes

Standard configuration with side inlet and outlet

150L GS16 / 2 / AC(X-100) / (P)- 18L.P3T / EI1 / (P)- 18L.P3T / RC



1. Inlet section * page 10

TYPE	CODE	DESCRIPTION
AC(X-100)	30 08 5751	Side inlet with direct pressure relief valve
AD(X-100)	30 08 5666	Upper inlet with direct pressure relief valve
AC(V)	30 08 5657	Without pressure relief valve

2. Working section * page 16

TYPE	CODE	DESCRIPTION
P-18L	15W010000	Parallel circuit, prearranged for port valves, double acting spool with spring return, lever control
S-18L	15W010002	Series circuit, lever control
SP-18L	15W010003	As previous with series-parallel (tandem) circuit

3. Intermediate sections * page 44

TYPE	CODE	DESCRIPTION
DFG	30 08 5776	Pressure compensated flow divider section
EI1(X-100)	30 08 5736	With direct pressure relief valve
EI2(X-100)	30 08 5737	With direct pressure relief valve and auxiliary inlet

4. Outlet section * page 46

TYPE	CODE	DESCRIPTION
RC	30 08 5658	Side outlet
RD	30 08 5721	Upper outlet
RE	30 08 5723	Upper outlet with side carry-over sleeve
RK	30 08 5722	Upper outlet with closed centre
RF	30 08 5725	With ports plugged
RV	30 08 5724	With backpressure valve the combination with electro-hydraulic control is required


NOTE (*) - Items are referred to **BSP** thread.

Valve general informations

Complete sections ordering codes

Configuration with 2 side inlets and mid return manifold

150L GS16 / 2 / AC(X-100) / 18L.P3T / CS1 / ED - 18L.P3T / BC(X-100)



5. Return manifold * page 43

TYPE	CODE	DESCRIPTION
CS1	30 08 5781	Mid return manifold with G3/4 outlet port

6. Right inlet working section *

TYPE	CODE	DESCRIPTION
P-ED-18L	15W010006	Parallel circuit, prearranged for port valves, double acting spool with spring return, lever control
S-ED-18L	15W010004	As previous with series circuit
SP-ED-18L	15W010005	As previous with series-parallel (tandem) circuit

7. Right inlet section *

TYPE	CODE	DESCRIPTION
BC(X-100)	30 08 5755	Side inlet with direct pressure relief valve
BD(X-100)	30 08 5759	Upper inlet with pilot operated pressure relief valve
BC(V)	30 08 5771	Side inlet with valve blanking plug

8. Assemb. kit without intermediate section

CODE	DIRECTIONAL VALVE
30 05 6045	Tie rod kit for 1 section valve
30 05 6049	Tie rod kit for 2 sections valve
30 05 6050	Tie rod kit for 3 sections valve
30 05 6089	Tie rod kit for 4 sections valve
30 05 6090	Tie rod kit for 5 sections valve
30 05 6093	Tie rod kit for 6 sections valve
30 05 6114	Tie rod kit for 7 sections valve
30 05 6115	Tie rod kit for 8 sections valve
30 05 6051	Tie rod kit for 9 sections valve
30 05 6046	Tie rod kit for 10 sections valve
30 05 6047	Tie rod kit for 11 sections valve
30 05 6048	Tie rod kit for 12 sections valve


9. Assemb. kit with intermediate section

CODE	DIRECTIONAL VALVE
30 05 6050	Tie rod kit for 2 sections valve (with CS1)
30 05 6089	Tie rod kit for 3 sections valve (with CS1)
30 05 6090	Tie rod kit for 4 sections valve (with CS1)
30 05 6093	Tie rod kit for 5 sections valve (with CS1)
30 05 6114	Tie rod kit for 6 sections valve (with CS1)
30 05 6115	Tie rod kit for 7 sections valve (with CS1)
30 05 6051	Tie rod kit for 8 sections valve (with CS1)
30 05 6046	Tie rod kit for 9 sections valve (with CS1)
30 05 6047	Tie rod kit for 10 sections valve (with CS1)

NOTE (*) - Items are referred to **BSP** thread.

Parts ordering codes

150L GS16 / AC (X - 100) ELN - MAN14 - 12VDC




Available configurations

AC: with side inlet, for left inlet (standard) directional valve

AD: with upper inlet, for left inlet (standard) directional valve

BC: with side inlet, for right inlet directional valve

BD: with upper inlet, for right inlet directional valve



1. Inlet cover body * page 11

CODE	DESCRIPTION
-	Standard body

2. Parts *

TYPE	CODE	DESCRIPTION
MAN18	30 05 6102	G1/8 Pressure gauge arrangement
MAN14	30 05 6101	G1/4 Pressure gauge arrangement

3. Inlet relief valve options page 12

TYPE	CODE	DESCRIPTION
KE10K01 : direct pressure relief valve type X (X-100)	30 05 4912	Range 20 to 315 bar / 290 to 4600 psi standard setting 100 bar / 1450 psi

KE10K02 : pilot operated pressure relief valve type Z
(Z-100) 30 05 4915 Range 25 to 315 bar / 360 to 4600 psi
standard setting 100 bar / 1450 psi

Standard setting is referred to 6 l/min flow.

V 30 05 4914 Relief valve blanking plug

NOTE (*) - Items are referred to **BSP** thread.

4. Inlet valve options page 14

TYPE	CODE	DESCRIPTION
-	30 05 4914	Relief valve blanking plug (omit in description)
F	-	Inlet anti-cavitation valve
L	-	Hydraulic pilot unloader valve
Solenoid operated unloader valve		
ELN	30 05 6108	Without emergency
ELP	30 05 6109	Push-button emergency
ELT	30 05 6110	Push and twist type with detent emergency

5. Coils



TYPE	CODE	DESCRIPTION
12VDC	20 03 2268	Coil type BER , ISO4400 integrated type 12VDC
24VDC	20 03 2269	Coil type BER , ISO4400 integrated type 24VDC

Inlet section



Dimensional data and hydraulic circuit

For left inlet directional valve (standard)

With side inlet, type AC





With upper inlet, type AD





For right inlet directional valve

With side inlet, type BC



With upper inlet, type BD



Inlet section


Inlet relief options

Direct pressure relief valve

KE10K01 (X - 100)


Standard setting in bar

Adjustment type (X, XH)




Adjustment type


X: with screw




XH: valve set and locked



Performance data



Time response




Inlet section

Inlet relief options

Pilot pressure relief valve


KE10K02 (Z - 100)

Standard setting in bar
Adjustment type (Z, ZH)




Adjustment type



Z: with screw




ZH: valve set and locked



Performance data



V: relief valve blanking plug



Inlet section

Inlet valve options

Unloader valves

Description example: AC (X - 100) **ELN** - **12VDC**



Hydraulic operated valve: **L**
Solenoid operated valve: **ELN**
ELP
ELT

Feeding voltage: for
solenoid operated





Solenoid operated

Emergency with push button and spring return; for detent position turn the button after press it.

WARNING: the manual override option is intended for emergency use, not for continuous duty operation.





Hydraulic operated



Anti-cavitation valve

Description example: AC (X - 100) **F**




Inlet section for special applications


Configuration with rotary commutator

Dimensional data and hydraulic circuit

Drawing and circuit are referred to left inlet directional valve.



Hydraulic circuit and ordering codes



Parts ordering codes (mechanical control)

Description example:

150L GS16 / P - 1 8 L . U 1 (100) *

1.

2.

3.

4.


5.

Port valves setting in bar

1 mounted on A port.

2 mounted on B port.

3 mounted on A and B port.



1. Working section kit *

TYPE	CODE	DESCRIPTION
P	-	With parallel circuit
S	-	With series circuit
SP	-	With series-parallel (tandem) circuit

Include body, seals, rings and load check valve.

2. Spools page 18

TYPE	CODE	DESCRIPTION
1	30 01 3604	Double acting, 3 positions, with A and B closed in neutral position
1A	30 01 3607	Double acting, 3 positions, with A open to tank in neutral position
1B	30 01 3608	Double acting, 3 positions, with B open to tank in neutral position

2. Spools page 18

TYPE	CODE	DESCRIPTION
2	30 01 3605	Double acting, 3 positions, with A and B open to tank in neutral position
3	30 01 3611	Single acting on A, 3 positions, B plugged; requires G3/4 plug (see part a)
4	30 01 3612	Single acting on B, 3 positions, A plugged; requires G3/4 plug (see part a)
2H	30 01 3606	Double acting, 3 positions, with A and B partially open to tank in neutral position
1AH	30 01 3609	Double acting, 3 positions, with A partially open to tank in neutral position
1BH	30 01 3610	Double acting, 3 positions, with B partially open to tank in neutral position

Working section


Parts ordering codes (mechanical control)

2. Spool options page 18			3. "A" side spool positioners page 19		
TYPE	CODE	DESCRIPTION	TYPE	CODE	DESCRIPTION
Special spools for particular positioner kits			Particular positioner kits for special spools		
5DY	30 01 3614	Double acting, 4 positions, float in position 3 with spool in, 13NZ type positioner kit is required	13NZ	30 07 5419	4 positions with spring return in neutral position and detent in pos.3: for 5DY spool
8P	30 01 3613	Double acting 3 positions, regenerative circuit in 3rd position with spool in: need dedicated positioner kit	8CR	30 07 5575	3 positions with spring return in neutral and reduced spool stroke: for 8P spool
3. "A" side spool positioners page 19			4. "B" side options page 32		
TYPE	CODE	DESCRIPTION	TYPE	CODE	DESCRIPTION
8	30 07 5375	With spring return in neutral position	L	30 07 5403	Standard lever box
8D	30 07 5383	As type 8, M8 female threaded pin extension for dual control	LF1	30 07 5405	Lever box with spool stroke limiter in position 1
8D1	30 07 5402	As type 8, pin with Ø 8 mm (0.31 in) radial hole	SL	-	Without lever box
8D2	30 07 5384	As type 8, M8 male threaded pin extension for dual control	SLP	30 07 5406	Without lever box, with dust-proof plate
8TL	30 07 5397	As type 8 with pin control with flexible cable	SLCZ	30 07 5347	Without lever box, with endcap.
8F2	30 07 5377	As type 8 with adjustable stroke limiter	LB	30 07 5407	Steel lever
19	30 07 5436	2 positions, with spring return in neutral position from position 1	LEB	30 07 5409	Safety lever box, vertical configuration
20	30 07 5437	2 positions, with spring return in neutral position from position 2	TQ	30 07 5398	Flexible cable connection; for CG cables
11	30 07 5378	With detent in position 1, neutral and 2	LCB	30 07 5433	Joystick lever for 2 sections operation
12	30 07 5438	Detent in positions 1 and 2			
15	30 07 5439	2 positions, detent in pos. 1 and neutral			
16	30 07 5440	2 positions, detent in pos. 2 and neutral			
17	30 07 5441	With spring return position 1			
18	30 07 5381	With spring return position 2			
17D	30 07 5442	With spring return position 1 and pin with M8 female thread for dual control			
18D	30 07 5382	With spring return position 2 and pin with M8 female thread for dual control			
9B	30 07 5386	With detent in position 1 and spring return in neutral position			
10B	30 07 5387	With detent in position 2 and spring return in neutral position			
11B	30 07 5388	With detent in position 1, 2 and spring return in neutral position			
8MG3(NO)	30 07 5435	As type 8 and operation with microswitch in positions 1 and 2, contact normally open			
8MG3(NC)	30 07 5434	As previous, with contact normally closed			
8P	30 07 5399	ON-OFF pneumatic kit			
8PF	-	Proportional pneumatic kit			
8EP3	30 07 5443	ON-OFF 12VDC electro-pneumatic kit			
	30 07 5400	ON-OFF 24VDC electro-pneumatic kit			
8EP4	30 07 5345	ON-OFF 12VDC electro-pneumatic kit with manifold			
	30 07 5346	ON-OFF 24VDC electro-pneumatic kit with manifold			
8EI3	30 07 5401	ON-OFF 12VDC electro-hydraulic kit			
	30 07 5361	ON-OFF 24VDC electro-hydraulic kit			
8EI3F2	-	12 VDC ON/OFF electrohydraulic kit with adjustable stroke limiter			
-	24 VDC ON/OFF electrohydraulic kit with adjustable stroke limiter				
5. Port valves page 40			6. Complete controls page 37		
TYPE	CODE	DESCRIPTION	TYPE	CODE	DESCRIPTION
Assembled on section			8IM	30 07 5414	-
P3T	30 05 4941	A and B ports valve blanking plugs	R	30 07 5379	-
C	-	Anti-cavitation			
Anti-shock valve					
P	30 05 6196	From 0 to 315 bar / 0 to 4600 psi standard setting 100 bar / 1450 psi			
Anti-shock and anti-cavitation valve					
U	30 05 4938	From 0 to 315 bar / 0 to 4600 psi standard setting 100 bar / 1450 psi			
<i>Standard setting is referred to 6 l/min flow.</i>					
a. "A" and "B" ports plugs			b. Optional handlevers		
TYPE	CODE	DESCRIPTION	TYPE	CODE	DESCRIPTION
G3/4	30 05 4920	For single acting spools type 3 and 4	AL01/M10x200	30 05 4989	Lenght L = 200mm / 7.87in


Proportional hydraulic control type **8IM**, **13IM** and rotative control type **R**.

Spools options


Type 1 (30 01 3604)




Type 1A (30 01 3607)




Type 3 (30 01 3611)




Type 2H (30 01 3606)




Type 1BH (30 01 3610)




Type 5DY (30 01 3614)




Type 2 (30 01 3605)




Type 1B (30 01 3608)




Type 4 (30 01 3612)



Type 1AH (30 01 3609)



Type 8P (30 01 3613)





Working section

"A" side spool positioners

With spring return in neutral position


8 kit (30 07 5375)

It's supplied with standard spring type D (see force-stroke diagram).
It's available with lighter spring type C (8MC) or heavier type E (8ME).




8D kit (30 07 5383)


With M8 female threaded pin extension for dual control.




Spool end joint dimensions (optional)



8D1 kit (30 07 5402)



8D2 kit (30 07 5384)




"A" side spool positioners



With spring return in neutral position

8F2 kit (30 07 5377)



With spool stroke adjustment in position 2 (P → B)




8TL kit (30 07 5397)



19 kit (30 07 5436)



20 kit (30 07 5437)




Working section

"A" side spool positioners


With detent

11 kit (30 07 5378)




Operating features
Locking and release force : 260 N / 58 lbf ±10%

12 kit (30 07 5438)




Operating features
Locking and release force : 260 N / 58 lbf ±10%

15 kit (30 07 5439)



Operating features
Locking and release force : 260 N / 58 lbf ±10%

16 kit (30 07 5440)




Operating features
Locking and release force : 260 N / 58 lbf ±10%


"A" side spool positioners

With spring return


17 kit (30 07 5441)




18 kit (30 07 5381)



17D kit (30 07 5442)



18D kit (30 07 5382)





Working section



"A" side spool positioners

With detent and spring return to neutral position from either directions



9B kit (30 07 5386)



10B kit (30 07 5387)



11B kit (30 07 5388)



Working section

"A" side spool positioners



With microswitch type 8MG3(NO) (30 07 5435)

With spring return in neutral position and microswitch operated in both directions.



Also available **8MG1(NO)** configuration (microswitch operated in position 1) and **8MG2(NO)** configuration (microswitch operated in position 2); dimensions are the same of **8MG3(NO)** configuration.

Same configurations are available with normally closed (NC) contact.

For more information contact Sales Department.



Other configurations



Operating features

MICROSWITCH

Mechanical life

: 5x10⁵ operations



Electrical life (resistive load)

: 5x10⁴ operations 10A / 12VDC

: 5x10⁴ operations 3A / 24VDC

Type 8MG1\MG2(NC-NC) (30 07 5396)

With double microswitch in position 1 and 2.



Positions	A	B
1		
0		
2		

Operating features

MICROSWITCH

Mechanical life

: 5x10⁵ operations

Electrical life (resistive load)

: 5x10⁴ operations 10A / 12VDC



: 5x10⁴ operations 3A / 24VDC

Working section

"A" side spool positioners

ON/OFF pneumatic kit type 8P (30 07 5399)



With spring return to neutral position.



Operating features
Pilot pressure.....: min. 5.5 bar / 80 psi
: max.10 bar / 145 psi

8PF pneumatic proportional kit (30 07 5596)

With spring return to neutral position.




Operating features
Pilot pressure.....: min. 5.5 bar / 80 psi
: max.10 bar / 145 psi


"A" side spool positioners

ON/OFF electropneumatic kit type 8EP3 - 30 07 5443 (12V) - 30 07 5400 (24V)


With spring return to neutral position.



Scheme



Scheme ISO 1219



Operating features

CONTROL


Pilot pressure : 6 bar / 87 psi
: max. 15 bar / 218 psi

COIL


Nominal voltage tolerance : $\pm 10\%$
Power rating : 8 W
Nominal current : 12 VDC
: 24 VDC

Coil insulation : Class H
Weather protection : IP65


ON/OFF electropneumatic kit type 8EP4 - 30 07 5345 (12V) - 30 07 5346 (24V)



Scheme



Scheme ISO 1219




Working section


"A" side spool positioners

ON/OFF electrohydraulic kit type 8EI3 - 30 07 5401 (12V) - 30 07 5361 (24V)


ON/OFF electro-hydraulic control with external pilot and drain.



Scheme



Scheme ISO 1219



Operating features

CONTROL

Pilot pressure : min. 10 bar / 145 psi
: max. 50 bar / 725 psi
Max. backpressure on drain L : 25 bar / 360 psi


COIL

Nominal voltage tolerance : ±10%
Power rating : 21 W
Nominal current : 1.75 A - 12 VDC / 0.87 A - 24 VDC
Coil insulation : Class F
Weather protection : IP65


"A" side spool positioners

ON/OFF electrohydraulic kit type 8EI3F2


Collector kit with pilot and drain lines with stroke limiter



Scheme



Scheme ISO 1219



Operating features

CONTROL

Pilot pressure	: min. 10 bar / 145 psi
	: max. 50 bar / 725 psi
Max. backpressure on drain L	: 25 bar / 360 psi

COIL


Nominal voltage tolerance	: $\pm 10\%$
Power rating	: 21 W
Nominal current	: 1.75 A - 12 VDC / 0.87 A - 24 VDC
Coil insulation	: Class F
Weather protection	: IP65

Working section

"A" side spool positioners

ON/OFF electrohydraulic kit type 8EI3

Collector kit for external pilot and drain



Description example :
150L GS16/2/AC(X-100)/18EI3L/18EI3L/RC-KE2S0-24VDC


COLLECTOR KIT CODES		
Type	Code	Description
KE1S0	30 07 5537	Kit one section
KE2S0	30 07 5532	Kit for 2 sections
KE3S0	30 07 5533	Kit for 3 sections
KE4S0	30 07 5534	Kit for 4 sections
KE5S0	30 07 5535	Kit for 5 sections
KE6S0	30 07 5536	Kit for 6 sections
KE7S0	--	Kit for 7 sections

"A" side spool positioners

ON/OFF electrohydraulic kit type 8EI3

Collector kit with pilot and drain lines

The kit include collector, VRP pressure reducing valve and pipes.



Operating features

VRP VALVE
Output pressure : 25 bar / 363 psi
Max. flow : 8 l/min
Filtering : 80 µ

Description example :
150L GS16/2/AC(X-100)/18EI3L/18EI3L/RV-KE2R3-24VDC


Description type for outlet
cover with VRE valve.

COLLECTOR KIT CODES

Type	Code	Description
KE1R3	30 07 5500	Kit one section
KE2R3	30 07 5507	Kit for 2 sections
KE3R3	30 07 5508	Kit for 3 sections
KE4R3	30 07 5509	Kit for 4 sections
KE5R3	30 07 5510	Kit for 5 sections
KE6R3	30 07 5511	Kit for 6 sections

VRE backpressure valve

Valve is assembled on flow through passage of outlet cover; it's necessary to provides pilot pressure to the actuator.
RV complete (with backpressure valve and tapered plug)




Working section

"A" side spool positioners

Particular positioner kits for special spools


8CR kit (30 07 5575)

3 positions with spring return in neutral and reduced spool stroke: **for 8P spool.**



13NZ kit (30 07 5419)

4 positions with spring return in neutral and detent in position 3: **for 5DY spool.**




"B" side options


Lever control

Type L (30 07 5403)

Alluminium lever pivot box with protective rubber bellow; it can be roated 180° (configuration **L180**).




configuration L180




Type LF1 (30 07 5405)

With spool stroke adjustment in position 1 (P → A).



Type SLP (30 07 5406)

Mechanical control with dust-proof plate kit.



Working section



"B" side options

Lever control

Type LB (30 07 5407)

Steel manufacture.
Pivot can be assembled below (LB1 configuration) or above (LB3 configuration).

1	0	2
---	---	---




"B" side options

Safety lever control

Safety levers with lock in neutral complete with handlever; lift handlever knob to operate.
With insulated handlever type **LEBP**

Type LEB (30 07 5409)




Working section


"B" side options

Controls prearrangement

Type SL




Type SLCZ (30 07 5347)



Protection cap usable with pneumatic, electropneumatic, and electrohydraulic spool positioners.


TQ cable remote control kit (30 07 5398)

Waterproof cap prearranged for remote control with flexible cable.




"B" side options

LCB mechanical joystick for two sections control (30 07 5433)



Dimensions and movement scheme




Working section


Complete controls

Proportional hydraulic control type 8IM (30 07 5414)

It can be used with standard spools and body



Connection example




Working section

Complete controls

Proportional hydraulic control type 13IM (30 07 5421)

It can be used with floating spools and special body kit



Operating features

Pilot pressure : max. 50 bar / 725 psi


Internal leakage A(B) → T ($\Delta p = 100 \text{ bar} - 1450 \text{ psi}$ / $T = 40^\circ\text{C}$)

.....: max. $6 \text{ cm}^3/\text{min} - 0.37 \text{ in}^3/\text{min}$

Performance data

Pressure - stroke diagram


Max. pilot pressure 30 bar - 435 psi.



Working section

Special configurations

Directional valve with rotary control kit (30 07 5379)






Port valves

Anti - shock valves


P 1 (100)

Standard setting in bar

- 1 mounted on port A.
- 2 mounted on port B.
- 3 mounted on ports A and B.



Valve type



Performance data




Working section

Port valves


Antishock and anticavitation valves

U 1 (100)


- Standard setting in bar
- 1 mounted on port A.
- 2 mounted on port B.
- 3 mounted on ports A and B.



Valve type



Performance data (Antishock and anticavitation valves)







Port valves

Anticavitation valves

C 1




- 1 mounted on port A.
- 2 mounted on port B.
- 3 mounted on ports A and B.



Valve blanking plug with tank connection

DST 1





- 1 mounted on port A.
- 2 mounted on port B.



Valve blanking plug

P 1 T


- 1 mounted on port A.
- 2 mounted on port B.
- 3 mounted on ports A and B.




Intermediate section

CS1 mid return manifold

Mid return manifolds for directional valve with left and right inlet both; they allow 2 independent circuits with common outlet.



Hydraulic circuit




Description example:
150L GS16/2/AC(X-100)/18L/ CS1/ED-18L/BC(X-100)


Intermediate section

DFG pressure compensated flow divider section

The flow on the downstream sections can be adjusted from 0 to 150 l/min. by means of graduated handwheel; exceeding setting flow goes to tank.



Hydraulic circuit



Description example:

150L GS16/2/AC(X-100)/18L/ DFG/18L/RC

Intermediate section


Service relief valve section

EI configuration

The operation of up stream section exclude the EI downstream section.


The pressure of the downstream sections should be adjusted at least 20 bar below the relief valve setting.

Execution EI2, without plug, is prearranged for a second inlet.



Description example:

150L GS16/2/AC(X-100)/18L/EI1(X-100)/18L/RC



Description example:

150L GS16/2/AC(X-100)/18L/EI2(X-100)/18L/RC

Parts ordering codes

Ordering example:

150L GS16 / RC



Available configurations

RC: side outlet


RD: upper outlet

RE: upper outlet with side carry-over

RK: upper outlet and closed centre

RF: With ports plugged

RV: With backpressure valve: **to be used together with the electro-hydraulic control**




1. Complete outlet cover *			2. Circuit options *			
TYPE	CODE	DESCRIPTION	TYPE	CODE	QTY	DESCRIPTION
RC	30 08 5658	Side outlet	-	30 05 4918	1	G 3/8 plug for carry-over (RE), carry-over with backpressure valve (RV) and closed centre (RK) options
RD	30 08 5721	Upper outlet	VRE	30 05 4905	1	VRE backpressure valve for RV configuration
RE	30 08 5723	Upper outlet with side carry-over sleeve	-	30 05 4993	1	Plug G1
RK	30 08 5722	Upper outlet with closed center				
RF	30 08 5725	With ports plugged				
RV	30 08 5724	With backpressure valve				


NOTE (*) - Items are referred to **BSP** thread.

Outlet section


Dimensional data and hydraulic circuit




Type RC




Type RD




Type RF




Type RV



Type RE




Type RK



Sectional drawing

When hand lever pushed (spool out position) P to A port. B to T port.



When hand lever pulled (spool in position) P to B port. A to T port.

