

Description

DS1 Series Pressure Switch opens and closes electrical circuit depends on pressure increase or decrease. Working pressure is adjustable between 0,2 bar and 400 bar. System has adjustable feature while system is working. They can be used under all compressed air, liquids or gases.

- Compact and economic design
- NA/NC Socket
- Reproducibility of pressure switch in %3
- NBR, HNBR, VITON seal equipment.
- Body material stainless steel, brass, steel options.

Applications

- Hydraulic and mobile hydraulic
- Pneumatics
- Heavy Duty
- All compressed air, liquids or gases.



Technical Features

Mechanical Connection	: G1/4" , G1/8" , 1/4" BSPT , 1/8" BSPT , M10x1,0 , M12 x 1,5 , 1/8" NPT , 1/4" NPT
Reproducibility	: Reproducibility of adjusted pressure in %3
Working Temperature	: -40 °C...+85 °C
(DIN EN 60068-2-27)	: 20 g (Test Time 30 min)
Shock Test (DIN EN 60068-2-27:1993)	: 30 g
Working Cycle	: 5 000 000 Cycle
Viscosity	: Between 10 ... 800 mm2/sec
Electrical Connection Feature	: 250 VAC 5A

Notes

These values are maximum values and they can not be used at the same me.

When you need to use the pressure switch in aggressive chemicals or fluids please contact with us.


You must stict to rules of clearence standarts Hydraulic oils (fluids). Use filteraon to blocking system errors. It is effecve for long working life of pressure switches. Please avoid using out of indicated values to have a long service from pressure switch

Order Codes

Model	Body	Sealing Type	Mechanical Connection	Pressure			Set Pressure	Pressure Condition
				Code	Pressure Range (bar)	P _{max}		
DS1 Model Pressure Switch	Y Pirinç "MS58"	V VITON	A3 G1/4"					
	E EPDM		A4 G1/8"					
	Z Paslanmaz "316 L"	H HNBR	S3 1/4" BSPT					
			S4 1/8" BSPT	002	0,2 ... 2	40 bar	If you need a product that adjusted before, you can write pressure value here.	D <i>Dropping set pressure</i> Y <i>Rising set pressure</i>
			B1 M10 x1,0	012	1 ... 12	40 bar		
			B3 M12x1,5	100	5 ... 100	600 bar		
			N3 1/8"NPT	200	20 ... 200	600 bar		
			N4 1/4"NPT	400	50 ... 400	600 bar		
	If you do not indicate any body type, It is delivered as zinc-plated stainless body.	If you do not indicate any leakageproof type, It is delivered as "NBR"						If you indicated set pressure please indicate the pressure condition

Note:
Minimum order pieces of all product whic is beginning with DS1 A3 ... codes. Order pieces must be 10 and multiples of 10.

Electrical Connection Types




- Switch Function:
- Terminal 1 - 2 :It has current in case of pressure increases. (NA)
 - Terminal 1 - 3 :It has current in case of pressure decreases or there is no pressure.(NC)


Electrical Connection	3-TERMINAL
Maximum Touching Surface	0,5mm²
Minimum Current	1mA 12 VDC
Maksimum Current	3A 130 VAC
Cable Length	2 meter

Pressure Differential Difference Graphics

Working Pressure : Adjustable between 0,2 bar 2 bar.
System pressure Max. (Pmax) : 40 bar
Type : Diaphragm




Working Pressure : Adjustable between 1 bar 12 bar .
System Pressure Max. (Pmax) : 40 bar
Type : Diaphragm




Pressure Differential Difference Graphics

Working Pressure : Adjustable between 10 bar 100 bar.
System pressure Max. (Pmax) : 600 bar
Type : Piston




Working Pressure : Adjustable between 20 bar 200 bar .
System Pressure Max. (Pmax) : 600 bar
Type : Piston



Pressure Differential Difference Graphics

Working Pressure : Adjustable between 20 bar 400 bar.
System pressure Max. (Pmax) : 600 bar
Type : Piston



Technical Dimensions

