

Product Datasheet model uvex i-guard+ 9143 300

**UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth**

1. Product Characteristics

- versatile 3in1 safety eyewear range – allows eyewear to be adapted according to workplace hazards
- interchangeable side arms and headband means eyewear can be worn as either a spectacle or goggle depending on the workplace hazards
- large, flat lens delivers unrestricted field of vision
- x-tended sideshield offers additional protection from hazards
- soft, flexible face seal adapts to the wearer providing both protection and comfort. It also protects against droplets or splashes of liquids and large dust particles (markings 3 and 4)
- increased impact protection – marking B
- individually adjustable headband and side arms with multi-incline points for a perfect fit and secure hold
- robust polycarbonate lens with uvex's proven supravision coating technology – permanent anti-fog and scratch-resistant lens
- UV400 – 100 % protection against dangerous UV radiation up to 400 nm
- metal-free

2. Technical Details Body

Face seal

Material	TPE, recycled
Colour	anthracite

Headband

Material	textile headband
Features	individually adjustable
Colour	blue, anthracite

Headband hooks

Material	PC-PBT
Colour	anthracite

Marking

Manufacturer 's ID code	W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid) 4 (large dust particles)
Impact resistance	B (120 m/s)
Conformity symbol	CE

Temple

Material	PC-PBT
Features	side arms with multi-incline points
Colour	anthracite, blue

Marking






Manufacturer 's ID code	W
Applicable EN norm	166
Field of use	3 (drops and splashes of liquid) 4 (large dust particles)
Impact resistance	F (45 m/s)
Conformity symbol	CE

3. Technical Details Lens

Material	PC
Thickness	2.35 mm at PD
Coating	uvex supravision excellence
Colour	clear
UV protection	UV400
Marking	
Filter	2C-1.2 (EN 170)
Manufacturer 's ID code	W
Optical class	1
Impact resistance	B (120 m/s)
Scratch resistance	K
Antifog	N
Conformity symbol	CE
Factory symbol	

4. Logistical Information

Product

Weight	50g		
Dimensions (L x W x B) in approx. mm	 		
	55 x 150 x 60		
	Packing unit 1	Packing unit 2	Packing unit 3
EAN Code	4031101944258	4031101958958	4031101958965
Quantity in pcs.	1	8	128
Dimensions (L x W x H) in approx. mm	 picture only for reference		
	70 x 150 x 70	185 x 290 x 97	600 x 400 x 400
Net weight in approx. g	56	448	7,170
Gross weight in approx. g	72	680	11,780
Country of Origin	Germany		

5. Miscellaneous

Standards	EN 166 + EN 170
PPE Category	Category II