


C - (COPPER) PROCESS TUBE
GAGE I.D. TO 6.45-6.55
× 15.00-17.00 DEEP.

— D - (COPPER) DISCHARGE TUBE
GAGE I.D. TO 4.92-5.02
x 15.00-17.00 DEEP.



- NOTES:
- 1- IF SPECIFIED IN BM. ASSEMBLE PARTS AS SHOWN.
 - 2- SEE SPEC. "A-B" & A-C FOR PROCESS.
 - 3- THERE CAN BE NO CREASES IN THE TUBES. (CREASES ARE SIGNS OR MARKS THAT ARE IN SOMETHING THAT BENDS)
 - 4- AFTER THE FOLDS IN THE TUBES, CANNOT BE ACCELERATED TO AREA EXCEEDING 30%.
 - 5- TUBES OF SUCTION, DISCHARGE AND PROCESS MUST BE FREE OF INK ON 15.8mm (5/8") FROM TOP OF THE TUBES AS SPEC. T.P.Co. A-B4.
 - 6- FOR SUPPLIER ENVIRONMENTAL REGULATORY REQUIREMENTS, SEE TECUMSEH GLOBAL SPEC. 08.

THIRD ANGLE PROJECTION  UNITS: mm DRAWING SIZE: A2	 tecumseh	
Q. A, SYMBOLS AS PROCEDURE 2.01,031 TECUMSEH OF BRAZIL		
NAME SALES COMPRESSOR PART NO. DCAE132		
DWN. J. BARBANO	CK. ANDRE MARTINEZ	APPR. WALTER CORREA
DATE 09/06/11	REF.	SCALE 1:2 FAMILY A2