

Product Datasheet model i-3 9190 885



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189,
D-90766 Fürth

Product characteristics	* Innovative protective spectacle, perfectly fit the face * Individually adjustable side arms with variable inclination * Integrated Softflex zone ensures outstanding wearer comfort for all head sizes * Softflex adjustable nose piece ensures comfortable, pressure-free fit and remains firmly in place * Soft ear and Softflex bridge pieces ensure a secure fit in any situation
Technical details Frame Material Features Colour	Front piece/Temple TPU/TPE variable inclination, individually adjustable black-light grey

Manufacturer's ID code	Marking W
Applicable EN norm	166
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Conformity symbol	CE
Lens	
Material	PC
Thickness	2,2 mm
Coating	Antifog on the inside
Colour	dark silvermirror
Filter	Marking 5-3,1 (DIN EN 172)
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Conformity symbol	CE
Miscellaneous	
Weight	30g
Packing	5 spectacles per box
	160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 172